

1643

3A-30-045-21665

300-30-045-26897

E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO  
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit I Sec. 15 Twp 30 Rng 8

Name of Well/Wells or Pipeline Serviced HOWELL K #300, #3A  
cps 1056w

Elevation 6436' Completion Date 5/31/89 Total Depth 520' Land Type\* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used  
N/A

Depths & thickness of water zones with description of water when possible:  
Fresh, Clear, Salty, Sulphur, Etc. DAMP AT 150' & 250'

Depths gas encountered: N/A

Type & amount of coke breeze used: N/A

Depths anodes placed: 450', 440', 300', 290', 280', 270', 260', 250', 240', 200'

Depths vent pipes placed: 501' OF 1" PVC VENT PIPE

Vent pipe perforations: BOTTOM 350'

Remarks: gb #2

RECEIVED

MAY 31 1991

OIL CO.

DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

\*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  
If Federal or Indian, add Lease Number.

3A-30-045-21665  
300-30-045-26897

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO  
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SE Sec. 15 Twp 30 Rng 8

Name of Well/Wells or Pipeline Serviced HOWELL K #3A, #300

cps 1056w

Elevation 6436' Completion Date 9/8/76 Total Depth 698' Land Type\* N/A

Casing, Sizes, Types & Depths 23' 3" OF 8 5/8 CASING

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. WET AT 430'

Depths gas encountered: N/A

Type & amount of coke breeze used: 70 SACKS

Depths anodes placed: 685', 675', 665', 655', 645', 635', 625', 505', 495', 455'

Depths vent pipes placed: N/A

Vent pipe perforations: 271'

Remarks: gb #1

RECEIVED

MAY 31 1991

OIL CON.

If any of the above data is unavailable, please indicate so. <sup>1</sup> <sup>2</sup> <sup>3</sup> Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

\*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  
If Federal or Indian, add Lease Number.