

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

30-039-21718

Operator. UNOCAL - Bloomfield, NM Location: Unit Sec. 17 Twp. 27N Rng. 6W

Name of Well/Wells or Pipeline Served: RINCON UNIT 81AMV

Elevation: 6577 GR Completion Date: 11/07/96 Total Depth: 340' Land Type* F

Casing, Sizes, Types & Depths: NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used: NONE

Depths & thickness of water zones with description of water when possible:

WATER AT 110'

Fresh, Clear, Salty, Sulfur, Etc : CLEAR

Depths gas encountered. NONE

Type & amount of coke breeze used 2500 LBS , SWB METALURGICAL PETROLEUM COKE

Depths anodes placed: 130' 140' 150' 160' 170' 180' 190' 200' 210' 220' 230' 240'

Depths vent pipes placed: 0' - 340', 1" PVC

Vent pipe perforations: 1/8" PERFORATIONS FROM 100' TO 300'

Remarks SECOND GROUND BED INSTALLED ON THIS LOCATION

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analysis & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian, S-State; P-Fee
If Federal or Indian, add Lease Number

RECEIVED
DEC - 5 1996

OIL CON. DIV.
DIST. 3

RECEIVED
NOV 27 1996

OIL CON. DIV.
DIST. 3

COMPANY: Unocal DATE: 11-7-96
 WELL: Rincon 81A PIPELINE:
 LOCATION: 1/4 1/4 SEC. 17-27-6 STATE: N.M. Rio Arriba
 GROUND BED: DEPTH: 340' DIAMETER: 6 3/4" BACKFILL: Metolergies ANODES TYPE: Durachlor 51

DEPTH FT.	DRILLERS LOG	ANODE LOG			ANODE DEPTH	REMARKS
		Logged	Coked	R		
20	<i>Sand</i>					
30	<i>Sand Stone</i>					
40						
50						
60						
70						
80						
90						
100	<i>Sand Stone</i>					
110		.6				<i>Water</i>
120		.6				<i>Coke Breeze</i>
130	<i>Shale</i>	1.3	2.9		130'	
140		1.0	2.6		140'	
150		1.9	4.0		150'	
160		1.6	3.4		160'	
170	<i>Sandy Shale</i>	.8	2.1		170'	
180		.9	2.2		180'	
190		1.0	2.6		190'	
200	<i>Shale</i>	1.6	3.0		200'	
210		1.9	4.6		210'	
220		1.5	2.4		220'	
230		.8	1.9		230'	
240		1.2	2.2		240'	
250	<i>Sandy Shale</i>	.5				
260		.7				
270		.5				
280	<i>Sand Stone</i>	.2				
290		.3				
300		.3				
310		.2				
320		.2				
330		.3				
340		.3				
350						

NOTES:

POWER SOURCE: Batteries VOLTS: 9.1
 INDICATE WATER ZONE DEPTHS 110'
 CASING RUN: YES / ☒ NO TYPE: _____ DEPTH: _____ CEMENTED: YES / ☒ NO
 ISOLATION PLUGS SET: YES / ☒ NO IF SO, WHERE: _____
 TOTAL: AMPS 9.1 RESISTANCE: 1