

3560 30-045-09519

7

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL INC. Location: Unit NE Sec. 14 Twp 30 Rng 8

Name of Well/Wells or Pipeline Serviced HOWELL E #2

cps 2096w

Elevation 5704' Completion Date 11/21/61 Total Depth 19' EA Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. N/A

Depths gas encountered: N/A

Type & amount of coke breeze used: 204 lbs, 248 lbs, 158 lbs, 114 lbs, 158 lbs

Depths anodes placed: 8', 13', 10', 9', 10'

Depths vent pipes placed: N/A

Vent pipe perforations: N/A

Remarks: Wb #1 CONVENTIONAL BEDS. RETIRED.

RECEIVED
MAY 31 1991
OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

SAN JUAN DIVISION
WELL CASING CATHODIC PROTECTION
DAILY CONSTRUCTION
PROGRESS REPORT

DATE 11-21-61

WELL NAME - Howell #2 (14-30-8) WORK ORDER NO. 184-51029-50-10

NUMBER AND DEPTH OF HOLES: #1 19', #2 19', #3 20', #4 19', #5 19'.

DEPTH OF EACH ANODE: #1 8', #2 13', #3 10', #4 9', #5 10', #6 , #7

#8 , #9 , #10 .

ANODE RESISTANCES: #1 7.5, #2 6.7, #3 7.3, #4 7.3, #5 6.2, #6 , #7

#8 , #9 , #10 .

TOTAL CIRCUIT RESISTANCE: 3.0 OHMS.

DRILLING LOG: (ATTACH HERETO)

AMOUNT OF COKE BREEZE PLACED IN EACH HOLE: #1 204 lbs, #2 248 lbs, #3 158 lbs

#4 114 lbs, #5 158 lbs

ANY DIFFICULTIES ENCOUNTERED IN DRILLING:

ROCKS- Gravel & Boulders AT 20'

LOST CIRCULATION-

CASING INSTALLED-

DATE ALL CONSTRUCTION COMPLETED .

REMARKS:

I switched to conventional Bed

Three anodes = 3.8 Ω

Four anodes = 3.4 Ω

*Insulating union on
Dehydrator*

① - ② ③ ④ ⑤

0 ← Pole

↓
N



Edward R. Paulk
SIGNATURE OF INSPECTOR

5704

	LEASE	WELL NO.	CONTRACTOR	RIG NO.	REPORT NO.	DATE
MORNING						
DAYLIGHT						
EVENING						

[illegible]

SIGNED: Toolpusher

Company Supervisor