

#6 30-039-21371

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit A Sec. 25 Twp 24 Rng 06

Name of Well/Wells or Pipeline Serviced _____

CANYON LA 190 UNIT #6

Elevation 6646 Completion Date 8/14/93 Total Depth 396' Land Type F

Casing Strings, Sizes, Types & Depths 6/8 SET 59' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 12 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 120', AND MORE WATER

AT 185'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 396' DEPTH.

USED 108 SACKS OF ASBURY 218R (5400#)

Depths anodes placed: 385', 360', 350', 343', 336', 330', 324', 295', 289', 283', 277', 268', 230', 160', +140'

Depths vent pipes placed: SURFACE TO 396'.

Vent pipe perforations: BOTTOM 280'.

Remarks: _____

RECEIVED

JAN 31 1994

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.