

#64 30-039-07105  
#86 30-039-07114

**DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO**

Operator MERIDIAN OIL CO. Location: Unit M Sec. 9 Twp 27 Rng. 5

Name of Well/Wells or Pipeline Serviced SAN JUAN 27 - 5 # 86 & 64

CDS 745w

Elevation 6726 Completion Date 10/3/90 Total Depth 360 Land Type N/A

Casing Strings, Sizes, Types & Depths 20 ft. 8" PVC Casing

If Casing Strings are cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used  
N/A

Depths & thickness of water zones with description of water: Fresh, Clear,  
Salty, Sulphur, Etc. wet at 55 & 80 ft., hit water at 350 & got a sample

Depths gas encountered: N/A

Ground bed depth with type & amount of coke breeze used: 4400 lbs.

Depths anodes placed: 330, 320, 310, 300, 290 280, 250, 215, 205, 195

Depths vent pipes placed: 360 ft. 1" PVC Vent Pipe

Vent pipe perforations: 280 ft. perforated

Remarks: gb #2

**RECEIVED**

MAY 31 1991

OIL CON.

DIST.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  
If Federal or Indian, add Lease Number.

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO  
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SW Sec. 9 Twp 27 Rng 5

Name of Well/Wells or Pipeline Serviced SAN JUAN 27-5 UNIT #64, #86

cps 745w

Elevation 6726' Completion Date 4/12/66 Total Depth 340' Land Type\* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used  
N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. WET TO 60'

RECEIVED  
MAY 31 1991

Depths gas encountered: N/A

Type & amount of coke breeze used: 5625 lbs.

OIL CON. DIV  
DIST. 3

Depths anodes placed: 310', 304', 298', 292', 284', 278', 265', 254', 248'

Depths vent pipes placed: 310' OF 3/4" PLASTIC HOSE

Vent pipe perforations: BOTTOM 65'

Remarks: gb #1

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

\*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  
If Federal or Indian, add Lease Number.