DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO (Submit 3 copies to OCD Aztec Office)

| Operator MERIDIAN OIL | Location: Unit M Sec. 5 Twp 27 Rng 5 |
|---|---|
| Name of Well/Wells or Pipeline Serv | riced SAN JUAN 27-5 UNIT #53. #85 |
| | cps 740w |
| Elevation 6660' Completion Date 8/17/82 | Total Depth 260' Land Type* N/A |
| Casing, Sizes, Types & Depths N/ | 1 |
| If Casing is cemented, show amounts | & types used N/A |
| If Cement or Bentonite Plugs have b | een placed, show depths & amounts used |
| Depths & thickness of water zones w | ith description of water when possible: |
| Fresh, Clear, Salty, Sulphur, Etc | 60' SAMPLE TAKEN REGENCE |
| Depths gas encountered: N/A | MAY 3 1 1991 |
| Type & amount of coke breeze used: | OII CON DIV |
| | ', 185', 145', 125', 115', 105', 95', 85' |
| Depths vent pipes placed: 255' OF | 1" PVC VENT PIPE |
| Vent pipe perforations: BOTTOM | 200' |
| Remarks: gb #2 | |
| | |
| | |

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

^{*}Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO (Submit 3 copies to OCD Aztec Office)

| Operator MERIDIAN OIL Location: Unit SW Sec. 5 Twp 27 Rng 5 |
|--|
| Name of Well/Wells or Pipeline Serviced SAN JAUN 27-5 UNIT #53, #85 |
| cps 740w |
| Elevation 6660' Completion Date 4/5/66 Total Depth 260' Land Type* N/A |
| Casing, Sizes, Types & Depths N/A |
| |
| If Casing is cemented, show amounts & types used N/A |
| |
| If Cement or Bentonite Plugs have been placed, show depths & amounts used |
| N/A |
| Depths & thickness of water zones with description of water when possible: |
| Fresh, Clear, Salty, Sulphur, Etc. 60' TO 80' |
| DEGET WITH |
| Depths gas encountered: N/A MAY 3 1 1991 |
| Type & amount of coke breeze used: 4625 lbs. |
| DIS Depths anodes placed: 214', 208', 202', 196', 120', 114', 108', 102', 77' |
| Depths vent pipes placed: 214' OF 3/4" PLASTIC HOSE |
| Vent pipe perforations: BOTTOM 60' FROM 85' TO 125' |
| Remarks: gb #1 |
| |

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

^{*}Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.