

43 30-039-07860
442 30-039-24460

Exhibit D

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator MERIDIAN OIL CO. Location: Unit A Sec. 13 Twp. 30 Rng. 6

Name of Well/Wells or Pipeline Serviced SJ 30-6 #43, #442

cps 189w

Elevation 6349' Completion Date 10-22-90 Total Depth 340' Land Type N/A

Casing Strings, Sizes, Types & Depths 20 feet of 8" PVC casing

If Casing Strings are cemented, show amounts & types used 1 bag cement

If Cement or Bentonite Plugs have been placed, show depths & amounts use

N/A

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 70 feet No water sample

Depths gas encountered: N/A


Ground bed depth with type & amount of coke breeze used: 150 feet with
Petroleum coke breeze.

Depths anodes placed: 305, 290, 255, 245, 235, 225, 215, 205, 195, 185

Depths vent pipes placed: 340 feet

Vent pipe perforations: 260 feet

Remarks: qb #3



If any of the above data is unavailable, please indicate so. Copies of a logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Private.
If Federal or Indian, add Lease Number.

443 30-039-07860

442 30-039-24460

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit NE Sec. 14 Twp 30 Rng 6

Name of Well/Wells or Pipeline Serviced SAN JUAN 30-6 UNIT #43, #442

cps 189w

Elevation 6349' Completion Date 6/10/69 Total Depth 640' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. 280'

Depths gas encountered: N/A

Type & amount of coke breeze used: 8550 lbs.

Depths anodes placed: 522', 516', 416', 410', 404', 398', 392', 386', 376', 311'

Depths vent pipes placed: 516' OF 3/4" HOSE

Vent pipe perforations: 470'

Remarks: gb #2 STYROFOAM MOLD USED ON CAPPING 7 ANODES. MASKING TAPE USED ON

CAPPING 3 ANODES.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

43 30-039-07860

442 30-039-24460

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit NE Sec. 14 Twp 30 Rng 6

Name of Well/Wells or Pipeline Serviced SAN JUAN 30-6 UNIT #43, #442

189w

Elevation 6349 Completion Date 4/29/63 Total Depth 140' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. N/A

Depths gas encountered: N/A

Type & amount of coke breeze used: 1105 lbs.

Depths anodes placed: 123', 117', 80', 74', 68'

Depths vent pipes placed: N/A

Vent pipe perforations: N/A

Remarks: qb #1

RECEIVED

MAY 31 1991

OIL CON. D"
DIS

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.