

30-045-28970

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit G Sec. 30 Twp 28 Rng 11

Name of Well/Wells or Pipeline Serviced \_\_\_\_\_

RHodes C#100

Elevation \_\_\_\_\_ Completion Date 9/9/93 Total Depth 485' Land Type I

Casing Strings, Sizes, Types & Depths 7/8 SET 59' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 12 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. HIT A DAMP LAYER AT 85' AND FRESH WATER AT 215'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 485' DEPTH.

USED 140 SACKS OF ASBURY 218R (7000#)

Depths anodes placed: 475' 468' 461' 454' 445' 438' 432' 382' 376' 343' 333' 307' 164' 153' + 130'

Depths vent pipes placed: SURFACE TO 485'

Vent pipe perforations: BOTTOM 370'

Remarks: \_\_\_\_\_

RECEIVED  
JAN 31 1994  
OIL CON. DIV.  
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.