

District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources

Form C-144
June 1, 2004

Oil Conservation Division

1220 South St. Francis Dr.
Santa Fe, NM 87505

For drilling and production facilities, submit to
appropriate NMOCD District Office
For downstream facilities, submit to Santa Fe
office

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes ☒ No ☐
Type of action: Registration of a pit or below-grade tank ☐ Closure of a pit or below-grade tank ☒

Operator ConocoPhillips Telephone 505-326-9700 e-mail address monrotn@conocophillips.com
Address 3401 E 30TH STREET, FARMINGTON, NM 87402 Formation PC
Facility or well name Gobernador 3 API # 30-039-21783 U/L or Qtr/Qtr M Sec 14 T 29N R 5W
County Rio Arriba Latitude 36 72139 Longitude 107 331497 NAD 1927 ☒ 1983 ☐ Surface Owner Federal ☒ State ☐ Private ☐ Indian ☐

Pit

Type: Drilling ☒ Production ☐ Disposal ☐
Workover ☒ Emergency ☐
Lined ☒ Unlined ☐
Liner type: Synthetic ☐ Thickness 12 mil Clay ☐
Pit Volume _____ bbl

Below-grade tank

Volume: _____ bbl Type of fluid: _____
Construction material: _____
Double-walled, with leak detection? Yes ☐ If If not, explain why not.

Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)

Less than 50 feet
50 feet or more, but less than 100 feet
100 feet or more

(20 points)
(10 points)
(0 points)

0

Wellhead protection area. (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)

Yes
No

(20 points)
(0 points)

0

Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses)

Less than 200 feet
200 feet or more, but less than 1000 feet
1000 feet or more

(20 points)
(10 points)
(0 points)

10

Ranking Score (Total Points)

10

If this is a pit closure: (1) attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location (check the onsite box if you are burying in place) onsite ☒ offsite ☐ If offsite, name of facility _____. (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No ☒ Yes ☐ If yes, show depth below ground surface _____ ft and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations. (6) The pit was closed on 4/28/07

Additional Comments:

Lined per BLM requirements.

RCVD MAY 19 '08

OTI CONS. DIV.
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☒, or an (attached) alternative OCD-approved plan ☐.

Date: 5/15/2008

Printed Name/Title Tracey N. Monroe/ Regulatory Tech

Signature

Tracey N. Monroe

Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.

Approval.

Deputy Oil & Gas Inspector,
District #3

Printed Name/Title

Signature

Bob Bell

Date:

MAY 30 2008

MESAVERDE/DAKOTA LAYOUT

Goforwarder #3

CLOSED 4/28/07

APPROXIMATE
15'x75'
PIT AREA
LINED WITH
12 MIL. POLY. LINER

4' HIGH WALL
FROM BOTTOM
OF BLOW PIT

1' HIGH BERM

RAMP INTO PIT
CONSTRUCTED
FROM PAD GRADE
TO THE BOTTOM
OF FLARE AREA

Positive drain
to reserve pit.

RIG ANCHOR

6' DEEP

3' DEEP

1' DEEP

20'

15'

35'

70'

DIKE

10' Deep

2:1 Slopes Reserve Pit

100'

RIG ANCHOR

REAR

Wellhead to back

140'

LAYDOWN

Wellhead to front

160'

130'

Wellhead to side

130'

RIG ANCHOR

N

130'

50'
CONSTRUCTION ZONE

PIT CROSS SECTION

