Form 3160-5 (April 2004)

1

RECEIVED

UNITED STATES DEPARTMENT OF THE INTERIORY 2 3 2008 BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS Office

Do not use this form for proposals to drill or to re-enter an

FORM APPROVED
OM B No 1004-0137
Expires, March 31, 200

	Expires.	Marc	h 31	, 20
Lease Seria	al No			

14-20-603-1371

6.	If Indian, Allottee or Tribe Name	

abandoned well. Use Form 3160-3 (APD) for such proposals.	NAVAJO ALLOTTEE #011156		
SUBMIT IN TRIPLICATE- Other instructions on reverse side.	7. If Unit or CA/Agreement, Name and/or No.		
Type of Well Gas Well Other	8. Well Name and No. NAVAJO 11 #05		
Name of Operator NOBLE ENERGY, INC. Address 3b. Phone No. (include area code) 5802 US HIGHWAY 64 FARMINGTON, NM 87402 505-632-8056	9. API Well No. 30-045-34161 10 Field and Pool, or Exploratory Area		
Location of Well (Footage, Sec., T, R, M, or Survey Description) 1980' FNL, 660' FWL E Sec 11 - T25N - R10W	Basin Dakota/BasinMancos 11. County or Parish, State SAN JUAN CTY, NEW MEXICO		
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, R	EPORT, OR OTHER DATA		
TYPE OF SUBMISSION TYPE OF ACTION			
Acidize Deepen Production (State Alter Casing Fracture Treat Reclamation Casing Repair New Construction Recomplete Change Plans Plug and Abandon Temporarily At Convert to Injection Plug Back Water Disposal	Well Integrity Other CHANGE OF CEMENT PLANS		

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

NOBLE ENERGY, INC. REQUESTS CHANGES TO THE CEMENTING PLANS PER THE ATTACHED DOCUMENT.

RCVD MAY 28'08 OIL CONS. DIV.

DIST. 3

SEE ATTACHED FOR **CONDITIONS OF APPROVAL**

14 I hereby certify that the foregoing is true and correct Name (Printed/Typed)						
BILLIE MAEZ	Title DISTRICT MANAGER					
Signature Sillie Malz	Date 05/21/2008		08			
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
Approved by Troy L Salves		Title PE	Date 5.27.2008			
Conditions of approval, if any, are attached. Approval of this notice does not warrant certify that the applicant holds legal or equitable title to those rights in the subject lear which would entitle the applicant to conduct operations thereon.		Office FF				
Title 18 U.S.C. Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any production of the first state of the firs	person k	nowingly and willfully to make	to any department or agency of the United			



1

CEMENTING PROGRAMS: Navajo 2-15, 2-23, 11-7, 11-5, 11-15, 11-13 wells

9-5/8" Surface casing:

200 sx Type III cement with 3% CaCl₂, ½#/sx cellofakes. 100% excess to circulate cement to surface. WOC 4 hrs. Pressure test surface casing to 1000 psi for 30 minutes.

Slurry weight: 15.2 ppg Slurry yield: 1.28 ft³/sack

Volume basis:

 40' of 9-5/8" shoe joint
 17 cu ft

 300' of 12-1/4" x 9-5/8" annulus
 100 cu ft

 100% excess (annulus)
 100 cu ft

 Total
 217 cu ft

Note:

1. Design top of cement is the surface.

2. Have available 100 sx Type III cement with 2% CaCL₂ for top out purposes.

4 1/2" Production easing:

Lead: ~670 sx of 50-50 POZ cement plus additives

Base Slurry Density: 13.0 ppg Base Slurry yield: 1.41 ft³/sx

Foamed Slurry Density: 9.0 ppg with Nitrogen

Approx N2 volume: 90000 scf

Top of cement: Surface

Tail

Lead: 220 sx of 50-50 POZ cement plus additives

Slurry weight: 13.0 ppg Slurry yield: 1.44 ft³/sx

Top of cement: 300' above Gallup formation

Volume basis:

Lead:
300' of 4 1/2" casing x 9 5/8" casing
96 cu ft
5350' of 4 ½" x 7 7/8" hole
1,220 cu ft

Tail:

 900' of 4 ½" x 7 7/8' hole
 205 cu ft

 40' of 4 ½" casing shoe jt
 3 cu ft

 30% excess (annulus)
 430 cu ft

 Total
 1954 cu ft

Note:

- 1. Excess foamed cement will be returned to surface and diverted to reserve pit.
- 2. Top of Tail cement will be 300' above Gallup formation based on open hole logs.
- 3. Actual cement volumes to be based on caliper log plus 30%.

DRILLING CONDITIONS OF APPROVAL

Operator:

Noble Energy Inc.

Lease No.:

14-20-603-1371

Well Name:

Navajo 11 #5

Well Location:

Sec. 11, T25N, R10W; 1980' FNL & 660' FWL

The following requirement(s) must be met before nipple-up operations of the Blow Out Preventor (BOP):

Wait on cement (WOC) time will be a minimum of 250 psi compressive strength at 60 degrees Fahrenheit. See general requirements attached to APD.

NMOCD minimum WOC time is 8 hours