

(October 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Bureau of Land Management

RECEIVED
 SUBMIT IN DUPLICATE
 (See other instructions on reverse side)
 MAY 19 2008

FOR APPROVED
 OMB NO. 1004-0137

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

SF-080245

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME, WELL NO.

Hamner 2M

9. API WELL NO.

30-045-33995

10. FIELD AND POOL, OR WILDCAT

Basin Dakota/Blanco MV

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec.28 T29N R9W, NMPM**RCVD MAY 22 '08****OIL CONS. DIV.****WELL COMPLETION OR RECOMPLETION REPORT AND LOG**

1a. TYPE OF WELL.

OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF RESVR ☐ Other ☐

2. NAME OF OPERATOR

ConocoPhillips

3. ADDRESS AND TELEPHONE NO.

PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface **Unit E (SWNW) 1695' FNL, 636' FWL**At top prod. interval reported below **Same as above**At total depth **Same as above**

14. PERMIT NO. DATE ISSUED

12. COUNTY OR PARISH

San Juan

13. STATE

DIST. 3 New Mexico

19. ELEV. CASINGHEAD

GL 5715' KB 5730'

23. INTERVALS DRILLED BY

ROTARY TOOLS

yes

CABLE TOOLS

No

25. WAS DIRECTIONAL SURVEY MADE

No

27. WAS WELL CORED

No

31. PERFORATION RECORD (Interval, size and number)

.34" @ 1 SPF**4160' - 4738' = 30 holes****Total holes = 30**

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8"	32.3#, H-40	230'	12 1/4"	surface; 75 sx (120 cf)	3 bbls
7"	20# J-55	3968'	8 3/4"	surface; 650 sx (1328 cf)	40 bbls
4 1/2"	10.5#, J-55	6664'	6 1/4"	TOC 3800'; 200 sx (406 cf)	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	6553'	

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number)

.34" @ 1 SPF**4160' - 4738' = 30 holes**

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

4160' - 4738'**A/10 bbls 15% HCL Acid, Frac w/44,940 gals 60Q****slickwater N2 foam, w/100,000# 20/40 Brady Sand****N2 = 965,575 SCF**

33. PRODUCTION

DATE FIRST PRODUCTION **SI** PRODUCTION METHOD (Flowing, gas lift, pumping--size and type of pump) **Flowing** WELL STATUS (Producing or shut-in) **SI**DATE OF TEST **5/4/08** HOURS TESTED **1** CHOKE SIZE **1/2"** PROD'N FOR TEST PERIOD **0** OIL-BBL **0** GAS-MCF **24 MCF** WATER-BBL **trace** GAS-OIL RATIOFLOW. TUBING PRESS. **SI - 466#** CASING PRESSURE **SI - 378#** CALCULATED 24-HOUR RATE **0** OIL-BBL **0** GAS-MCF **563 mcf/d** WATER-BBL **trace** OIL GRAVITY-API (CORR.)34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) **To be sold** TEST WITNESSED BY

35. LIST OF ATTACHMENTS

This is a MV/DK well being DHC per order #2638AZ.

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED **Thomson** TITLE **Regulatory Technician** DATE **5/19/08**

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the

United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

MAY 21 2008**NMOCD****FARMINGTON FIELD OFFICE**

Well Name			Hamner 2M		
Ojo Alamo	985'	1160'	White, cr-gr ss.	Ojo Alamo	985'
Kirtland	1160'	1617'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	1160'
Fruitland	1617'	2106'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss	Fruitland	1617'
Pictured Cliffs	2106'	2341'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	2106'
Lewis	2341'	2736'	Shale w/siltstone stringers	Lewis	2341'
Huerfanito Bentonite	2736'	3099'	White, waxy chalky bentonite	Huerfanito Bent.	2736'
Chacra	3099'	3722'	Gry fn grn silty, glauconitic sd stone w/drak gry shale	Chacra	3099'
Mesa Verde	3722'	3875'	Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	3722'
Menefee	3875'	4391'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	3875'
Point Lookout	4391'	4766'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Point Lookout	4391'
Mancos	4766'	5585'	Dark gry carb sh.	Mancos	4766'
Gallup	5585'	6346'	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg. Interbeb sh	Gallup	5585'
Greenhorn	6346'	6407'	Highly calc gry sh w/thin lmst.	Greenhorn	6346'
Graneros	6407'	6472'	Dk gry shale, fossil & carb w/pyrite incl.	Graneros	6407'
Dakota	6472'		Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shall breaks	Dakota	6472'

Well Name		Hamner 2M			
Ojo Alamo	985'	1160'	White, cr-gr ss.	Ojo Alamo	985'
Kirtland	1160'	1617'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	1160'
Fruitland	1617'	2106'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss	Fruitland	1617'
Pictured Cliffs	2106'	2341'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	2106'
Lewis	2341'	2736'	Shale w/siltstone stringers	Lewis	2341'
Huerfanito Bentonite	2736'	3099'	White, waxy chalky bentonite	Huerfanito Bent.	2736'
Chacra	3099'	3722'	Gry fn grn silty, glauconitic sd stone w/drk gry shale	Chacra	3099'
Mesa Verde	3722'	3875'	Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	3722'
Menefee	3875'	4391'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	3875'
Point Lookout	4391'	4766'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Point Lookout	4391'
Mancos	4766'	5585'	Dark gry carb sh.	Mancos	4766'
Gallup	5585'	6346'	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg. Interbeb sh	Gallup	5585'
Greenhorn	6346'	6407'	Highly calc gry sh w/thin lmst.	Greenhorn	6346'
Graneros	6407'	6472'	Dk gry shale, fossil & carb w/pyrite incl.	Graneros	6407'
Dakota	6472'		Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shall breaks	Dakota	6472'