MAY 1 5 2008

Form 3160-5 (August 1999 UNITED STATES

FORM APPROVED

	Budget Bureau No	100	4-013:
lana	10 El Otto, Mayombor	20	2000

DEPARTMENT OF THE INTERIOR AU OI Land Mana Jeresones: Novembureau of Land Management Field Coloras Frial No. SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an

NMNM-62970

6. If Indian, Allottee or Tribe Name DOIN MAY 77 YOR

and Cement Report

abandoned well. Use Form 3160-3 (APD) for such proposals.					POUD MAY 22 '0  7. If Unit or CA/Agreement, Name and/or No.			
SUBMIT IN TR	IPEICATE - Other instru	ctions on reverse side	9 1					
1 Type of Well ☐O:1 Well ☑s 2 Name of Operator	Well Other		•	8 Well Name a TSAH TA 9. API Well No	H 4 #1			
ROSETTA RESOURCES  3a Address c/o Walsh Engingeeiring & Production (3b) Phone No (include area code)  7415 East Main St. Farmington, NM 87402 (505) 327-4892  4 Location of Well (Footage, Sec , T , R., M., or Survey Description)					30-045-34672  10 Field and Pool, or Exploratory Area BASIN FRUITLAND COAL  11. County or Pansh, State			
1302' FNL & 1177' FEL SEC 4	_	INDICATE NATUR	E OF NOTIC	San Juan, I				
TYPE OF SUBMISSION	TYPE OF ACTION							
☐ Notice of Intent	☐ Acidize ☐ Alter Casing	□Deepen □Fracture Treat	Production Reclamatio	(Start/Resume) n	□ater S □ell Int			
Subsequent Report	Casing Repair	New Construction	Recomplete	Recomplete Pher Spud & C		Spud & Casing		

13 Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated date of any proposed work and approximate duration thereof If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, A Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection )

Plug and Abandon

Plug Back

Temporarily Abandon

Water Disposal

☐ Change Plans

Convert to Injection

05/5/08 spud 8-3/4" surface hole. Drilled to 135' KB Ran 3 jts (123 70') of 7", 20#, J-55, ST&C new casing and set casing at 129 KB. Cemented with 65 sx (77 cu. ft ) of Type 5, 3% CaCl and 1/4 #/sk celloflake. Circulated 6.0 bbls of good cement to surface.

05/6/08 Nippled up the BOP. Pressure tested the BOP, choke manifold and casing to 250 psi - low and 1000 psi - high.

05/9/08 TD 6-1/4" hole at 1860' Ran 45 jts (1849 62') of 4.-1/2", 10 5#, J-55, ST&C production casing and set casing at 1855' KB. Insert float is at 1835' KB and the top of marker joint is at 1395' KB. Cemented with 150 sx (309cu.ft.) of Type 5, 2% sodium metasillicate, 1/4#/sk celloflake, followed by 75 sx (89 cu. ft ) of Type 5, with 1/4# celloflake Bumped plug-to

1500 psi. Circulated 25 bbls of cement to surface.

Final Abandonment Notice

ACCEPTED FOR RECORD

14. I hereby certify that the foregoing is true and correct				
Name (Printed/Typed)				
Paul C. Thompson, P.E.		Agent/Engineer		
Signature lan C. / hours		May 12, 2008		
THIS SPACE FOR FEDER	AL OR S	TATE OFFICE USE		
Approved by	Title	Date		
Conditions of approval, if any, are attached Approval of this notice does not warran	t or			
certify that the applicant holds legal or equitable title to those rights in the subject   Office				
which would entitle the applicant to conduct operation thereon	<u> </u>			
Title 18 U C S Section 1001 and Title 43 U S C Section 1212, makes it a crime to	or any person	knowingly and willfully to make any department or agency of the Unit		
States any false, fictitious or fraudulent statements or representations as to any matter	r within its jur	nsdiction		

Tachede pt 45 CSG Next Report.

