This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Completion

Mesa verde

NEW MEXICO OIL CONSERVATION DIVISION

Page 1

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Revised June 10, 2003

	•	•	weii
Operator _	WILLIAMS PRODUCTION	Lease Name Rosa Unit	No138 MV/PC

Location Of Well: Unit Letter I Sec 17 Twp 31N Rge 06W API # 30-0 4529147

	•	,	• •		
	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. Or Csg.)	
Upper Completion	Picture Cliff	Gas	Fbw	Tbg	
Lower		_		7	

Pre-Flow Shut-In Pressure Data

Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	0825 5-13-08	7 Days	T928 C928	
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	0825 5-13-08	1.7Day5	252	

Flow Test No. 1 Commenced at (hour, date)*0944 Zone producing (Upper or Lower) 5-19-08 Time Lapsed Time Prod. Zone Pressure Remarks Since* Upper Compl. Lower Compl. (Hour, Date) Temp. 24 HRS RCVD JUN 25'08 48 HRS 730 OIL CONS. DIV. C916 916 72 HRS. C916 1916 96 HRS 196 T927/c927 144 HRS Production rate during test

Oil: BOPD based on Bbls. In Hrs. Grav. GOR

Gas: 140 MCFPD; Test thru (Orifice or Meter): Meter

Mid-Test Shut-In Pressure Data

Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	0949 5/25/08	8day 5	T931 C926	
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	0945 5/25/08	8day5	256	

(Continue on reverse side)

Flow Test No. 2

Commenced a	t (hour, date)**	0930	6-2	-08	Zone	producing (U)	oper or Lower):	
Time	Lapsed Time		Pre	ssure		Prod. Zone	Remarks	
(Hour, Date)	Since**	Upper	Compl.	Lower Comp	1.	Temp.		
0930 6208		T931	C926	256		840	τ	
0930 6-308	24485	T40	c924	259		90°	P.C Logged	off does not produce
0930 64-08	48 HRS	T32	c 926	259		76°	1 '	;
0930 6-5-08	72 Hes	T20	c 926	263		66°	1,	
0930 6-6-08	96 HRS	T30	c 918	263		69°	\ ;	
0930 6-5-08 0930 6-6-08 0930 6-7-08	120 HRS	T 20	L920	268		710	-1	
Production rate	during test		•	• •	,			
Oil:	BOPD base			Bbls. In			Grav	GOR
Gas:	MCFF	PD; Test	thru (Orif	ice or Meter):	Me	te^		
Remarks:								
I hereby certify	that the informa	tion here	in contair	ned is true and	comp	ete to the best	of my knowledge.	•
Approved	JUL 0 1			20		Operator <u>u</u>	PX	
	New Mexico Oil Conservation Division By Darren Rowley							
By Cally	G. Roll	E		•		Title Tec		

Northwest New Mexico Packer Leakage Test Instructions

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Deputy Oil & Gas Inspector, District #3

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

E-mail Address darren. rowley @ Williams.com

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98. with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).