1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave, Artesia, NM 88210

District III

1000 Rio Brazos Rd, Aztec, NM 87410 District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources** 

> Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 June 16, 2008 For temporary pits, closed-loop sytems, and below-grade

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

tanks, submit to the appropriate NMOCD District Office.

# Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action:	X Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
[	Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the

environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances Operator: Burlington Resources Oil & Gas Company, LP OGRID#: 14538 Address: PO Box 4289, Farmington, NM 87499 Facility or well name: Stull #100S API Number: 30-045-32105 OCD Permit Number: U/L or Qtr/Qtr: L(NWSW) Section: 10 Township: 10W County: San Juan Range: **107\*52'25.932" W** NAD: **X** 1927 1983 Center of Proposed Design: Latitude: 36\*59'47.969" N Longitude: X Private Tribal Trust or Indian Allotment Surface Owner: Federal Pit: Subsection F or G of 19.15.17.11 NMAC X Closed-loop Systems: Subsection H of 19.15.17.11 NMAC Drilling Workover Drying Pad X Tanks Haul-off Bins Other: Temporary: Permanent Emergency Cavitation Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other: String-Reinforced Seams: Welded Factory Other: Seams: Welded Factory Other Volume: 500 bbl Dimensions: Dimernsions: Length 45' x Width 10' Below-grade tank: Subsection I of 19 15.17 11 NMAC Fencing: Subsection D of 19.15.17.11 NMAC Volume: bbl Chain link, six feet in height, two strangs of barbed wire at top Type of fluid: Four foot height, four strands of barbed wire evenly spaced between Tank Construction Material: one and four feet Secondary containment with leak detection Netting: Subsection E of 19.15.17.11 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Screen Netting Visible sidewalls and liner Monthly inspections Visible sidewalls only Subsection C of 19.15.17 11 NMAC Signs: Other: 12"x 24", 2" lettering, provided Operator's name, site location, and Liner type: Thickness: mil HDPE emergency telephone numbers Other: X Signed in compliance with 19.15.3.103 NMAC Alternative Method: **Administrative Approvals and Exceptions:** Justifications and/or demonstrations of equivalency are required. Please Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration refer to 19.15.17 NMAC for guidance. of approval. Please check a box if one or more of the following is requested, if not Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC  Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.						
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.  - NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells	Yes	□No				
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	□Yes	□No				
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No				
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	□NA	į				
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No				
<ul> <li>(Applied to permanent pits)</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>	∐NA					
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	□Yes	□No				
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	□Yes	□No				
<ul> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> <li>Within 500 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	□Yes	□No				
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	□Yes	□No				
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes	□No				
Within a 100-year floodplain - FEMA map	Yes	□No				
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.						
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintence Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC						
Previously Approved Design (attach copy of API Number: or Permit						
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.						
Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9  Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC						
Previously Approved Design (attach copy of API Number:						

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC							
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.							
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC							
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC							
Climatological Factors Assessment							
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC							
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC							
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC							
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC							
Quality Control/Quality Assurance Construction and Installation Plan							
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC							
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC							
Nusance or Hazardous Odors, including H2S, Prevention Plan							
Emergency Response Plan							
Oil Field Waste Stream Characterization							
Monitoring and Inspection Plan	ľ						
Erosion Control Plan							
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC							
Proposed Closure: 19.15.17.13 NMAC							
Type: Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank X Closed-loop System Altern	native						
Proposed Cleaning VIWesta Function and Personal							
Proposed Closure X Waste Excavation and Removal							
On-site Closure Method (only for temporary pits and closed-loop							
In-place On-site Trench							
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau f	or						
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC							
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan, Recommentations of acceptable source							
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate							
district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.							
Ground water is less than 50 feet below the bottom of the buried waste							
Ground water is less than 50 feet below the bottom of the buried waste.	□Yes□No						
Ground water is less than 50 feet below the bottom of the buried waste.  - NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells	∐Yes ∏No ∏NA						
- NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste	□NA □						
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul>	□NA □Yes □No						
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> </ul>	∏NA ∏Yes ∏No ∏NA						
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> </ul>	NA Yes No NA Yes No						
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal</li> </ul>	NA  Yes No  NA  Yes No  Yes No						
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).</li> </ul>	NA Yes No NA Yes No						
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	NA Yes No NA Yes No NA Yes No						
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).</li> </ul>	NA Yes No NA Yes No						
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> </ul>	NA Yes No NA Yes No NA Yes No						
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste</li> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial</li> </ul>	NA Yes No NA Yes No NA Yes No Yes No						
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic</li> </ul>	NA Yes No NA Yes No NA Yes No Yes No						
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time</li> </ul>	NA Yes No NA Yes No NA Yes No Yes No						
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.         <ul> <li>NM Office of the State Engineer - 1WATERS database; Visual inspection (certification) of the proposed site</li> </ul> </li> </ul>	NA Yes No NA Yes No NA Yes No Yes No						
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.</li> </ul>	NA Yes No NA Yes No NA Yes No Yes No						
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal	NA Yes No NA Yes No NA Yes No Yes No						
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.         <ul> <li>NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended         <ul> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> </ul> </li> </ul>	NA Yes No NA Yes No NA Yes No Yes No Yes No						
<ul> <li>NM Office of the State Engineer - IWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.</li></ul>	NA Yes No NA Yes No NA Yes No Yes No						
<ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aenal photo; Satellite image</li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.</li></ul>	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No						
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Ground water is between 50 and 100 feet below the bottom of the buried waste         <ul> <li>NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Ground water is more than 100 feet below the bottom of the buried waste.         <ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul> </li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).         <ul> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial         <ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul> </li> <li>Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.         <ul> <li>NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site</li> </ul> </li> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended         <ul> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> </ul> </li> <li>Within the area overlying a subsurface mine.</li> </ul>	NA Yes No NA Yes No NA Yes No Yes No Yes No						
- NM Office of the State Engineer - IWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - IWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal  (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic  or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time  of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No						
- NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - 1WATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No						
- NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - 1WATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM	NA						
- NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - 1WATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.	NA						
- NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - 1WATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM	NA						

	Waste Excavation and Removal Closure Plan Checklist: (19 15.17 13 NMAC) Instructions: Each of the following items must be attached						
to the closure plan. Please indicfate, by a check mark in the box, that the documents are attached.							
Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC   Confiramtion Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC							
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)							
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19 15.17.13 NMAC							
X Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC							
Site Reclamation Plan - based upon the appropriate requirements of Su	bsection G of 19.15.17.13 NMAC						
Waste Removal Closure for Closed-loop Systems That Utilize Haul-off I facilities for the disposal of liquids, drilling fluids and drill cuttings.							
Disposal Facility Name: Envirotech, Basin Disposal	Disposal Facility Permit Number NM-01-0011 & NM-01-005						
On-Site Closure Plan Checklist: (19.15 17 13 NMAC) Instructions: Each of the check mark in the box, that the documents are attached.	following items must bee attached to the closure plan. Please indicate, by a						
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19 15.17.13 NMAC							
Construction and Design of Burial Trench (if applicable) based upon t	Construction and Design of Burial Trench (if applicable) based upon the appropriate requirements of 19 15.17 11 NMAC						
Protocols and Procedures - based upon the appropriate requirements of	F 19.15 17 13 NMAC						
Confirmation Sampling Plan (if applicable) - based upon the appropria	te requirements of Subsection F of 19 15 17 13 NMAC						
Waste Material Sampling Plan - based upon the appropriate requireme							
Disposal Facility Name and Permit Number (for liquids, drilling fluids	-						
Soil Cover Design - based upon the appropriate requirements of Subse							
Re-vegetation Plan - based upon the appropriate requirements of Subscillar Stre Reclamation Plan - based upon the appropriate requirements of Su							
	iosection of 15.15.17 13 Nimae						
Operator Application Certification:  I hereby certify that the information submitted with this application is true, accurat	e and complete to the heat of my knowledge and helief						
Name (Print): Crystal Tafoya	Title: Regulatory Technician						
7 10-1							
Signature: Longtal Jafoya	Date: 7/10/2008						
e-mail address: crystal tafoya@conocophidos.com Telephone: 505-326-9837							
OCD Representative Signature: Bol bell	Closure Plan (only)  Approval Date: 7/11/08						
OCD Representative Signature: Bol bell	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC						
OCD Representative Signature: Bel Bell Title: Enviro 15per	Approval Date: 7/11/08  OCD Permit Number						
OCD Representative Signature:  Title:  ENV, 70   Spec  Closure Report (required within 60 days of closure completion): Subsection K of 19 15.	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC Closure Completion Date:						
OCD Representative Signature:  Title:  ENVINO   Spec  Closure Report (required within 60 days of closure completion): Subsection K of 19 15.  Closure Method:  Waste Excavation and Removal On-Site Closure   Alt	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC						
OCD Representative Signature: B-	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC  Closure Completion Date:						
OCD Representative Signature:  Title:  ENVINO   Spec  Closure Report (required within 60 days of closure completion): Subsection K of 19 15.  Closure Method:  Waste Excavation and Removal On-Site Closure   Alt	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC  Closure Completion Date:						
OCD Representative Signature:  Title:  ENVINO Spec  Closure Report (required within 60 days of closure completion): Subsection K of 19 15.  Closure Method:  Waste Excavation and Removal On-Site Closure Alt  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached.  Proof of Closure Notice	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC  Closure Completion Date:						
OCD Representative Signature:  Title:  ENVIRO   Spec  Closure Report (required within 60 days of closure completion): Subsection K of 19 15.  Closure Method:  Waste Excavation and Removal On-Site Closure Alt  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC  Closure Completion Date:						
OCD Representative Signature:  Title:  ENVIRO   Spec  Closure Report (required within 60 days of closure completion): Subsection K of 19 15.  Closure Method:  Waste Excavation and Removal On-Site Closure Alt  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC  Closure Completion Date:						
OCD Representative Signature:  Title:  ENVIRO   Spec  Closure Report (required within 60 days of closure completion): Subsection K of 19 15.  Closure Method:  Waste Excavation and Removal On-Site Closure Alt  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC  Closure Completion Date:						
Closure Report (required within 60 days of closure completion): Subsection K of 19 15.  Closure Method:  Waste Excavation and Removal On-Site Closure Alt of the following items box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan  Confirmation Sampling Analytical Results  Waste Material Sampling Analytical Results  Disposal Facility Name and Permit Number	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC  Closure Completion Date:						
Closure Report (required within 60 days of closure completion): Subsection K of 19 15.  Closure Method:  Waste Excavation and Removal  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan  Confirmation Sampling Analytical Results  Waste Material Sampling Analytical Results  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC  Closure Completion Date:						
Closure Report (required within 60 days of closure completion): Subsection K of 19 15.  Closure Method:  Waste Excavation and Removal  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan  Confirmation Sampling Analytical Results  Waste Material Sampling Analytical Results  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC  Closure Completion Date:						
Closure Report (required within 60 days of closure completion): Subsection K of 19 15.  Closure Method:  Waste Excavation and Removal  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan  Confirmation Sampling Analytical Results  Waste Material Sampling Analytical Results  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC  Closure Completion Date:						
Closure Report (required within 60 days of closure completion): Subsection K of 19 15.  Closure Method:  Waste Excavation and Removal  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan  Confirmation Sampling Analytical Results  Waste Material Sampling Analytical Results  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique  Site Reclamation (Photo Documentation)  On-site Closure  Latitude:	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC Closure Completion Date:  ernative Closure  must be attached to the closure report. Please indicate, by a check mark in the						
Closure Report (required within 60 days of closure completion): Subsection K of 19 15.  Closure Method:  Waste Excavation and Removal On-Site Closure Alterial If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan  Confirmation Sampling Analytical Results  Waste Material Sampling Analytical Results  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique  Site Reclamation (Photo Documentation)  On-site Closure Latitude:	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC Closure Completion Date:  ernative Closure  amust be attached to the closure report. Please indicate, by a check mark in the  Longitude: NAD: 1927 1983  e. accurate and complete to the best of my knowledge and belief 1 also certify that the						
OCD Representative Signature:  Title:	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC Closure Completion Date:  ernative Closure  amust be attached to the closure report. Please indicate, by a check mark in the  Longitude: NAD: 1927 1983  e. accurate and complete to the best of my knowledge and belief 1 also certify that the						
Closure Report (required within 60 days of closure completion): Subsection K of 19 15.  Closure Method:  Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude:  Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is to closure complies with all applicable closure requirements and conditions specified in the	Approval Date: 7/11/08  OCD Permit Number  7.13 NMAC Closure Completion Date:  ernative Closure  finust be attached to the closure report. Please indicate, by a check mark in the  Longitude:						

ESTRICT | E.O. Box 1980, Hobba, N.M. 88241-1980

EISTRICT II P.O. Drower DD, Artesia, N.M. 88211-0719

State of New Mexico Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION

Form C-102
Revised February 21, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

1000 Rio Brazos Rd.,	, Aztec, N	M. 87410		-	P.O. 8			1		ree Lee	ase - 3 Copies
DISTRICT IV PO Box 2088, Santa	Fa NN S	75042088		So	onta Fe, N	M 87	504-2088			] AMEN	NDED REPORT
ru 60x 2000, 30mm	110, 100 0		VELL LO	CATIO	N AND	ACI	REAGE DEDI	CATION PI	ΔΤ		
WELL LOCATION AND ACREAGE DEDICATION ACREAGE DEDICATION ACREAGE DEDICATION ACREAGE DEDICATI							<sup>3</sup> Pool Narme				
30-045- 3	30-045- 32/05 71629					Basin Fritland Coal					
*Property Code	•	<sup>®</sup> Property Name STULL						• Well Humber			felt Number 100S
	7554							<u>'</u>			
70GRID No. 14538			BURLI	*Oper SOURCES	YLP			Elevation 6136			
					10 Surfa	ice	Location •				
UL or lot no.	Section 10	Township 32-N	Range 10-W	Lot Idn	Feet from the 1615		North/South line SOUTH	Feet from the .1085	East/Wes WES		County SAN JUAN
			11 Botto	m Hole	Location	on I	f Different Fro	om Surface			
UL or lot no.	Section	Township	Range	Lot ldn ,	Feet from t		North/South line	Feet from the	East/We	st line	County
<sup>12</sup> Dedicated Acres		10 Je	oint or Infill		** Consolidati	on Co	de	<sup>18</sup> Order No.			<del></del>
339.83		ļ									
	ABLE \	MLL BE A	SSIGNED	TO THI	S COMPL	ETIC	ON UNTIL ALL	INTERESTS I	IAVE B	EEN C	ONSOLIDATED
3							EEN APPROVE				
								] 17	10 <i>E</i> D 41	OD 00	ERTIFICATION
			7			Ane som town		i hereby cortif	y that the Inf	ormation, cos	nitathed herein is
					18 18 18 18 18 18 18 18 18 18 18 18 18 1	TE /	TORK .	true and correc	ists to the b	at of my ter	nowledge and belief
				É							
				$\int_{\mathbb{R}^{3}} dz$	J/31	4. J.1					
				1:	•	•					
				(	\$4 · •		· 🚁 🤳				
				1	, Grand	. 1 %	14	Tan	must l	uni<8	#
,				``	A Comment			Signature	Wimsat		<del></del>
							do to	Printed No		<u> </u>	<del></del>
W.C. FD 3 1/4" BUM 1969 BC		COLO	RADO						atory S	Specia	alist
<del></del>		NEW M	EXICO ]	<del></del>	<del></del>	7		TH 1-	13-04	•	
CALC'D. CORNER		ROBERT J.	— ¬i	aug 5	·	TI.		Date			
1		DOUGHTIE,	ET UX	CHARLET BRADFO	T H. RD, ET UX			18 S	URVEYO	R CEF	RTIFICATION
EARL STULL ET UX		11				LOT 5	i hereby cartify that the vallocations shown on this was plotted from field notes of actual surveys made				
1085		BILLIE JEAN	I TAYLOR			#	25. 0	1	a hast to	The Case	the same is true and
1000	<b>-</b>	ANN MA	11	li		ili .			CID A.J	OHNC	<b>\ 3</b>
ļ <u>.                                    </u>		D. & R.		 ^ ==-		' اار	USA SF - 078699	Date of Sur	THE WA	36	<del></del>
E. (%)	2,	LAT: 36'59.	.7995' N	() == () (NAD 27)	<del></del> )	1		T Signefrages in		1. 1	Girlera:
17.0	615	LONG:107°52	2.4322' Ŵ.	MARVIN		111		18/		"	<i>I≲)</i>
520.55°	-	D. & R.	.G.W.		RY, ET UX					2//:	E CX
22 22 25 25 25 25	arl stui	L, ET UX	li	li		#	LOT 6		O PROFE		4
IFD 3 1/4°		S 89'24'		li		ili		14827			
BUM_1969_BC		2578.62'_		CALC'D.	CORNER	ili		1	17	<u> </u>	

# ConocoPhillips Company Closed-loop Plans

## **Closed-loop Design Plan**

COPC's closed loop system will not entail a drying pad, temporary pit, below grade tank or sump. It will include an above ground tank suitable for holding the cuttings and fluids for rig operations. The tank will be sufficient volume to maintain a safe free board between disposal of the liquids and solids from rig operations.

- 1. Fencing is not required for an above ground closed-loop system
- 2. It will be signed in compliance with 19.15.3.103 NMAC
- 3. A frac tank will be on location to store fresh water

### **Closed-loop Operating and Maintenance Plan**

COPC's closed-loop tank will be operated and maintained to contain liquids and solids in order to prevent contamination of fresh water sources, in order to protect public health and the environment. To ensure the operation is maintained the following steps will be followed:

- 1. The liquids will be vacuumed out and disposed of at the Basin Disposal facility (Permit # NM-01-005). Solids in the closed-loop tank will be vacuumed out and disposed of at Envirotech (Permit # NM-01-0011) on a periodic basis to prevent over topping.
- 2. No hazardous waste, miscellaneous solid waste or debris will be discharged into or stored in the tank. Only fluids or cutting used or generated by rig operations will be placed or stored in the tank.
- 3. The division district office will be notified within 48 hours of the discovery of compromised integrity of the closed-loop tank. Upon the discovery of the compromised tank, repairs will be enacted immediately
- 4. All of the above operations will be inspected and a log will be signed and dated. During rig operations the inspection will be daily.

### **Closed-loop Closure Plan**

The closed-loop tank will be closed in accordance with 19.15.17.13. This will be done by transporting cuttings and all remaining sludges to Envirotech (Permit # NM-01-0011) immediately following rig operations. All remaining liquids will be transported and disposed of in the Basin Disposal facility (Permit # NM-01-005). The tanks will be removed from the location as part of the rig move. At time of well abandonment, the site will be reclaimed and re-vegetated to pre-existing conditions when possible.