

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

**RECEIVED****JUL 10 2008****Sundry Notices and Reports on Wells**

**Bureau of Land Management  
Farmington Field Office**

1. **Type of Well**  
GAS

2. **Name of Operator**  
**CONOCOPHILLIPS COMPANY**

3. **Address & Phone No. of Operator**

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. **Location of Well, Footage, Sec., T, R, M**

Unit A (NENE), 948' FNL & 1214' FEL, Sec. 7 T29N, R5W, NMPM

5. **Lease Number**  
NMSF-078277

6. **If Indian, All. or Tribe Name**

7. **Unit Agreement Name**

8. **San Juan 29-5 Unit Well Name & Number**  
San Juan 29-5 Unit #229

9. **API Well No.**  
30-039-25227

10. **Field and Pool**  
Basin Fruitland Coal

11. **County and State**  
Rio Arriba Co., NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

Type of Submission	Type of Action	
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection

Other -

**RCVD JUL 14 '08  
OIL CONS. DIV.  
DIST. 3**

**13. Describe Proposed or Completed Operations**

7/3/08 MIRU A-Plus #10. 7/7/08 ND WH, NU BOP. TOO H w/tubing and packer. RIH w/WL & set CR @ 3133'. PT-OK. Load hole w/water & PT casing to 800# - Held. **Plug #1** (3133'- 3029') pumped 20 sx Class G cement to cover & isolate FTC openhole interval & top. Load casing w/water. **Plug #2** - (2853'- 2510') Pumped 66 sx Class G cement to cover & isolate Kirtland & Ojo Alamo tops. Load casing w/water. **Plug #3** (1240' -0 1396') Pumped 30 sx Class C cement to cover & isolate Nacimiento Top. Load casing. **Plug #4** - (341' - surface) Pumped 76 sx Class G cement to isolate & cover casing shoe. Good cement out csg valve. LD workstring. 7/7/08 RD. 7/8/08 Tagged TOC @ 7'. ND BOP. Dig out & cut off WH. Installed P&A marker w/30 sx Class G cement. RD & released rig @ 1030 hrs 7/8/08.

This well is now P&A'd.

**14. I hereby certify that the foregoing is true and correct.**

Signed Patsy Clugston Patsy Clugston Title Regulatory Specialist Date 7/10/08

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U S C Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

**ACCEPTED FOR RECORD****JUL 11 2008****FARMINGTON FIELD OFFICE****NMOCD**