

submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RCVD JUL 14 '08

OIL CONS. DIV.  
DIST. 3

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator  
**MERIDIAN OIL**

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
800'FNL, 1500'FWL, Sec.20, T-26-N, R-10-W, NMPM

5. Lease Number  
SF-077933A

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

Huerfano Unit

8. Well Name & Number  
Huerfano U NP #212

9. API Well No.  
30-045-20737

10. Field and Pool  
Basin Dakota

11. County and State  
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

11-7-94 MIRU. Kill well w/55 bbl wtr. ND WH. NU BOP. SDON.  
11-8-94 TOO H w/208 jts 2 3/8" tbq. TIH w/4 1/2" cmt retainer, set @ 6383'. Circ hole w/44 bbl wtr. Stung into retainer. Establish circ into Dakota. Plug #1: pump 12 sx Class "B" cmt into Dakota perfs. Stung out of cmt retainer. Spot 14 sx Class "B" cmt on top of retainer. TOC @ 6199'. POOH to 5533'. Plug #2: w/cmt cmt retainer set @ 5533'. Pump 12 sx Class "B" cmt @ 5375-5533'. POOH to 3209'. Plug #3: pumped 27 sx Class "B" cmt @ 3353-3709'. POOH to 1948'. Plug #4: pumped 73 sx Class "B" cmt @ 987-1958' inside csg. POOH. SDON.  
11-9-94 TIH. Tag cmt @ 994'. Shot 4 sqz holes @ 965'. Load hole w/wtr. Establish circ @ 750 psi. TIH w/4 1/2" cmt retainer, set @ 912'. Established circ @ 750 psi into perfs. Plug #5: sqzd 43 sx Class "B" cmt below cmt retainer and 5 sx above retainer @ 846'. POOH. Shot 2 sqz holes @ 263'. TOO H. Establish circ out bradenhead w/15 bbl wtr. Plug #6: pumped 99 sx Class "B" cmt @ 0-263' inside & outside. WOC. ND BOP. Cut off WH. Install dry hole marker w/20 sx cmt. RD. Well plugged & abandoned 11-9-94.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 11/11/94

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

**APPROVED**

NOV 21 1994

**ACTING MANAGER**

OPERATOR