This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator Burli		Lease Name SAN JUAN 29-7 UNIT					Well No4A		
Location of We	ell: Unit	Letter E S	Sec	10	Twp 029	<u> </u>	Rge	007W API	# 30-039-25574
	Name of Reservoir or Pool			Type of Prod			Method of Prod		Prod Medium
Upper Completion	PC			Gas			Artificial Lift		Tubing
Lower Completion	MV			Gas			Artificial Lift		Tubing
			Pre-	Flow S	hut-In Pres	sure Da	ta		
Upper	Hour, Date, Shut-In			Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No)
Completion	6/23/2008			360 hours			208		Yes
Lower Completion	Hour, Date, Shut-In			Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No)
	6/23/2008			456 hours			205		Yes
				Flo	w Test No.	1			
Commenced	at:	7/8/2008					g (Upper	or Lower): Up	per
Time		Lapsed Time Since*		PRESSURE I			Prod Zone		
(date/time	e)			r zone	Lower zon	e Temp	perature		Remarks
7/9/2008 9:45·00 AM		33	1:	25	203/				
7/10/2008 9:45:00 AM		57	1:	21	201				
7/11/2008		72							
7/12/2008 96									
Production rate	during	test	1		LESS THAN	10% DROF	?		
Oil:	BPOD Based on:Bbl			s. InHrs		Grav.		GOR	
Gas		MCFPD; Test th	hru (Orifi	ce or M	eter)				
ý			Mid-	-Test S	hut-In Pres	sure Dat	ta		
Upper Completion	Hour, Date, Shut-In			Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No)
Lower Completion				Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No)

(Continue on reverse side)

RCVD JUL 16 '08 OIL CONS. DIV.

Flow Test No. 2

Commenced at:			Zone Pro	Zone Producing (Upper or Lower)							
Time	•		SURE	Prod Zone							
(date/time)	Since*	Upper zone	Lower zone	Temperature)	Remarks					
					<u> </u>						
			-								
				<u> </u>	<u>, </u>						
Production rate during test											
Oil:BPO	D Based on:	Bbls. In	Hrs.		Grav.	GOR					
Gas MCFPD; Test thru (Orifice or Meter)											
Remarks:											
Tiomano.											
I hereby certify that the information herein contained is true and complete to the best of my knowledge.											
Approved:	JUL 1 / 2000	20	Opera	tor: Burlingt	on Resources						
New Mexico Oil C	onservation Division		· Ву:	·							
By: Kalz G	to Day,	,	Title:	Title: Multi-Skilled Operator							
Title: Der	A Gas Insp	ector,	Date:	Date: Tuesday, July 15, 2008							

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer of the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the
- while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for atmosphere due to lack of a pipeline connection the flow period shall be three hours

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests, immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data

24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone

8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)

Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3