

UNITED STATES  
DEPARTMENT OF INTERIOR  
BUREAU OF LAND MANAGEMENT

JUL 17 2008

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

Bureau of Land Management

SUNDRY NOTICE AND REPORTS ON WELLS Farmington Field Office

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION TO DRILL" for permit for such proposals

Lease Designation and Serial No.  
NMSF-078770

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation  
Rosa Unit

8. Well Name and No.  
258A

9. API Well No.  
30-039-30142

10. Field and Pool, or Exploratory Area  
Basin Fruitland Coal

11. County or Parish, State  
Rio Arriba, NM

SUBMIT IN TRIPLICATE

1. Type of Well  
Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator  
WILLIAMS PRODUCTION COMPANY, LLC

3. Address and Telephone No.  
PO BOX 640, AZTEC, NM 87410 (505) 634-4200

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
2320' FNL & 180 FEL SEC 21, T31N, R5W  
1650' FNL & 990 FWL SEC 22, T31N, R5W

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

Notice of Intent

X Subsequent Report

Final Abandonment

TYPE OF ACTION

Abandonment  
Recompletion  
Plugging Back  
Casing Repair  
Altering Casing  
Surface Casing

X Other

Change of Plans  
New Construction  
Non-Routine Fracturing  
Water Shut-Off  
Conversion to Injection

Dispose Water  
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7/15/08

TD- 12 1/4" SURFACE HOLE @ 345', 0630 HRS

Ran 7 JTS, 9 5/8", 1 JT CSG SHOE, 36#, K-55, 8-rd, STC, CSG SET @ 339'. FC @ 289'.

RCVD JUL 23 '08  
OIL CONS. DIV.

DIST. 3

7/16/08

CEMENT 9-5/8" CASING @ 339' - SHOE DEPTH / SINGLE SLURRY CEMENT JOB / 20 BBLS. FRESH WATER SPACER / 150 SXS TYPE 3 CEMENT + 2% CaCl-2 + .25#/SX CELLO FLAKE + 37.80 BBL. WATER = 80 BBL. (212 CuFt) SLURRY @ 14.5 PPG (YIELD = 1.41 / WGPS = 6.84) / DISPLACE WITH 23 BBL. WATER / PLUG DOWN ON 7/15/2008 @ 1205 AM BUMP PLUG W/ 230 PSI, 8 BBL. OF CEMENT RETURNS TO SURFACE. ✓  
INSTALL TEST PLUG & TEST BOP PIPE & BLIND RAMS, CHOKE MANIFOLD VALVES, MUD CROSS VALVES, FLOOR VALVE KELLY @ 250# 5-MIN EACH & 1500# 10-MIN EACH. TEST 9 5/8" CSG @ 1500# 30-MIN. TEST PUMP & TEST CHARTS USED ON ALL TEST. ALL TESTED GOOD. ✓

ACCEPTED FOR RECORD

JUL 21 2008

FARMINGTON FIELD OFFICE  
BY T. Salyers

14. I hereby certify that the foregoing is true and correct

Signed

Heather Riley

Title Regulatory Spec

Date July 17, 2008

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

NMUCD