<u> Dustrict I</u>

1625 N. French Dr , Hobbs, NM 88240

1301 W Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

> Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 June 16, 2008 For temporary pits, closed-loop sytems, and below-grade

tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or

Proposed Alternative Method Perr	mit or Closure Plan Application
Type of action: X Permit of a pit, closed-loop system	, below-grade tank, or proposed alternative method
Closure of a pit, closed-loop syster	n, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individu	n, below-grade tank, or proposed alternative method all pit, closed-loop system, below-grade tank or alternative request ity should operations result in pollution of surface water, ground paths to 20 th any other applicable governmental authority's rules, regulations or ordinances
environment. Nor does approval relieve the operator of its responsibility to comply with	h any other applicable governmental authority's rules, regulations or ordinances
Operator: Burlington Resources Oil & Gas Company, LP	OGRID#: 14538/9 5-1/1FU B
Address: PO Box 4289, Farmington, NM 87499	2 REULING 25
Facility or well name. Ute #4	
API Number: 30-045-11479 OC	D Permit Number: OIL CONS. DIV. DIST. 3
U/L or Qtr/Qtr: N(SESW) Section: 10 Township: 32N	Range: 14W County: San Juan
Center of Proposed Design: Latitude: 36.9971500' N L	ongitude: 108.2977300' W NAD: X .1927 1983
Surface Owner: Federal State Private X Triba	l Trust or Indian Allotment
Pit: Subsection F or G of 19.15.17.11 NMAC	X Closed-loop Systems: Subsection H of 19.15.17.11 NMAC
Temporary: Drilling Workover	Drying Pad X Tanks Haul-off Bins Other:
Permanent Emergency Cavitation	Lined Unlined
Lined Unlined	Liner type: Thickness mıl LLDPE HDPE PVC
Liner type: ThicknessmilLLDPEHDPEPVC	Other:
Other String-Reinforced	Seams: Welded Factory Other:
Seams: Welded Factory Other	Volume: <u>500</u> bbl <u>104</u> yd3
Volume:bbl Dimensions: LxWxD	Dimernsions: Length 45' x Width 10'
	P. J. Charles D. (101517111111111111111111111111111111111
Below-grade tank: Subsection I of 19 15.17.11 NMAC Volume: bbl	Fencing: Subsection D of 19.15.17.11 NMAC Chain link, six feet in height, two strangs of barbed wire at top
Type of fluid:	Four foot height, four strands of barbed wire evenly spaced between
Tank Construction Material:	one and four feet
Secondary containment with leak detection	Netting: Subsection E of 19.15.17.11
Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	Screen Netting Other
Visible sidewalls and liner	Monthly inspections
Visible sidewalls only	Signs: Subsection C of 19.15 17.11 NMAC
Other:	12"x 24", 2" lettering, provided Operator's name, site location, and
Liner type: Thickness:mul	emergency telephone numbers
Other:	X Signed in compliance with 19.15.3.103 NMAC
Alternative Method:	Administrative Approvals and Exceptions:
Submittal of an exception request is required. Exceptions must be	Justifications and/or demonstrations of equivalency are required. Please
submitted to the Santa Fe Environmental Bureau office for consideration of approval.	refer to 19.15.17 NMAC for guidance.
	Please check a box if one or more of the following is requested, if not leave blank:
	Administrative approval(s): Requests must be submitted to the
	appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan)
	Exception(s): Requests must be submitted to the Santa Fe
	Environmental Bureau office for consideration of approval.



Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.		
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	□No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	□No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)	NA	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	_	_
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits)	∐Yes □NA	∐No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Пил	
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	□No
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.		!
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	Yes	□No
- Written confirmation or verification from the municipality; Written approval obtained from the municipality		'
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes	□No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	□No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes	No
Within a 100-year floodplain	□Yes	\square No
- FEMA map		
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do		re attached.
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintence Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC		
Previously Approved Design (attach copy of API Number: or Permit		
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC		
X Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Previously Approved Design (attach copy of API Number:		

I the control of the first term of the first process that the first process is the first process of the first process that the first process is the first process of the first process that the first process is the first process of the first process that the first process is the first process that the first process thand the first process that the first process that the first proce		
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are at	tached.	
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC		
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC		
Climatological Factors Assessment		
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC		
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC		
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC		
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC		
Quality Control/Quality Assurance Construction and Installation Plan		
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC		
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC		
Nuisance or Hazardous Odors, including H2S, Prevention Plan		
Emergency Response Plan		
Oil Field Waste Stream Characterization		
Monitoring and Inspection Plan		
Erosion Control Plan		
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC		
and the about a point are appropriate requirements of bassection e of 19,13,17,13 title e and 19,13,17,13 title		
Proposed Closure: 19.15.17.13 NMAC		
Type: Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank X Closed-loop System Alter	native	
Proposed Closure X Waste Excavation and Removal		
On-site Closure Method (only for temporary pits and closed-loop		
In-place On-site Trench		
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau f	for	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC		
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommentations of acceptable source		
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate		
district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of		
approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.		
Ground water is less than 50 feet below the bottom of the buried waste	□ Vas □ No	
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search: USGS: Data obtained from nearby wells	☐Yes ☐No	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□NA □	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste		
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells 	∏NA	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste		
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	NA Yes No NA Yes No NA NA NA	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal 		
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	NA Yes No NA Yes No NA NA NA	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial 	NA Yes No NA Yes No NA NA NA	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	NA Yes No NA Yes No NA Yes No NA Yes No	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic 	NA Yes No NA Yes No NA Yes No NA Yes No	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time 	NA Yes No NA Yes No NA Yes No Yes No	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. 	NA Yes No NA Yes No NA Yes No Yes No	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial appelication (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	NA Yes No NA Yes No NA Yes No Yes No Yes No	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal	NA Yes No NA Yes No NA Yes No Yes No	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	NA Yes No NA Yes No NA Yes No Yes No Yes No	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No Yes No Yes No	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No Yes Yes	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No Yes Yes	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. 	NA Yes No NA Yes No NA Yes No	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division Within an unstable area.	NA Yes No NA Yes No NA Yes No	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No	

to the closure plan. Please indicfate, by a check mark in the box, that the documents are	attached	
$ \overline{X} $ Protocols and Procedures - based upon the appropriate requirements of		
Confiramtion Sampling Plan (if applicable) - based upon the appropria		
Disposal Facility Name and Permit Number (for liquids, drilling fluids	and drill cuttings)	
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC		
X Re-vegetation Plan - based upon the appropriate requirements of Subse		
X Site Reclamation Plan - based upon the appropriate requirements of Su	bsection G of 19.15.17.13 NMAC	
Waste Removal Closure for Closed-loop Systems That Utilize Haul-off Facilities for the disposal of liquids, drilling fluids and drill cuttings.		
Disposal Facility Name: Envirotech, Basin Disposal	Disposal Facility Permit Number: NM-01-0011 & NM-01-005	
On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the check mark in the box, that the documents are attached.	following stems must bee attached to the closure plan. Please indicate, by a	
Siting Criteria Compliance Demonstrations - based upon the appropria	-	
Proof of Surface Owner Notice - based upon the appropriate requirement		
Construction and Design of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC		
Protocols and Procedures - based upon the appropriate requirements of Confirmation Sampling Plan (if applicable) - based upon the appropria		
Waste Material Sampling Plan - based upon the appropriate requireme	•	
Disposal Facility Name and Permit Number (for liquids, drilling fluids		
Soil Cover Design - based upon the appropriate requirements of Subse		
Re-vegetation Plan - based upon the appropriate requirements of Subsci		
Site Reclamation Plan - based upon the appropriate requirements of Su		
Operator Application Certification:		
I hereby certify that the information submitted with this application is true, accurate	e and complete to the best of my knowledge and belief.	
Name (Print): Crystal Tafoya	Title: Regulatory Technician	
Signature Contal Talaya	Date: 7/17/2008	
e-mail address crystal.tafoya@conocophillus.com	Telephone. 505-326-9837	
OCD Representative Signature: Brand Sell		
	<u> </u>	
OCD Representative Signature: Brand Sell	OCD Permit Number	
OCD Representative Signature: Bund Sell Title: Enviro (spec	OCD Permit Number	
OCD Representative Signature: Title: Enciro (Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC	
OCD Representative Signature: Title: Enciro (Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC	
OCD Representative Signature: Title: Enciro (Spec. Closure Report (required within 60 days of closure completion): Subsection K of 19 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date:	
OCD Representative Signature: Title: Enciro (Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 15 15 15 15 15 15 15 15 15 15 15 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure	
OCD Representative Signature: Title: Enciro (Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 15 15 15 15 15 15 15 15 15 15 15 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure	
OCD Representative Signature: Title: Enciro (Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 15 15 15 15 15 15 15 15 15 15 15 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure	
OCD Representative Signature: Title: Enciro (Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 15 15 15 15 15 15 15 15 15 15 15 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure	
OCD Representative Signature: Title: Enciro (Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 15 15 15 15 15 15 15 15 15 15 15 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure	
OCD Representative Signature: Title: Enciro (Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 15 15 15 15 15 15 15 15 15 15 15 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure	
OCD Representative Signature: Title: Enciro (Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 15 15 15 15 15 15 15 15 15 15 15 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure	
Closure Method: Waste Excavation and Removal On-Site Closure Alternative Signature	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure	
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 15 15 15 15 15 15 15 15 15 15 15 15	OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure must be attached to the closure report. Please indicate, by a check mark in the	
OCD Representative Signature: Title: ENDITO Spec. Closure Report (required within 60 days of closure completion): Subsection K of 19 15 15 15 15 15 15 15 15 15 15 15 15 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure	
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 15 15 15 15 15 15 15 15 15 15 15 15	OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure must be attached to the closure report. Please indicate, by a check mark in the	
OCD Representative Signature: Title: Exciso (Specs Closure Report (required within 60 days of closure completion): Subsection K of 19 15 15 15 15 15 15 15 15 15 15 15 15 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure must be attached to the closure report. Please indicate, by a check mark in the Longitude: NAD 1927 1983 e, accurate and complete to the best of my knowledge and belief I also certify that the	
OCD Representative Signature: Title:	OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure must be attached to the closure report. Please indicate, by a check mark in the Longitude: NAD 1927 1983 e, accurate and complete to the best of my knowledge and belief 1 also certify that the proved closure plan	
OCD Representative Signature: Title: Exciso (Specs Closure Report (required within 60 days of closure completion): Subsection K of 19 15 15 15 15 15 15 15 15 15 15 15 15 15	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: must be attached to the closure report. Please indicate, by a check mark in the Longitude: NAD 1927 1983 e, accurate and complete to the best of my knowledge and belief I also certify that the	
OCD Representative Signature: Title:	OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure must be attached to the closure report. Please indicate, by a check mark in the Longitude: NAD 1927 1983 e, accurate and complete to the best of my knowledge and belief I also certify that the proved closure plan	

Form C-144 Oil Conservation Division Page 4 of 4

Burlington Resources Oil & Gas Company, LP Closed-loop Plans

Closed-loop Design Plan

BR's closed loop system will not entail a drying pad, temporary pit, below grade tank or sump. It will include an above ground tank suitable for holding the cuttings and fluids for rig operations. The tank will be sufficient volume to maintain a safe free board between disposal of the liquids and solids from rig operations.

- 1. Fencing is not required for an above ground closed-loop system
- 2. It will be signed in compliance with 19.15.3.103 NMAC
- 3. A frac tank will be on location to store fresh water

Closed-loop Operating and Maintenance Plan

BR's closed-loop tank will be operated and maintained to contain liquids and solids in order to prevent contamination of fresh water sources, in order to protect public health and the environment. To ensure the operation is maintained the following steps will be followed:

- 1. The liquids will be vacuumed out and disposed of at the Basin Disposal facility (Permit # NM-01-005). Solids in the closed-loop tank will be vacuumed out and disposed of at Envirotech (Permit # NM-01-0011) on a periodic basis to prevent over topping.
- 2. No hazardous waste, miscellaneous solid waste or debris will be discharged into or stored in the tank. Only fluids or cutting used or generated by rig operations will be placed or stored in the tank.
- 3. The division district office will be notified within 48 hours of the discovery of compromised integrity of the closed-loop tank. Upon the discovery of the compromised tank, repairs will be enacted immediately
- 4. All of the above operations will be inspected and a log will be signed and dated. During rig operations the inspection will be daily.

Closed-loop Closure Plan

The closed-loop tank will be closed in accordance with 19.15.17.13. This will be done by transporting cuttings and all remaining sludges to Envirotech (Permit # NM-01-0011) immediately following rig operations. All remaining liquids will be transported and disposed of in the Basin Disposal facility (Permit # NM-01-005). The tanks will be removed from the location as part of the rig move. At time of well abandonment, the site will be reclaimed and re-vegetated to pre-existing conditions when possible.