State of New Mexico Energy Minerals and Natural Resources

Form C-144 June 16, 2008

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr , Santa Fe, NM 87505

Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Proposed Alternative Method Permit or Closure Plan Application						
Closure of a pit, closed-loop syster Instructions: Please submit one application (Form C-144) per individu Please be advised that approval of this request does not relieve the operator of liabil environment. Nor does approval relieve the operator of its responsibility to comply with	nty should operations result in pollution of surface water ground water of the hany other applicable governmental authority's rules aggulations of ordinances. RECEIVED					
Operator: Burlington Resources Oil & Gas Company, LP	OGRID#: 14538 = 000 500 50					
Address: PO Box 4289, Farmington, NM 87499	/5. OII COMP DIA 1917. 3 (9)					
Facility or well name: Allison Unit Com #111S	<u> </u>					
API Number 30-045-31235 OC	D Permit Number:					
U/L or Qtr/Qtr: J(NWSE) Section: 18 Township: 32N	Range: 6W County: San Juan					
Center of Proposed Design: Latitude: 36.94971000' N L	ongitude: 107.46172000' W NAD: X 1927 1 983					
Surface Owner: Federal State X Private Triba	l Trust or Indian Allotment					
Pit: Subsection F or G of 19.15.17.11 NMAC Temporary: Drilling Workover	X Closed-loop Systems: Subsection H of 19.15.17.11 NMAC Drying Pad X Tanks Haul-off Bins Other:					
Permanent Emergency Cavitation	Lined Unlined					
Lined Unlined	Liner type: Thickness mil LLDPE HDPE PVC					
Liner type: Thickness milLLDPEHDPEPVC	Other:					
OtherString-Reinforced	Seams: Welded Factory Other:					
Seams: Welded Factory Other	Volume: <u>500</u> bbl <u>104</u> yd3					
Volume:bbl	Dimernsions: Length 45' x Width 10'					
Below-grade tank: Subsection I of 19.15.17.11 NMAC	Fencing: Subsection D of 19.15 17.11 NMAC					
Volume:bbl	Chain link, six feet in height, two strangs of barbed wire at top					
Type of fluid:	Four foot height, four strands of barbed wire evenly spaced between					
Tank Construction Material:	one and four feet					
Secondary containment with leak detection	Netting: Subsection E of 19.15.17.11					
Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	Screen Netting Other					
Visible sidewalls and liner	Monthly inspections					
Visible sidewalls only	Signs: Subsection C of 19 15.17.11 NMAC					
Other:	12"x 24", 2" lettering, provided Operator's name, site location, and					
Liner type: Thickness: mil HDPE PVC	emergency telephone numbers					
Other:	X Signed in compliance with 19.15.3.103 NMAC					
Alternative Method:	Administrative Approvals and Exceptions:					
Submittal of an exception request is required. Exceptions must be	Justifications and/or demonstrations of equivalency are required. Please					
submitted to the Santa Fe Environmental Bureau office for consideration of approval.	refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not					
	leave blank:					
	Administrative approval(s): Requests must be submitted to the					
	appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan)					
	Exception(s): Requests must be submitted to the Santa Fe					
	Environmental Bureau office for consideration of approval.					



Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.						
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	□No				
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	□No				
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No				
(Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	□NA					
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	∏Yes	□No				
(Applied to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	□NA					
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	□No				
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	Yes	□No				
- Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland.	Yes	□No				
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine.	□Yes	□No				
- Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	1 es					
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes	□No				
Within a 100-year floodplain	Yes	□No				
- FEMA map						
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC						
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the d	ocuments ar	e attached.				
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintence Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC						
Previously Approved Design (attach copy of API Number: or Permit						
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9						
Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC X Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC						
X Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC						
X Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC						
Previously Approved Design (attach copy of API Number:						

Form C-144 Oil Conservation Division Page 2 of 4

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC						
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.						
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC						
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC						
Climatological Factors Assessment						
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC						
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC						
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC						
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC						
Quality Control/Quality Assurance Construction and Installation Plan						
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC						
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC						
Nuisance or Hazardous Odors, including H2S, Prevention Plan						
Emergency Response Plan						
Oil Field Waste Stream Characterization						
Monitoring and Inspection Plan						
Erosion Control Plan						
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC						
Closure Frain - based upon the appropriate requirements of Subsection C of 19,13,17,9 NVIAC and 19,13,17.13 NVIAC						
Proposed Closure: 19.15.17.13 NMAC						
Type: Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank X Closed-loop System Altern	native					
Proposed Closure X Waste Excavation and Removal						
On-site Closure Method (only for temporary pits and closed-loop						
In-place On-site Trench						
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau f	or					
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC						
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommentations of acceptable source						
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate						
district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of						
approval. Justification analor demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.	approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.					
Ground water is less than 50 feet below the hottom of the buried waste	□Ves□No					
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search: USGS: Data obtained from nearby wells	☐Yes ☐No ☐NA					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□NA □					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste						
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells 	□NA □Yes□No □NA					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste	□NA □Yes □No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	NA Yes No NA Yes No NA NA					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal 	NA Yes No NA Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	NA Yes No NA Yes No NA NA					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial 	NA Yes No NA Yes No NA NA					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	NA Yes No NA Yes No NA Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic 	NA Yes No NA Yes No NA Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time 	NA Yes No NA Yes No NA Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. 	NA Yes No NA Yes No NA Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	NA Yes No NA Yes No NA Yes No Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal 	NA Yes No NA Yes No NA Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended 	NA Yes No NA Yes No NA Yes No Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial residence of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No Yes No Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Written confirmation or verification from the municipality; Written approval obtained from the municipality 	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No Yes No Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division Within an unstable area.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	NA					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No					

Waste Excavation and Removal Closure Plan Checklist: (19.15 17 13 NMAC) Instructions: Each of the following items must be attached					
to the closure plan. Please indicfate, by a check mark in the box, that the documents are attached. $ \overline{X} $ Protocols and Procedures - based upon the appropriate requirements of 19 15.17.13 NMAC					
Confirantion Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17 13 NMAC					
X Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)					
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC					
X Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17 13 NMAC					
X Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC					
Waste Removal Closure for Closed-loop Systems That Utilize Haul-off Bins Only: (19 15 17 13 D NMAC) Instructions: Please identify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings.					
Disposal Facility Name: Envirotech, Basin Disposal Disposal Facility Permit Number: NM-01-0011 & NM-01-005					
On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.					
Siting Criteria Compliance Demonstrations - based upon the appropria	•				
Proof of Surface Owner Notice - based upon the appropriate requireme	ents of Subsection F of 19.15.17.13 NMAC				
Construction and Design of Burial Trench (if applicable) based upon the	••••				
Protocols and Procedures - based upon the appropriate requirements of					
Confirmation Sampling Plan (if applicable) - based upon the appropria	•				
Waste Material Sampling Plan - based upon the appropriate requireme					
Disposal Facility Name and Permit Number (for liquids, drilling fluids Soil Cover Design - based upon the appropriate requirements of Subse	-				
Re-vegetation Plan - based upon the appropriate requirements of Subse					
Site Reclamation Plan - based upon the appropriate requirements of Su					
Operator Application Certification:					
I hereby certify that the information submitted with this application is true, accurate	e and complete to the best of my knowledge and belief.				
Name (Print) Crystal Tafoya	Title Regulatory Technician				
Signature. Linetal Talana	Date. 7/17/2008				
e-mail address. crystal.tafoya@conocophillips.com	Telephone: 505-326-9837				
e-mail address. crystal.tatoya@coMocophilips.com releptione: 505-326-983/					
OCD Approval: Permit Application (including closure plan) OCD Representative Signature:	llosure Plan (only)				
	losure Plan (only)				
OCD Representative Signature: Brank Sell	OCD Permit Number				
OCD Representative Signature: Brank Sell Title: Enviro 15pec	OCD Permit Number				
OCD Representative Signature: Title: Enviro Spec Closure Report (required within 60 days of closure completion): Subsection K of 1915	OCD Permit Number 7 13 NMAC				
OCD Representative Signature: Title: Enviro Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method:	OCD Permit Number 7 13 NMAC				
OCD Representative Signature: Title: Enviro Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method:	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date:				
OCD Representative Signature: But Sell Title: Ensire Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alternative Signature: Alternative Signat	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date:				
OCD Representative Signature: Title: Ensire Spec Closure Report (required within 60 days of closure completion): Subsection K of 1915 Closure Method: Waste Excavation and Removal On-Site Closure Alterial of the following items box, that the documents are attached.	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date:				
OCD Representative Signature: Title: Ensire Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alterial If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date:				
OCD Representative Signature: Title: Ensire Spec Closure Report (required within 60 days of closure completion): Subsection K of 1915 Closure Method: Waste Excavation and Removal On-Site Closure Alterial of the following items box, that the documents are attached.	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date:				
OCD Representative Signature: Brank Sell Title: Ensire Spec Closure Report (required within 60 days of closure completion): Subsection K of 1915 Closure Method: Waste Excavation and Removal On-Site Closure Alterial Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date:				
Closure Report (required within 60 days of closure completion): Subsection K of 1915 Closure Method: Waste Excavation and Removal If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date:				
Closure Report (required within 60 days of closure completion): Subsection K of 1915 Closure Method: Waste Excavation and Removal If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date:				
Closure Report (required within 60 days of closure completion): Subsection K of 1915 Closure Method: Waste Excavation and Removal If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date:				
Closure Report (required within 60 days of closure completion): Subsection K of 1915 Closure Method: Waste Excavation and Removal If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date:				
Closure Report (required within 60 days of closure completion): Subsection K of 1915 Closure Method: Waste Excavation and Removal On-Site Closure Alta If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date:				
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alto If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)	Approval Date: 7-18-08 OCD Permit Number 7 13 NMAC Closure Completion Date: ernative Closure must be attached to the closure report. Please indicate, by a check mark in the				
Closure Report (required within 60 days of closure completion): Subsection K of 1915 Closure Method: Waste Excavation and Removal On-Site Closure Alta If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude.	Approval Date:				
Closure Report (required within 60 days of closure completion): Subsection K of 1915 Closure Method: Waste Excavation and Removal If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude. Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is true.	Approval Date:				
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alto If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude. Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is true closure complies with all applicable closure requirements and conditions specified in the applicable closure requirements and conditions specified in	Approval Date:				

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 37410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources

Form C-102

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number 30-45-31235	Pool Name BASIN FRUITLAND COAL (GAS)	Pool Code 71629
Property Code 6784	Property Name ALLISON UNIT	Well No • 111S
OGRID No 14538	Operator Name Burlington Resources Oil and Gas Company LP	Elevation 6504

Surface And Bottom Hole Location

1	UL or Lot	Section 18	Township 32N	Range 06W	Lot ldn	Feet From 2065	N/S Line S	Feet From 2295	E/W Line E	County San Juan
,	Dedicated Acres 320		Joint or	Infill	Consoli	dation Code		Order N	No.	

,	
	G.

OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

Electronically Signed By: Peggy Cole

Title: Manager Date: 10/9/2002

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Electronically Signed By: Jason C. Edwards

Date of Survey: 9/20/2002 Certificate Number: 15269

Burlington Resources Oil & Gas Company, LP Closed-loop Plans

Closed-loop Design Plan

BR's closed loop system will not entail a drying pad, temporary pit, below grade tank or sump. It will include an above ground tank suitable for holding the cuttings and fluids for rig operations. The tank will be sufficient volume to maintain a safe free board between disposal of the liquids and solids from rig operations.

- 1. Fencing is not required for an above ground closed-loop system
- 2. It will be signed in compliance with 19.15.3.103 NMAC
- 3. A frac tank will be on location to store fresh water

Closed-loop Operating and Maintenance Plan

BR's closed-loop tank will be operated and maintained to contain liquids and solids in order to prevent contamination of fresh water sources, in order to protect public health and the environment. To ensure the operation is maintained the following steps will be followed:

- 1. The liquids will be vacuumed out and disposed of at the Basin Disposal facility (Permit # NM-01-005). Solids in the closed-loop tank will be vacuumed out and disposed of at Envirotech (Permit # NM-01-0011) on a periodic basis to prevent over topping.
- 2. No hazardous waste, miscellaneous solid waste or debris will be discharged into or stored in the tank. Only fluids or cutting used or generated by rig operations will be placed or stored in the tank.
- 3. The division district office will be notified within 48 hours of the discovery of compromised integrity of the closed-loop tank. Upon the discovery of the compromised tank, repairs will be enacted immediately
- 4. All of the above operations will be inspected and a log will be signed and dated. During rig operations the inspection will be daily.

Closed-loop Closure Plan

The closed-loop tank will be closed in accordance with 19.15.17.13. This will be done by transporting cuttings and all remaining sludges to Envirotech (Permit # NM-01-0011) immediately following rig operations. All remaining liquids will be transported and disposed of in the Basin Disposal facility (Permit # NM-01-005). The tanks will be removed from the location as part of the rig move. At time of well abandonment, the site will be reclaimed and re-vegetated to pre-existing conditions when possible.