District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd, Aztec, NM 87410

District IV

1220 S St. Francis Dr , Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

 $\label{eq:June 16, 2008} \mbox{ June 16, 2008}$ For temporary pits, closed-loop sytems, and below-grade

Form C-144

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System,	
Proposed Alternative Method Peri	mit or Closure Plan Application
Type of action: X Permit of a pit, closed-loop system	OIL COMS. DIV.
Closure of a pit, closed-loop syster	n, below-grade tank, or proposed alternative method 151. 3
Instructions: Please submit one application (Form C-144) per individue. Please be advised that approval of this request does not relieve the operator of habit	ial pit, closed-loop system, below-grade tank or alternative request
environment. Not does approval relieve the operator of its responsibility to comply with	
Out of the control of	OCDID#. 14520
Operator: Burlington Resources Oil & Gas Company, LP	OGRID#: 14538
Address: PO Box 4289, Farmington, NM 87499	
Facility or well name: Hudson J #3	
	D Permit Number:
U/L or Qtr/Qtr: E(SWNW) Section: 35 Township: 30N	Range: 12W County: San Juan
	ongitude: 108.072680' W NAD: X 1927 1983
Surface Owner: X Federal State Private Triba	al Trust or Indian Allotment
Pit: Subsection F or G of 19.15.17.11 NMAC	X Closed-loop Systems: Subsection H of 19.15.17.11 NMAC
Temporary: Drilling Workover	Drying Pad X Tanks Haul-off Bins Other:
Permanent Emergency Cavitation	Lined Unlined
Lined Unlined	Liner type: Thickness mil LLDPE HDPE PVC
Liner type: Thickness mil LLDPE HDPE PVC	Other:
Other String-Reinforced	Seams: Welded Factory Other:
Seams: Welded Factory Other	Volume:bblyd3
Volume:bbl Dimensions: LxWxD	Dimernsions: Length 45' x Width 10'
Below-grade tank: Subsection I of 19.15.17.11 NMAC	Fencing: Subsection D of 19.15 17.11 NMAC
Volume: bbl	Chain link, six feet in height, two strangs of barbed wire at top
Type of fluid:	Four foot height, four strands of barbed wire evenly spaced between
Tank Construction Material:	one and four feet
Secondary containment with leak detection	Netting: Subsection E of 19.15.17.11
Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	Screen Netting Other
Visible sidewalls and liner	Monthly inspections
Visible sidewalls only	Signs: Subsection C of 19.15.17.11 NMAC
Other:	12"x 24", 2" lettering, provided Operator's name, site location, and
Liner type: Thickness: mil HDPE PVC	emergency telephone numbers
Other:	X Signed in compliance with 19.15.3.103 NMAC
Alternative Method.	Administrative Appropriate and Executions.
Alternative Method: Submittal of an exception request is required. Exceptions must be	Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please
submitted to the Santa Fe Environmental Bureau office for consideration	refer to 19.15.17 NMAC for guidance.
of approval.	Please check a box if one or more of the following is requested, if not
	leave blank: Administrative approval(s): Requests must be submitted to the
	appropriate division district or the Santa Fe Environmental Bureau
	office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe
	Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.					
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	□No			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	□No			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No			
(Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	□NA				
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No			
(Applied to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	□NA				
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	□Yes	□No			
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.					
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	□Yes	□No			
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	—				
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	∐Yes	∐No			
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	□Yes	□No			
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	Yes	□No			
Society; Topographic map					
Within a 100-year floodplain - FEMA map	Yes	∐No			
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.	.9 NMAC				
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the d	ocuments ar	e attached.			
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintence Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC					
Previously Approved Design (attach copy of API Number: or Permit					
Closed-loop Systems Permit Application Attachment Checklist: Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC					
X Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC					
Previously Approved Design (attach copy of API Number:		ļ			

Form C-144 Oil Conservation Division Page 2 of 4

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC					
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are att	ached.				
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC					
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC					
Climatological Factors Assessment					
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC					
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC					
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC					
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC					
Quality Control/Quality Assurance Construction and Installation Plan					
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC					
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC					
Nussance or Hazardous Odors, including H2S, Prevention Plan					
Emergency Response Plan					
Oil Field Waste Stream Characterization					
Monitoring and Inspection Plan					
Erosion Control Plan					
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC					
Proposed Closure: 19.15.17.13 NMAC					
Type: Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank X Closed-loop System Altern	native				
Proposed Closure X Waste Excavation and Removal					
On-site Closure Method (only for temporary pits and closed-loop					
In-place On-site Trench					
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for	or				
Siting Critorio (recording on site elecure methods only): 10.15.17.10 NMAC					
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC					
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommentations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate					
district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of					
approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.					
Ground water is less than 50 feet below the bottom of the buried waste.					
	☐Yes ☐No				
- NM Office of the State Engineer - IWATERS database search; USGS; Data obtained from nearby wells	☐Yes ☐No ☐NA				
	□NA □Yes □No				
- NM Office of the State Engineer - tWATERS database search; USGS; Data obtained from nearby wells	□NA □				
 NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. 	∏NA ☐Yes ☐No ☐NA ☐Yes ☐No				
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□NA □ No □NA				
 NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. 	∏NA ☐Yes ☐No ☐NA ☐Yes ☐No				
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). 	NA Yes No NA Yes No NA NA				
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	NA Yes No NA Yes No NA Yes No				
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial 	NA Yes No NA Yes No NA NA				
 NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	NA Yes No NA Yes No NA Yes No Yes No				
 NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic 	NA Yes No NA Yes No NA Yes No				
 NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time 	NA Yes No NA Yes No NA Yes No Yes No				
 NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. 	NA Yes No NA Yes No NA Yes No Yes No				
- NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	NA Yes No NA Yes No NA Yes No Yes No				
- NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal	NA Yes No NA Yes No NA Yes No Yes No				
 NM Office of the State Engineer - tWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended 	NA Yes No NA Yes No NA Yes No Yes No				
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality	NA Yes No NA Yes No NA Yes No Yes No Yes No				
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland.	NA Yes No NA Yes No NA Yes No Yes No				
 NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended 	NA Yes No NA Yes No NA Yes No Yes No Yes No				
 NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No Yes No Yes No				
 NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No				
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No				
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No				
- NM Office of the State Engineer - tWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division Within an unstable area.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No				
 NM Office of the State Engineer - tWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division Within an unstable area. Engineering measures incorporated int	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No				

to the closure plan. Please indicfate, by a check mark in the box, that the documents are	Waste Excavation and Removal Closure Plan Checklist: (19.15.17 13 NMAC) Instructions: Each of the following items must be attached				
X Protocols and Procedures - based upon the appropriate requirements o					
Confirantion Sampling Plan (if applicable) - based upon the appropria					
X Disposal Facility Name and Permit Number (for Inquids, drilling fluids	-				
Soil Backfill and Cover Design Specifications - based upon the approp					
X Re-vegetation Plan - based upon the appropriate requirements of Subs					
X Site Reclamation Plan - based upon the appropriate requirements of Su	absection G of 19 15 17 13 NMAC				
Waste Removal Closure for Closed-loop Systems That Utilize Haul-off I facilities for the disposal of liquids, drilling fluids and drill cuttings.	Bins Only: (19 15 17 13 D NMAC) Instructions: Please identify the facility or				
Disposal Facility Name. Envirotech, Basin Disposal	Disposal Facility Permit Number. NM-01-0011 & NM-01-005				
On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the check mark in the box, that the documents are attached.	following items must bee attached to the closure plan. Please indicate, by a				
Siting Criteria Compliance Demonstrations - based upon the appropria	ite requirements of 19 15.17.10 NMAC				
Proof of Surface Owner Notice - based upon the appropriate requirem	-				
Construction and Design of Burial Trench (if applicable) based upon t	he appropriate requirements of 19.15.17.11 NMAC				
Protocols and Procedures - based upon the appropriate requirements o	f 19 15.17.13 NMAC				
Confirmation Sampling Plan (if applicable) - based upon the appropria	te requirements of Subsection F of 19.15.17.13 NMAC				
Waste Material Sampling Plan - based upon the appropriate requireme	nts of Subsection F of 19.15 17.13 NMAC				
Disposal Facility Name and Permit Number (for liquids, drilling fluids	and drill cuttings or in case on-site closure standards cannot be				
Soil Cover Design - based upon the appropriate requirements of Subse					
Re-vegetation Plan - based upon the appropriate requirements of Subs					
Site Reclamation Plan - based upon the appropriate requirements of Su	absection G of 19.15.17.13 NMAC				
Operator Application Certification:	and according to the back of my branch do and below				
I hereby certify that the information submitted with this application is true, accurat Name (Print). Crystal Tafova	Title: Regulatory Technician				
7 1 2 7 1					
Signature: Compton Capaya	Date. 7/18/2008				
e-mail address <u>crystal_tafoya@conocophillips.com</u>	Telephone: <u>505-326-9837</u>				
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Representative Signature: Approval Date: 7-25-08					
OCD Representative Signature:	7 00 00				
	7 00 00				
OCD Representative Signature: Ball Ball	Approval Date: 7-25-08 OCD Permit Number				
OCD Representative Signature: Boll Bull. Title: Enviro/Spec.	Approval Date: 7-25-08 OCD Permit Number				
OCD Representative Signature: Boll Bull. Title: Enviro/Spec.	Approval Date: 7-25-08 OCD Permit Number				
OCD Representative Signature: Title: Engl: 70/5 per Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method:	Approval Date: 7-25-08 OCD Permit Number				
OCD Representative Signature: Title: Eng. 70/5pec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method:	Approval Date: 7-25-08 OCD Permit Number 17.13 NMAC Closure Completion Date:				
OCD Representative Signature: Title: Env. 10/5 pec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached.	Approval Date: 7-25-08 OCD Permit Number 17.13 NMAC Closure Completion Date: ernative Closure				
OCD Representative Signature: Title: Env. ro 5 pec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice	Approval Date: 7-25-08 OCD Permit Number 17.13 NMAC Closure Completion Date: ernative Closure				
OCD Representative Signature: Title: Env. ro 5 pec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (1f applicable)	Approval Date: 7-25-08 OCD Permit Number 17.13 NMAC Closure Completion Date: ernative Closure				
OCD Representative Signature: Title: Env. ro 5 pec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice	Approval Date: 7-25-08 OCD Permit Number 17.13 NMAC Closure Completion Date: ernative Closure				
OCD Representative Signature: Title: Env.: ro/5pec. Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (1f applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results	Approval Date: 7-25-08 OCD Permit Number 17.13 NMAC Closure Completion Date: ernative Closure				
OCD Representative Signature: Title: Env. ro/5pec. Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (1f applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number	Approval Date: 7-25-08 OCD Permit Number 17.13 NMAC Closure Completion Date: ernative Closure				
OCD Representative Signature: Title: Env. 10 5 pec. Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation	Approval Date: 7-25-08 OCD Permit Number 17.13 NMAC Closure Completion Date: ernative Closure				
OCD Representative Signature: Title: Eng. co/spec. Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alterial In different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique	Approval Date: 7-25-08 OCD Permit Number 17.13 NMAC Closure Completion Date: ernative Closure				
OCD Representative Signature: Title: Env. 10 5 pec. Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation	Approval Date: 7-25-08 OCD Permit Number 17.13 NMAC Closure Completion Date: ernative Closure				
OCD Representative Signature: Title: Eng. ro 5 pec. Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alterial Interval Inte	Approval Date: 7-25-08 OCD Permit Number 17.13 NMAC Closure Completion Date: ernative Closure s must be attached to the closure report. Please inducate, by a check mark in the				
OCD Representative Signature: Title: Env. 10 5 pec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alterial State of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Waste Material Sampling Analytical Results Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is to	Approval Date: 7-25-08 OCD Permit Number 17.13 NMAC Closure Completion Date: ernative Closure s must be attached to the closure report. Please inducate, by a check mark in the Longitude: NAD: 1927 1983 1983 1984 1985 1985 1986 1986 1986 1986 1986 1986 1986 1986				
OCD Representative Signature: Title: Ery: ro 5 pec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alterial State of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (1f applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude	Approval Date: 7-25-08 OCD Permit Number 17.13 NMAC Closure Completion Date: ernative Closure s must be attached to the closure report. Please inducate, by a check mark in the Longitude: NAD: 1927 1983 1983 1984 1985 1985 1986 1986 1986 1986 1986 1986 1986 1986				
OCD Representative Signature: Title: Env. 10 5 pec. Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Alt If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (1f applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is tre closure complies with all applicable closure requirements and conditions specified in the applicable conditions of the following items to submitted with this closure report is tre closure complies with all applicable closure requirements and conditions specified in the applicable closure requirements.	Approval Date: 7-25-08 OCD Permit Number 17.13 NMAC Closure Completion Date: ernative Closure smust be attached to the closure report. Please inducate, by a check mark in the Longitude: NAD: 1927 1983 Le, accurate and complete to the best of my knowledge and belief 1 also certify that the proved closure plan				

Form C-144 Oil Conservation Division Page 4 of 4

WELL LOCATION AND ACERAGE DEDICATION PLAT

All distances must be from the outer boundaries of the Section.

Operator	. C C			Leas e	Hudson	·	! Well No)
Unit Letter	& Gas Compa	ny Township		Range	Coun.	·		<u> </u>
Ε	35	30 N	orth .	•	West	San Juan		
Actual Footage L	ocation of Well	10						
1750		North,_	ine cha	990		Tre West	line	
Ground Level 5 e			· · · · · · · · · · · · · · · · · · ·		in Dakota Victa Macay	erde (Ext)	Dedicated Avereage 320	e Acres
5857	Dakota						-	
1. Outline ti	ne acerage dedici	ated to the s	ubject well by	colored penc	II or hachure ma	rks on the plat be	low.	
2 If more tinterest and	than one lease : royalty),	s decicated t	to the well, o	utline each c	and identif, the	ownership there	of (both as to	working
3 If more to	than one lease o tization, unit zat	f different or Tun, force-po	wnership is de poling letc?	dicated to th	ne well, have the	e interests of all i	owners been cor	nso! dated
(X) Yes	: No	If answer is	"ves," type c	f consclidation	Commun	itization		
	"no," list the ow		ct description	s which have	actually conso	lidates (Use reve	erse side of thi	s form if
No allowable	e will be assigned	to the well u				"by communitizat eer approved by t		forced-
		·						
					WELLIEV.	CER	TIFICATI	0 N
				4 3	371.[]4 FF	A sample mande	fy that the inform	-A:
		,		1	MLO 196	herein is true a	ry man the intormi nd complete to th	
		12	- 	 -	JUN 2 196	Office ledge and be	lief,	
			1	1				
	_	L _ L	_ + +		OIL CONT.	CRIGINAL S	ICHED BY 10E	C SALMON
	1750		; 1	1			C. Salmon	
	117			, I		Position	.00	
					7		lct Superint	endent
- 9901	_ .	,	}	ł		Company	Odland Cad	
9	+	├	- + - +	+ -		Late Az Geo.	Oil and Gas	·
	1		1	ł		May 2	7, 1966	
		Sec					•	
		3 6				I kereby certif	y that the well loc	ation shown on
1 '				į			otted from field n	
h – +	+	├ - ┼ ·	- + - +	-, +-	N	. ,	me or under my s	
١	i İ	١ ا	1	1			true and correct to	the best of my
		 			_	knowledge and b	eliet.	
				•				
		<u> </u>	1	t .		Date Surveyed		
├ - ┤		- † ·	- + †	- + -	1	March 31,	1966	
			!	.)	Registered Francs and/or Land Surv	sional Engineer	
<u> </u>		<u> </u>				6017		do
							Chi Ma	W K
						Certificate No. 3	0U2	}

Burlington Resources Oil & Gas Company, LP Closed-loop Plans

Closed-loop Design Plan

BR's closed loop system will not entail a drying pad, temporary pit, below grade tank or sump. It will include an above ground tank suitable for holding the cuttings and fluids for rig operations. The tank will be sufficient volume to maintain a safe free board between disposal of the liquids and solids from rig operations.

- 1. Fencing is not required for an above ground closed-loop system
- 2. It will be signed in compliance with 19.15.3.103 NMAC
- 3. A frac tank will be on location to store fresh water

Closed-loop Operating and Maintenance Plan

BR will be using two tanks to complete the workover process. One will be used for to prepare and the other will be used for installation. BR's closed-loop tank will be operated and maintained to contain liquids and solids in order to prevent contamination of fresh water sources, in order to protect public health and the environment. To ensure the operation is maintained the following steps will be followed:

- 1. The liquids will be vacuumed out and disposed of at the Basin Disposal facility (Permit # NM-01-005). Solids in the closed-loop tank will be vacuumed out and disposed of at Envirotech (Permit # NM-01-0011) on a periodic basis to prevent over topping.
- 2. No hazardous waste, miscellaneous solid waste or debris will be discharged into or stored in the tank. Only fluids or cutting used or generated by rig operations will be placed or stored in the tank.
- 3. The division district office will be notified within 48 hours of the discovery of compromised integrity of the closed-loop tank. Upon the discovery of the compromised tank, repairs will be enacted immediately
- 4. All of the above operations will be inspected and a log will be signed and dated. During rig operations the inspection will be daily.

Closed-loop Closure Plan

The closed-loop tank will be closed in accordance with 19.15.17.13. This will be done by transporting cuttings and all remaining sludges to Envirotech (Permit # NM-01-0011) immediately following rig operations. All remaining liquids will be transported and disposed of in the Basin Disposal facility (Permit # NM-01-005). The tanks will be removed from the location as part of the rig move. At time of well abandonment, the site will be reclaimed and re-vegetated to pre-existing conditions when possible.