District I

1625 N French Dr , Hobbs, NM 88240

District II

1301 W. Grand Ave , Artesia, NM 88210

District III

1000 Rio Brazos Rd , Aztec, NM 87410

District IV

State of New Mexico
Energy Minerals and Natural Resources
Department

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-144 June 16, 2008

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application RCVD JUL 18 '08 Type of action: | X | Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop system, below-grade tank, or proposed alternative method | Closure Of a pit, closed-loop

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of hab environment. Nor does approval relieve the operator of its responsibility to comply w	
Operator: Burlington Resources Oil & Gas Company, LP	OGRID#: 14538
Address: PO Box 4289, Farmington, NM 87499	
Facility or well name: Neudecker Com #291	
API Number: 30-045-30549 OC	CD Permit Number:
U/L or Qtr/Qtr: M(SWSW) Section: 13 Township: 29N	Range: 10W County: San Juan
	Longitude:107.8414300' W NAD: X 1927 1983
Surface Owner: X Federal State Private Trib	al Trust or Indian Allotment
Pit: Subsection F or G of 19.15.17.11 NMAC	X Closed-loop Systems: Subsection H of 19.15.17.11 NMAC
Temporary: Drilling Workover	Drying Pad X Tanks Haul-off Bins Other:
Permanent Emergency Cavitation	Lined Unlined
Lined Unlined	Liner type: Thickness mil LLDPE HDPE PVC
Liner type: ThicknessmilLLDPEHDPEPVC	Other:
Other String-Reinforced	Seams: Welded Factory Other:
Seams: Welded Factory Other	Volume: 500 bbl 104 yd3
Volume:bbl Dimensions: LxWxD	Dimernsions: Length 45' x Width 10'
Below-grade tank: Subsection I of 19.15.17 11 NMAC	Fencing: Subsection D of 19 15.17.11 NMAC
Volume:bbl	Chain link, six feet in height, two strangs of barbed wire at top
Type of fluid:	Four foot height, four strands of barbed wire evenly spaced between
Tank Construction Material:	one and four feet
Secondary containment with leak detection	Netting: Subsection E of 19.15.17.11
Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	Screen Netting Other
Visible sidewalls and liner	Monthly inspections
Visible sidewalls only	Signs: Subsection C of 19.15.17.11 NMAC
Other:	12"x 24", 2" lettering, provided Operator's name, site location, and
Liner type: Thickness:mil HDPE PVC	emergency telephone numbers
Other:	X Signed in compliance with 19.15.3.103 NMAC
Alternative Method:	Administrative Approvals and Exceptions:
Submittal of an exception request is required. Exceptions must be	Justifications and/or demonstrations of equivalency are required. Please
submitted to the Santa Fe Environmental Bureau office for consideration of approval.	refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not
"	leave blank:
	Administrative approval(s): Requests must be submitted to the
	appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan)
	Exception(s): Requests must be submitted to the Santa Fe
	Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.					
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - IWATERS database search; USGS; Data obtained from nearby wells	Yes	□No			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	□Yes	□No			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	□Yes	□No			
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)	ΠNA				
- Visual inspection (certification) of the proposed site; Acrial photo; Satellite image					
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No			
(Applied to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	∐NA				
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.					
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.					
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended					
- Written confirmation or verification from the municipality; Written approval obtained from the municipality					
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site					
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	□No			
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes	No			
Within a 100-year floodplain - FEMA map	∐Yes	∐No			
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.	9 NMAC				
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.					
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintence Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC					
Previously Approved Design (attach copy of API Number: or Permit					
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC					
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC X Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC					
Previously Approved Design (attach copy of API Number:					

	Permanent Pits Permit Application Checklist: Subsection B of 19 15.17.9 NMAC					
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.						
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC						
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC						
Climatological Factors Assessment						
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC						
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC						
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC						
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC						
Quality Control/Quality Assurance Construction and Installation Plan						
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC						
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC						
Nuisance or Hazardous Odors, including H2S, Prevention Plan						
Emergency Response Plan						
Oil Field Waste Stream Characterization						
Monttoring and Inspection Plan						
Erosion Control Plan						
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC						
Proposed Closure: 19.15.17.13 NMAC						
Type: Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank X Closed-loop System Altern	native					
Type. Drining Workers Emergency Carnation Tremation in Delow-grade rank Microsco-toop system Emergency	iative					
Proposed Closure X Waste Excavation and Removal						
On-site Closure Method (only for temporary pits and closed-loop						
In-place On-site Trench						
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau fo	or					
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC						
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommentations of acceptable source						
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate						
district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of						
approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.						
Ground water is less than 50 feet below the bottom of the buried waste.	☐Yes ☐No					
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□Yes □No □NA					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□NA □					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste	□NA □Yes □No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells 	□NA □Yes □No □NA					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	NA					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa later 	NA Yes No NA Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). 	NA					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	NA Yes No NA Yes No NA Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). 	NA					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	NA Yes No NA Yes No NA Yes No Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic 	NA Yes No NA Yes No NA Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time	NA Yes No NA Yes No NA Yes No Yes No					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. 	NA Yes No NA Yes No NA Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	NA Yes No NA Yes No NA Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal	NA Yes No NA Yes No NA Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	NA Yes No NA Yes No NA Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal	NA Yes No NA Yes No NA Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	NA Yes No NA Yes No NA Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality	NA Yes No NA Yes No NA Yes No Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine.	NA Yes No NA Yes No NA Yes No Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division Within an unstable area.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division Within an unstable area.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No					
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No					

Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicfate, by a check mark in the box, that the documents are attached.					
To the closure plan. Please inalcjaie, by a check mark in the box, that the accuments are attached. To the closure plan. Please inalcjaie, by a check mark in the box, that the accuments are attached. To the closure plan. Please inalcjaie, by a check mark in the box, that the accuments are attached. To the closure plan. Please inalcjaie, by a check mark in the box, that the accuments are attached. To the closure plan. Please inalcjaie, by a check mark in the box, that the accuments are attached. To the closure plan. Please inalcjaie, by a check mark in the box, that the accuments are attached. To the closure plan. Please inalcjaie, by a check mark in the box, that the accuments are attached. To the closure plan. Please inalcjaie, by a check mark in the box, that the accuments are attached. To the closure plan. Please inalcjaie, by a check mark in the box, that the box is a check mark in the box. The content is a check mark in the box in the box is a check mark in the box. The check mark in the box is a check mark in the box. The check mark in the box is a check mark in the box is a check mark in the box. The check mark in the box is a check mark in the box is a check mark in the box is a check mark in the box. The check mark in the box is a check mark i					
Confiramtion Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15.17.13 NMAC					
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)					
Soil Backfill and Cover Design Specifications - based upon the appro					
X Re-vegetation Plan - based upon the appropriate requirements of Sub-					
X Site Reclamation Plan - based upon the appropriate requirements of S	subsection G of 19 15.17.13 NMAC				
Waste Removal Closure for Closed-loop Systems That Utilize Haul-off	Bins Only: (19 15 17 13 D NMAC) Instructions: Please identify the facility or				
facilities for the disposal of liquids, drilling fluids and drill cuttings. Disposal Facility Name: Envirotech, Basin Disposal	Disposal Facility Permit Number NM-01-0011 & NM-01-005				
On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the check mark in the box, that the documents are attached.	e following items must bee attached to the closure plan. Please indicate, by a				
Siting Criteria Compliance Demonstrations - based upon the appropri	ate requirements of 19.15.17.10 NMAC				
Proof of Surface Owner Notice - based upon the appropriate requiren	nents of Subsection F of 19.15.17 13 NMAC				
Construction and Design of Burial Trench (if applicable) based upon	the appropriate requirements of 19.15.17 11 NMAC				
Protocols and Procedures - based upon the appropriate requirements of					
Confirmation Sampling Plan (if applicable) - based upon the appropri	•				
Waste Material Sampling Plan - based upon the appropriate requirem					
Disposal Facility Name and Permit Number (for liquids, drilling fluid	-				
Soil Cover Design - based upon the appropriate requirements of Subs	·				
Re-vegetation Plan - based upon the appropriate requirements of Substitution Plan - based upon the appropriate requirements of S					
Operator Application Certification:	descending of 12.13.17 13 Market				
I hereby certify that the information submitted with this application is true, accura	te and complete to the best of my knowledge and belief				
Name (Print): Crystal Tafoya	Title: Regulatory Technician				
Signature. Constal Tologo	Date. 7/18/2008				
e-mail address <u>crystal tafoya@conocoptafllips.com</u>	Telephone: 505-326-9837				
OCD Approval: Permit Application (including closure plan) Closure Plan (only)					
OCD Approval: Permit Application (including closure plan)	Closure Plan (only)				
OCD Approval: Pennit Application (including closure plan) OCD Representative Signature:	Closure Plan (only) Approval Date: 7-29-08				
OCD Representative Signature: Brand Fell					
OCD Representative Signature: Brand Sell	Approval Date: 7-29-08				
OCD Representative Signature: Brand Fell	Approval Date: 7-29-08 OCD Permit Number 17 13 NMAC				
OCD Representative Signature: Brand Sell Title: Eurino/spec	Approval Date: 7-29-08 OCD Permit Number				
OCD Representative Signature: Title: Eusino Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method:	Approval Date: 7-29-08 OCD Permit Number 17 13 NMAC Closure Completion Date:				
OCD Representative Signature: Title: Funt Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure	Approval Date: 7-29-08 OCD Permit Number 17 13 NMAC				
OCD Representative Signature: Title: Eurino Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure All If different from approved plan, please explain	Approval Date: 7-29-08 OCD Permit Number: 17 13 NMAC Closure Completion Date: ternative Closure				
OCD Representative Signature: Title: Euring Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Al If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following item	Approval Date: 7-29-08 OCD Permit Number: 17 13 NMAC Closure Completion Date: ternative Closure				
OCD Representative Signature: Title: Eurino Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure All If different from approved plan, please explain	Approval Date: 7-29-08 OCD Permit Number: 17 13 NMAC Closure Completion Date: ternative Closure				
OCD Representative Signature: Title: Eurino Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure All of different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following item box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable)	Approval Date: 7-29-08 OCD Permit Number: 17 13 NMAC Closure Completion Date: ternative Closure				
OCD Representative Signature: Title: Eurino Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure All of different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following item box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan	Approval Date: 7-29-08 OCD Permit Number: 17 13 NMAC Closure Completion Date: ternative Closure				
OCD Representative Signature: Title: Eurino Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure All of different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following item box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable)	Approval Date: 7-29-08 OCD Permit Number: 17 13 NMAC Closure Completion Date: ternative Closure				
OCD Representative Signature: Title: Eurino Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Al If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following item box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results	Approval Date: 7-29-08 OCD Permit Number: 17 13 NMAC Closure Completion Date: ternative Closure				
OCD Representative Signature: Title: Eurico Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure Al If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following item box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation	Approval Date: 7-29-08 OCD Permit Number: 17 13 NMAC Closure Completion Date: ternative Closure				
OCD Representative Signature: Title: Eurico Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure All of different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following item box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique	Approval Date: 7-29-08 OCD Permit Number: 17 13 NMAC Closure Completion Date: ternative Closure				
OCD Representative Signature: Title: Eusico Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure All of different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following item box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)	OCD Permit Number 17 13 NMAC Closure Completion Date: ternative Closure is must be attached to the closure report. Please indicate, by a check mark in the				
OCD Representative Signature: Title: Eurico Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure All of different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following item box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique	Approval Date: 7-29-08 OCD Permit Number: 17 13 NMAC Closure Completion Date: ternative Closure				
OCD Representative Signature: Title: Eusico Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure All of different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following item box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)	OCD Permit Number 17 13 NMAC Closure Completion Date: ternative Closure is must be attached to the closure report. Please indicate, by a check mark in the				
OCD Representative Signature: Title: Eusino Spec Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure All of different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following item box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude:	Approval Date: 7-29-08 OCD Permit Number: 17 13 NMAC Closure Completion Date: ternative Closure si must be attached to the closure report. Please indicate, by a check mark in the Longitude: NAD: 1927 1983 ue, accurate and complete to the best of my knowledge and belief Lalso certify that the				
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following item box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Waste Material Sampling Analytical Results Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude: Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is tr	Approval Date: 7-29-08 OCD Permit Number: 17 13 NMAC Closure Completion Date: ternative Closure si must be attached to the closure report. Please indicate, by a check mark in the Longitude: NAD: 1927 1983 ue, accurate and complete to the best of my knowledge and belief Lalso certify that the				
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 Closure Method: Waste Excavation and Removal On-Site Closure All If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following item box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude: Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is trelowire complies with all applicable closure requirements and conditions specified in the agents.	Approval Date: 7-39-08 OCD Permit Number: 17 13 NMAC Closure Completion Date: ternative Closure is must be attached to the closure report. Please indicate, by a check mark in the Longitude: NAD: 1927 1983 The proved closure plan				

Form C-144 Oil Conservation Division Page 4 of 4

DISTRICT 1 P.O. Box 1980, Hobbs, N.M. 88241-1980

DISTRICT II P.O. Drawer DD, Artesia, N.M. 88211-0719

DISTRICT III 1001) Rio Brazos Rd., Aztec, N.M. 87410

DISTRICT IV PO Box 2088, Santa Fe, NM 87504-2088

API Number

30~045-

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, NM 87504-2088

² Pool Code

71629 -

Form C-102 Revised February 21, 1994 Instructions on back

Submit to Appropriate District Office State Lease — 4 Copies Fee Lease — 3 Copies

³ Pool Name

Basin Fruitland Coal

☐ AMENDED REPORT

Well Number

WELL LOCATION AND ACREAGE DEDICATION PLAT

Property Con	de O	⁵ Property Name						•	* Well Number 291	
7803	3	NEUDECKER COM								
7 OGRID No.	'	*Operator Name *Elevati BURLINGTON RESOURCES OIL AND GAS, INC. 5858					5858'			
14538										
Surface Location UL or lot no. Section Township Range Lot Idn Feet from the North/South line Feet from the East/West line County										
UL or lot no.	Section 13	Iownship 29-N	Range 10-W	Lot Idn	1205	SOUTH	1005	WEST	County SAN JUAN	
11 Bottom Hole Location If Different From Surface										
UL or tot no. Section Township Range			Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County		
12 Dedicated Acres	3	1 <u>",</u>	Joint or Infill	l	14 Consolidation C	ode	¹⁸ Order No.	<u> </u>		
W/319.8	}							•		
NO ALLO	WABLE	WILL BE	ASSIGNE	D TO TI	HIS COMPLET	TION UNTIL ALL	INTERESTS	HAVE BEEN	CONSOLIDATED	
		OR A	NON-ST	ANDARD	UNIT HAS E	BEEN APPROVE	BY THE D	IVISION		
16				7			17	OPERATOR (CERTIFICATION	
				1				ify that the information aplete to the best of m	contained herein is	
[USA SF	-01772-A		1)		·	Tue and con	aprece to the best or my	A Knowledge and Daker	
LOT 4		L L	.OT 3		LOT 2	LOT 1	1			
L		_1		<u>il </u>		·			4	
Γ				1			1	/	rl	
	} 1	! !				-	Signature	994	ll	
LOT 5		Lot	Т 6	1	LOT 7	LOT 8	Pegg	y Cole		
USA SF-0	079509					,	Printed Nome Regulatory Supervisor			
	1	Title .								
L							12-8.	00		
B.L.M. 1967		1		11			18	SURVEYOR C	ERTIFICATION	
13							I hereby c	ertify that the well la	cation shown on this plat	
LOT 11	•		OT 10		LOT 9	•			actual surveys made by me the same is true and	
741 Ze65.00	USA						the best of mix Weller	M. PL		
11 - "	36'43.3' N.	1		1				\$176A	(E) = 1	
1 LONG. =1	0750.5' W.	· 		-i 		 	Date of Signature	Lord Lord PHICA	sloval Surveyor	
E C				1				12/ D	7 787	
1-2		•		1				Te.		
100 LOT 12	in	Lo	T 13) of Calon		
z	1205				. (02)	8894		
11-4	. 1	N 86-39-	10 E	; FD. 3	1/2" BC.	1	Cartifica	to Number		

Burlington Resources Oil & Gas Company, LP Closed-loop Plans

Closed-loop Design Plan

BR's closed loop system will not entail a drying pad, temporary pit, below grade tank or sump. It will include an above ground tank suitable for holding the cuttings and fluids for rig operations. The tank will be sufficient volume to maintain a safe free board between disposal of the liquids and solids from rig operations.

- 1. Fencing is not required for an above ground closed-loop system
- 2. It will be signed in compliance with 19.15.3.103 NMAC
- 3. A frac tank will be on location to store fresh water

Closed-loop Operating and Maintenance Plan

BR will be using two tanks to complete the workover process. One will be used for to prepare and the other will be used for installation. BR's closed-loop tank will be operated and maintained to contain liquids and solids in order to prevent contamination of fresh water sources, in order to protect public health and the environment. To ensure the operation is maintained the following steps will be followed:

- 1. The liquids will be vacuumed out and disposed of at the Basin Disposal facility (Permit # NM-01-005). Solids in the closed-loop tank will be vacuumed out and disposed of at Envirotech (Permit # NM-01-0011) on a periodic basis to prevent over topping.
- 2. No hazardous waste, miscellaneous solid waste or debris will be discharged into or stored in the tank. Only fluids or cutting used or generated by rig operations will be placed or stored in the tank.
- 3. The division district office will be notified within 48 hours of the discovery of compromised integrity of the closed-loop tank. Upon the discovery of the compromised tank, repairs will be enacted immediately
- 4. All of the above operations will be inspected and a log will be signed and dated. During rig operations the inspection will be daily.

Closed-loop Closure Plan

The closed-loop tank will be closed in accordance with 19.15.17.13. This will be done by transporting cuttings and all remaining sludges to Envirotech (Permit # NM-01-0011) immediately following rig operations. All remaining liquids will be transported and disposed of in the Basin Disposal facility (Permit # NM-01-005). The tanks will be removed from the location as part of the rig move. At time of well abandonment, the site will be reclaimed and re-vegetated to pre-existing conditions when possible.