UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIMED

AUG 01 2008

		,
Sundry Notices and Reports on Wells	Bureau of Lari	i Management Field Office
	Earmingiou 5.	Lease Number
	<i>J.</i>	SF-080674
1. Type of Well	4	
GAS	6.	If Indian, All. or
UAS		Tribe Name
	7.	Unit Agreement Name
2. Name of Operator		
Burlington		
RESOURCES OIL & GAS COMPANY LP		San Juan 27-4 Unit
TIEGGGI IGEG OIL & GAS COMPANT LI	 8.	Well Name & Number
3. Address & Phone No. of Operator	3.	Well Name & Number
. Address & I hole 110. of Operator		San Juan 27-4 Unit 141
DO Poy 4280 Farmington NM 97400 (505) 226 0700	9.	API Well No.
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
	- 	30-039-30267
Location of Well, Footage, Sec., T, R, M		JU VOJ DVEVI
	10.	Field and Pool
Unit O (SWSE), 430' FSL & 2465' FWL, Section 15, T27N, R4W,	NMPM	Basin DK/Blanco MV
n (sesw)		
- Carre 1	11.	County and State
		Rio Arriba Co., NM
Final AbandonmentAltering CasingConversion to In	gection	OIL CONS. DIV. DIST. 3
13. Describe Proposed or Completed Operations 7/71/08 H&P 282. NU BOP. RIH w/ 8 3/4" bit & PT csg to 600#/30 mins Reached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 of Lead 447 sx (1162 cf – 207 bbls slurry) Type III, w/3% Bentonite, 5#/sx 50/50 POZ, w/2% Bentonite, 6#/sx Pheno seal. Dropped plug & displaced to 1200#. 7/22/08 sundry filed for TOC @ 660'. WOC. 7/21/08 @ 2200 to 7/23/08 D/O cmt. Drill ahead to 8400' TD. TD reached 7/24/08. Circ hole Csg & set @ 8397'. Pre-flush 10 bbls chemwash & 2 bbls FW. Tail 430 s .2% CFR3-L, .8% Halad (R) 9, 3.5#/sx Pheno seal. Dropped plug & displaced	4 - test good. D/O cmt & dr ", 20#, J-55 ST&C csg & se x Pheno seal. Tail 103 sx (no cmt to surface 7/21/08 (hrs PT csg to 2000#/30 mins e. RIH w/202 jts, 4 ½", 10 ex (624 cf - 111 bbls slurry)	DIST. 3 Ill ahead to 4223' interm TD at @ 4222'. Pre-flush ahead 137 cf - 26 bbls slurry) © 0300 hrs. Bumped plug a - test good. 5/11.6#, J-55 ST&C/LT&C 50/50 POZ standard, w/
13. Describe Proposed or Completed Operations 7/71/08 H&P 282. NU BOP. RIH w/ 8 3/4" bit & PT csg to 600#/30 mins Reached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 of Lead 447 sx (1162 cf – 207 bbls slurry) Type III, w/3% Bentonite, 5#/ss 50/50 POZ, w/2% Bentonite, 6#/sx Pheno seal. Dropped plug & displaced to 1200#. 7/22/08 sundry filed for TOC @ 660'. WOC. 7/21/08 @ 2200 17/23/08 D/O cmt. Drill ahead to 8400' TD. TD reached 7/24/08. Circ hole Csg & set @ 8397'. Pre-flush 10 bbls chemwash & 2 bbls FW. Tail 430 s .2% CFR3-L, .8% Halad (R) 9, 3.5#/sx Pheno seal. Dropped plug & displa ND BOP & NU WH. RD & RR 7/25/08. PT will be conducted by the completion rig & recorded on next report. TO 14. I hereby certify that the foregoing is true and correct.	s – test good. D/O cmt & dr. ", 20#, J-55 ST&C csg & sex Pheno seal. Tail 103 sx (no cmt to surface 7/21/08 @ hrs PT csg to 2000#/30 mins e. RIH w/202 jts, 4 ½", 10. ex (624 cf – 111 bbls slurry) aced w/130 bbls FW. Bump	DIST. 3 Ill ahead to 4223' interm TD at @ 4222'. Pre-flush ahead 137 cf – 26 bbls slurry) @ 0300 hrs. Bumped plug is – test good. 5/11.6#, J-55 ST&C/LT&C 50/50 POZ standard, w/ yed plug @ 0213 hrs.
13. Describe Proposed or Completed Operations 7/71/08 H&P 282. NU BOP. RIH w/8 3/4" bit & PT csg to 600#/30 mins Reached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 of Lead 447 sx (1162 cf – 207 bbls slurry) Type III, w/3% Bentonite, 5#/ss 50/50 POZ, w/2% Bentonite, 6#/sx Pheno seal. Dropped plug & displaced to 1200#. 7/22/08 sundry filed for TOC @ 660'. WOC. 7/21/08 @ 2200 ft 7/23/08 D/O cmt. Drill ahead to 8400' TD. TD reached 7/24/08. Circ hole Csg & set @ 8397'. Pre-flush 10 bbls chemwash & 2 bbls FW. Tail 430 s 2% CFR3-L, .8% Halad (R) 9, 3.5#/sx Pheno seal. Dropped plug & displa ND BOP & NU WH. RD & RR 7/25/08. PT will be conducted by the completion rig & recorded on next report. TO 14. I hereby certify that the foregoing is true and correct.	s – test good. D/O cmt & dr. ", 20#, J-55 ST&C csg & sex Pheno seal. Tail 103 sx (no cmt to surface 7/21/08 @ hrs PT csg to 2000#/30 mins e. RIH w/202 jts, 4 ½", 10. ex (624 cf – 111 bbls slurry) aced w/130 bbls FW. Bump	DIST. 3 Ill ahead to 4223' interm TD at @ 4222'. Pre-flush ahead 137 cf - 26 bbls slurry) @ 0300 hrs. Bumped plug a - test good. 5/11.6#, J-55 ST&C/LT&C 50/50 POZ standard, w/ yed plug @ 0213 hrs.
13. Describe Proposed or Completed Operations 7/71/08 H&P 282. NU BOP. RIH w/ 8 3/4" bit & PT csg to 600#/30 mins Reached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 of Lead 447 sx (1162 cf – 207 bbls slurry) Type III, w/3% Bentonite, 5#/ss 50/50 POZ, w/2% Bentonite, 6#/sx Pheno seal. Dropped plug & displaced to 1200#. 7/22/08 sundry filed for TOC @ 660'. WOC. 7/21/08 @ 2200 j 7/23/08 D/O cmt. Drill ahead to 8400' TD. TD reached 7/24/08. Circ hole Csg & set @ 8397'. Pre-flush 10 bbls chemwash & 2 bbls FW. Tail 430 s .2% CFR3-L, .8% Halad (R) 9, 3.5#/sx Pheno seal. Dropped plug & displa ND BOP & NU WH. RD & RR 7/25/08. PT will be conducted by the completion rig & recorded on next report. TO 14. I hereby certify that the foregoing is true and correct. Signed Rhonda Roge (This space for Federal or State Office use)	te-test good. D/O cmt & dr. ", 20#, J-55 ST&C csg & sex. R Pheno seal. Tail 103 sx (no cmt to surface 7/21/08 (hrs PT csg to 2000#/30 minste. RIH w/202 jts, 4 ½", 10. sx (624 cf - 111 bbls slurry) aced w/130 bbls FW. Bump C will be reported on next rest. Title Regulatory Techn.	DIST. 3 Ill ahead to 4223' interm TD at @ 4222'. Pre-flush ahead 137 cf - 26 bbls slurry) @ 0300 hrs. Bumped plug a - test good. 5/11.6#, J-55 ST&C/LT&C 50/50 POZ standard, w/ ed plug @ 0213 hrs.
13. Describe Proposed or Completed Operations 7/71/08 H&P 282. NU BOP. RIH w/ 8 3/4" bit & PT csg to 600#/30 mins Reached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 of Lead 447 sx (1162 cf – 207 bbls slurry) Type III, w/3% Bentonite, 5#/ss 50/50 POZ, w/2% Bentonite, 6#/sx Pheno seal. Dropped plug & displaced to 1200#. 7/22/08 sundry filed for TOC @ 660'. WOC. 7/21/08 @ 2200 ft/23/08 D/O cmt. Drill ahead to 8400' TD. TD reached 7/24/08. Circ hole Csg & set @ 8397'. Pre-flush 10 bbls chemwash & 2 bbls FW. Tail 430 s 2.2% CFR3-L, .8% Halad (R) 9, 3.5#/sx Pheno seal. Dropped plug & displa ND BOP & NU WH. RD & RR 7/25/08. PT will be conducted by the completion rig & recorded on next report. TO 14. I hereby certify that the foregoing is true and correct. Signed Rhonda Roge (This space for Federal or State Office use) APPROVED BY	te-test good. D/O cmt & dr. ", 20#, J-55 ST&C csg & sex. R Pheno seal. Tail 103 sx (no cmt to surface 7/21/08 (hrs PT csg to 2000#/30 minste. RIH w/202 jts, 4 ½", 10. sx (624 cf - 111 bbls slurry) aced w/130 bbls FW. Bump C will be reported on next rest. Title Regulatory Techn.	DIST. 3 Ill ahead to 4223' interm TE at @ 4222'. Pre-flush ahead 137 cf - 26 bbls slurry) @ 0300 hrs. Bumped plug s - test good. 5/11.6#, J-55 ST&C/LT&C 50/50 POZ standard, w/ yed plug @ 0213 hrs. eport. Ill ahead to 4223' interm TE at 223' interm
13. Describe Proposed or Completed Operations 7/71/08 H&P 282. NU BOP. RIH w/ 8 3/4" bit & PT csg to 600#/30 mins Reached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/ss 50/50 POZ, w/2% Bentonite, 6#/sx Pheno seal. Dropped plug & displaced to 1200#. 7/22/08 sundry filed for TOC @ 660'. WOC. 7/21/08 @ 2200 ft/23/08 D/O cmt. Drill ahead to 8400' TD. TD reached 7/24/08. Circ hole Csg & set @ 8397'. Pre-flush 10 bbls chemwash & 2 bbls FW. Tail 430 s 2% CFR3-L, .8% Halad (R) 9, 3.5#/sx Pheno seal. Dropped plug & displa ND BOP & NU WH. RD & RR 7/25/08. PT will be conducted by the completion rig & recorded on next report. TO 14. I hereby certify that the foregoing is true and correct. Signed Rhonda Roge This space for Federal or State Office use) APPROVED BY Title CONDITION OF APPROVAL, if any:	to test good. D/O cmt & dr. ", 20#, J-55 ST&C csg & sec. R Pheno seal. Tail 103 sx (no cmt to surface 7/21/08 (hrs PT csg to 2000#/30 minste. RIH w/202 jts, 4 ½", 10. sx (624 cf - 111 bbls slurry) aced w/130 bbls FW. Bump C will be reported on next restricted. Title Regulatory Techn	DIST. 3 All ahead to 4223' interm TI at @ 4222'. Pre-flush ahead 137 cf – 26 bbls slurry) @ 0300 hrs. Bumped plug at 15/11.6#, J-55 ST&C/LT&C 50/50 POZ standard, w/ and plug @ 0213 hrs. Peport. Cian Date 07/31/08
13. Describe Proposed or Completed Operations 17/1/08 H&P 282. NU BOP. RIH w/8 3/4" bit & PT csg to 600#/30 mins 18. Reached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 16 Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/ss 160/50 POZ, w/2% Bentonite, 6#/sx Pheno seal. Dropped plug & displaced to 1200#. 7/22/08 sundry filed for TOC @ 660'. WOC. 7/21/08 @ 2200 ft/23/08 D/O cmt. Drill ahead to 8400' TD. TD reached 7/24/08. Circ hole csg & set @ 8397'. Pre-flush 10 bbls chemwash & 2 bbls FW. Tail 430 strength 22% CFR3-L, .8% Halad (R) 9, 3.5#/sx Pheno seal. Dropped plug & displand BOP & NU WH. RD & RR 7/25/08. 19. Twill be conducted by the completion rig & recorded on next report. TO gigned	to test good. D/O cmt & dr. ", 20#, J-55 ST&C csg & sec. R Pheno seal. Tail 103 sx (no cmt to surface 7/21/08 (hrs PT csg to 2000#/30 minste. RIH w/202 jts, 4 ½", 10. sx (624 cf - 111 bbls slurry) aced w/130 bbls FW. Bump C will be reported on next restricted. Title Regulatory Techn	DIST. 3 Ill ahead to 4223' interm TI It @ 4222'. Pre-flush ahead 137 cf - 26 bbls slurry) @ 0300 hrs. Bumped plug s - test good. 5/11.6#, J-55 ST&C/LT&C 50/50 POZ standard, w/ (ed plug @ 0213 hrs. eport. cian Date 07/31/08
13. Describe Proposed or Completed Operations 17/1/08 H&P 282. NU BOP. RIH w/8 3/4" bit & PT csg to 600#/30 mins 18. Reached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 15. Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/ss 15. 60/50 POZ, w/2% Bentonite, 6#/sx Pheno seal. Dropped plug & displaced to 1200#. 7/22/08 sundry filed for TOC @ 660'. WOC. 7/21/08 @ 2200 ft/23/08 D/O cmt. Drill ahead to 8400' TD. TD reached 7/24/08. Circ hole csg & set @ 8397'. Pre-flush 10 bbls chemwash & 2 bbls FW. Tail 430 strength 22% CFR3-L, 8% Halad (R) 9, 3.5#/sx Pheno seal. Dropped plug & displand BOP & NU WH. RD & RR 7/25/08. 14. I hereby certify that the foregoing is true and correct. 15. Signed Rhonda Roge 16. This space for Federal or State Office use) 17. APPROVED BY Title 18. USC. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the 18 USC. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the 18 USC. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the 18 USC. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the 18 USC. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the 18 USC. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the 18 USC. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the 18 USC. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the 18 USC. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the 18 USC. Section 1001, makes it a crime for any person knowingly and will fully to make any department or agency of the 18 USC. Section 1001 it is a crime for any person	to test good. D/O cmt & dr. ", 20#, J-55 ST&C csg & sec. R Pheno seal. Tail 103 sx (no cmt to surface 7/21/08 (hrs PT csg to 2000#/30 minste. RIH w/202 jts, 4 ½", 10. sx (624 cf - 111 bbls slurry) aced w/130 bbls FW. Bump C will be reported on next restricted. Title Regulatory Techn	DIST. 3 All ahead to 4223' interm TI of @ 4222'. Pre-flush ahead 137 cf - 26 bbls slurry) By 0300 hrs. Bumped plug a - test good. S/11.6#, J-55 ST&C/LT&C 50/50 POZ standard, w/ (ed plug @ 0213 hrs.) By 13 hrs. Cian Date 07/31/08 Date
13. Describe Proposed or Completed Operations 17/71/08 H&P 282. NU BOP. RIH w/8 3/4" bit & PT csg to 600#/30 mins 18. Reached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 18. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 18. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 18. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 18. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 18. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 18. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 19. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 19. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 19. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 19. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 19. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 19. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 19. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 19. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 10. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 10. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 10. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 10. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 10. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 10. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 10. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 10. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 10. Of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sr 10. Of Lead 447 sx (1162 cf - 207 bbls s	to test good. D/O cmt & dr. ", 20#, J-55 ST&C csg & sec. R Pheno seal. Tail 103 sx (no cmt to surface 7/21/08 (hrs PT csg to 2000#/30 minste. RIH w/202 jts, 4 ½", 10. sx (624 cf - 111 bbls slurry) aced w/130 bbls FW. Bump C will be reported on next restricted. Title Regulatory Techn	DIST. 3 All ahead to 4223' interm TI of @ 4222'. Pre-flush ahead 137 cf - 26 bbls slurry) By 0300 hrs. Bumped plug a - test good. S/11.6#, J-55 ST&C/LT&C 50/50 POZ standard, w/ (ed plug @ 0213 hrs.) By 13 hrs. Cian Date 07/31/08 Date
13. Describe Proposed or Completed Operations 17/71/08 H&P 282. NU BOP. RIH w/8 3/4" bit & PT csg to 600#/30 mins 18. Reached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 18. Seached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 18. Seached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 18. Seached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 19. Seached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 19. Seached 7/19/08. Bentonite, 5#/sx 19. Seached 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sx 19. Seached 47/24/08. Bentonite, 5#/sx 19. Seached 47/24/08. Circ hole. To 19. Seached 7/24/08. Circ hole. Circ hole. Circ hole. Circ hole. Circ hole. To 19. Seached 7/24/08. Circ hole. Circ hole. Seached 7/24/08. Circ hole. To 19. Seached 7/24/08. Circ hole. Circ hole. Seached 7/24/08. Circ hole. Circ hole. Circ hole. Seached 7/24/08. Circ hole. Circ hole. Circ hole. To 19. Seached 7/24/08. Circ hole. Circ h	to test good. D/O cmt & dr. ", 20#, J-55 ST&C csg & sec. R Pheno seal. Tail 103 sx (no cmt to surface 7/21/08 (hrs PT csg to 2000#/30 minste. RIH w/202 jts, 4 ½", 10. sx (624 cf - 111 bbls slurry) aced w/130 bbls FW. Bump C will be reported on next restricted. Title Regulatory Techn	DIST. 3 Ill ahead to 4223' interm TI at @ 4222'. Pre-flush ahead 137 cf - 26 bbls slurry) @ 0300 hrs. Bumped plug s - test good. 5/11.6#, J-55 ST&C/LT&C 50/50 POZ standard, w/ yed plug @ 0213 hrs. eport. Cian Date
13. Describe Proposed or Completed Operations 7/71/08 H&P 282. NU BOP. RIH w/8 3/4" bit & PT csg to 600#/30 mins Reached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sz 50/50 POZ, w/2% Bentonite, 6#/sx Pheno seal. Dropped plug & displaced to 1200#. 7/22/08 sundry filed for TOC @ 660'. WOC. 7/21/08 @ 2200'. 7/23/08 D/O cmt. Drill ahead to 8400' TD. TD reached 7/24/08. Circ hole Csg & set @ 8397'. Pre-flush 10 bbls chemwash & 2 bbls FW. Tail 430 s 2% CFR3-L, .8% Halad (R) 9, 3.5#/sx Pheno seal. Dropped plug & displa ND BOP & NU WH. RD & RR 7/25/08. PT will be conducted by the completion rig & recorded on next report. TO 14. I hereby certify that the foregoing is true and correct. Signed Rhonda Roge This space for Federal or State Office use) APPROVED BY Rhonda Roge CONDITION OF APPROVAL, if any: Title 18 U S C. Section 1001, makes it a crune for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	tentest good. D/O cmt & dr. ", 20#, J-55 ST&C csg & sex. R Pheno seal. Tail 103 sx (no cmt to surface 7/21/08 (hrs PT csg to 2000#/30 mins. e. RIH w/202 jts, 4 ½", 10. ix (624 cf - 111 bbls slurry). aced w/130 bbls FW. Bump. C will be reported on next rest. Title Regulatory Techn.	DIST. 3 Ill ahead to 4223' interm TI at @ 4222'. Pre-flush ahead 137 cf - 26 bbls slurry) @ 0300 hrs. Bumped plug s - test good. 5/11.6#, J-55 ST&C/LT&C 50/50 POZ standard, w/ (ed plug @ 0213 hrs. eport. Cian Date
13. Describe Proposed or Completed Operations 7/71/08 H&P 282. NU BOP. RIH w/ 8 3/4" bit & PT csg to 600#/30 mins Reached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sv 50/50 POZ, w/2% Bentonite, 6#/sx Pheno seal. Dropped plug & displaced to 1200#. 7/22/08 sundry filed for TOC @ 660'. WOC. 7/21/08 @ 2200 j 7/23/08 D/O cmt. Drill ahead to 8400' TD. TD reached 7/24/08. Circ hole Csg & set @ 8397'. Pre-flush 10 bbls chemwash & 2 bbls FW. Tail 430 s .2% CFR3-L, .8% Halad (R) 9, 3.5#/sx Pheno seal. Dropped plug & displa ND BOP & NU WH. RD & RR 7/25/08. PT will be conducted by the completion rig & recorded on next report. TO 14. I hereby certify that the foregoing is true and correct. Signed Rhonda Roge (This space for Federal or State Office use) APPROVED BY Rhonda Roge Title CONDITION OF APPROVAL, if any: Title 18 U S C. Section 1001, makes it a crume for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	tentest good. D/O cmt & dr. ", 20#, J-55 ST&C csg & sex. R Pheno seal. Tail 103 sx (no cmt to surface 7/21/08 (hrs PT csg to 2000#/30 mins. e. RIH w/202 jts, 4 ½", 10. ix (624 cf - 111 bbls slurry). aced w/130 bbls FW. Bump. C will be reported on next rest. Title Regulatory Techn.	DIST. 3 All ahead to 4223' interm TI at @ 4222'. Pre-flush ahead 137 cf - 26 bbls slurry) By 0300 hrs. Bumped plug a test good. Sold 1.6#, J-55 ST&C/LT&C 50/50 POZ standard, w/ and plug @ 0213 hrs. By 13 hrs. Cian Date
13. Describe Proposed or Completed Operations 7/71/08 H&P 282. NU BOP. RIH w/ 8 3/4" bit & PT csg to 600#/30 mins Reached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/sv 50/50 POZ, w/2% Bentonite, 6#/sx Pheno seal. Dropped plug & displaced to 1200#. 7/22/08 sundry filed for TOC @ 660'. WOC. 7/21/08 @ 2200 j 7/23/08 D/O cmt. Drill ahead to 8400' TD. TD reached 7/24/08. Circ hole Csg & set @ 8397'. Pre-flush 10 bbls chemwash & 2 bbls FW. Tail 430 s 2% CFR3-L, .8% Halad (R) 9, 3.5#/sx Pheno seal. Dropped plug & displa ND BOP & NU WH. RD & RR 7/25/08. PT will be conducted by the completion rig & recorded on next report. TO 14. I hereby certify that the foregoing is true and correct. Signed Rhonda Roge (This space for Federal or State Office use) APPROVED BY Rhonda Roge Condition of APPROVAL, if any: Citle 18 U S C. Section 1001, makes it a crume for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	tentest good. D/O cmt & dr. ", 20#, J-55 ST&C csg & sex. R Pheno seal. Tail 103 sx (no cmt to surface 7/21/08 (hrs PT csg to 2000#/30 mins. e. RIH w/202 jts, 4 ½", 10. ix (624 cf - 111 bbls slurry). aced w/130 bbls FW. Bump. C will be reported on next rest. Title Regulatory Techn.	DIST. 3 Ill ahead to 4223' interm TI at @ 4222'. Pre-flush ahead 137 cf - 26 bbls slurry) @ 0300 hrs. Bumped plug s - test good. 5/11.6#, J-55 ST&C/LT&C 50/50 POZ standard, w/ yed plug @ 0213 hrs. eport. Cian Date
13. Describe Proposed or Completed Operations 7/71/08 H&P 282. NU BOP. RIH w/8 3/4" bit & PT csg to 600#/30 mins Reached 7/19/08. Ream from 3600' to 1827'. Circ hole. RIH w/103 jts, 7 of Lead 447 sx (1162 cf - 207 bbls slurry) Type III, w/3% Bentonite, 5#/ss 50/50 POZ, w/2% Bentonite, 6#/sx Pheno seal. Dropped plug & displaced to 1200#. 7/22/08 sundry filed for TOC @ 660'. WOC. 7/21/08 @ 2200 j 7/23/08 D/O cmt. Drill ahead to 8400' TD. TD reached 7/24/08. Circ hole Csg & set @ 8397'. Pre-flush 10 bbls chemwash & 2 bbls FW. Tail 430 s 2% CFR3-L, .8% Halad (R) 9, 3.5#/sx Pheno seal. Dropped plug & displa ND BOP & NU WH. RD & RR 7/25/08. PT will be conducted by the completion rig & recorded on next report. TO 14. I hereby certify that the foregoing is true and correct. Signed Rhonda Roge Chapproved By Rhonda Roge CONDITION OF APPROVAL, if any: The 18 U S C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulem statements or representations as to any matter within its jurisdiction.	tentest good. D/O cmt & dr. ", 20#, J-55 ST&C csg & sex. R Pheno seal. Tail 103 sx (no cmt to surface 7/21/08 (hrs PT csg to 2000#/30 mins. e. RIH w/202 jts, 4 ½", 10. ix (624 cf - 111 bbls slurry). aced w/130 bbls FW. Bump. C will be reported on next rest. Title Regulatory Techn.	DIST. 3 Ill ahead to 4223' interm Tot @ 4222'. Pre-flush ahea 137 cf - 26 bbls slurry) @ 0300 hrs. Bumped plug a - test good. Job 5/11.6#, J-55 ST&C/LT&C 50/50 POZ standard, w/ (ed plug @ 0213 hrs.) Peport. John Date 07/31/08 ACCEPTED FOR RECORD AUG 0 4 2008