UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

RECEIVED

AUG 1 2 2008

Sundry Notices and Reports on Wells	nington F	Field Office
	3	reid Office
	5.	Lease Number
	-	USA - SF-080675
. Type of Well	6.	If Indian, All. or
GAS		Tribe Name
	7.	Unit Agreement Name
Name of Operator		
BURLINGTON		
RESOURCES OIL & GAS COMPANY LP	 8.	San Juan 27-4 Unit Well Name & Number
. Address & Phone No. of Operator	— o.	Wen Name & Number
		San Juan 27-4 Unit 69N
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
		30-039-30435
Location of Well, Footage, Sec., T, R, M	10.	Field and Pool
Surf: Unit E (SWNW), 1400' FNL & 1160' FWL, Section 34, T27N, R4W, NMPM	10.	Basin DK/Blanco MV
BH: Unit F (SENW), 1540' FNL & 1970' FWL, Section 34, T27N, R4W, NMPM		
	11.	County and State
		Rio Arriba Co., NM
Final Abandonment Altering Casing Conversion to Injection 3. Describe Proposed or Completed Operations		OIL CONS. DIV. DIST. 3
3. Describe Proposed or Completed Operations 1/29/08 MIRU Aztec 711. 7/30/08 PT csg to 600#/30 mins – test good. RIH w/8 ¾" bit and ED/O cmt & drill to 4360' TMD interm TD & reached 8/2/08. Circ hole. TOH & LD DD tool. LT&C csg & set @ 4351': Pre-flush w/10 bbls FW & 10 bbls mud flush. Scavenger 20 sx (6 w/8% Bentonite, 3% CACL2, .25#/sx Celllo flake, .2% FL-52, GW-3LD, 5#/sx LCM-1, .4% States of the complete	RIH w/2 cf - 11 Sodium M 2% FL-5 Cello fla mt to sur D reached cf - 5 bl	DIST. 3 Tagged on cmt @ 175'. 101 jts, 7", 23#, L-80 bbls slurry) Premium Lite, Metasilicate. Lead 580 sx 2, GW-3LD, 5#/sx LCM-1, akes, .2% FL-52.Dropped face. WOC 8/5/08 @ 2300 hrs 18/8/08. Circ hole. RIH bls slurry) Premium Lite,
3. Describe Proposed or Completed Operations 1/29/08 MIRU Aztec 711. 7/30/08 PT csg to 600#/30 mins – test good. RIH w/8 ¾" bit and E 1/29/08 MIRU Aztec 711. 7/30/08 PT csg to 600#/30 mins – test good. RIH w/8 ¾" bit and E 1/29/08 MIRU Aztec 711. 7/30/08 PT csg to 600#/30 mins – test good. RIH w/8 ¾" bit and E 1/29/08 MIRU Aztec 711. 7/30/08 PT csg to 600#/30 mins – test good. TOH & LD DD tool. 1/28/20 & set @ 4351': Pre-flush w/10 bbls FW & 10 bbls mud flush. Scavenger 20 sx (6 w/8% Bentonite, 3% CACL2, .25#/sx Celllo flake, .2% FL-52, GW-3LD, 5#/sx LCM-1, .4% States of the substitution of the	RIH w/2 cf - 11 Sodium M 2% FL-5 Cello fla mt to sur D reached c cf - 5 bl 116 bbls bbls sug	Tagged on cmt @ 175'. 101 jts, 7", 23#, L-80 bbls slurry) Premium Lite, Metasilicate. Lead 580 sx 2, GW-3LD, 5#/sx LCM-1, lkes, .2% FL-52.Dropped face. WOC 8/5/08 @ 2300 hrs 18/8/08. Circ hole. RIH bls slurry) Premium Lite, slurry) Type III, w/.3% gar water & 117 bbls FW.
3. Describe Proposed or Completed Operations /29/08 MIRU Aztec 711. 7/30/08 PT csg to 600#/30 mins – test good. RIH w/8 ¾" bit and E /29/08 MIRU Aztec 711. 7/30/08 PT csg to 600#/30 mins – test good. RIH w/8 ¾" bit and E /20/00 cmt & drill to 4360' TMD interm TD & reached 8/2/08. Circ hole. TOH & LD DD tool. // **Take C csg & set @ 4351':" Pre-flush w/10 bbls FW & 10 bbls mud flush. Scavenger 20 sx (6 // **W/8% Bentonite, 3% CACL2, 25#/sx Celllo flake, .2% FL-52, GW-3LD, 5#/sx LCM-1, .4% States 1129 cf – 201 bbls slurry) Premium Lite, w/8% Bentonite, 3% CACL2, .25#/sx Celllo flake, . // **Sodium Metasilicate. Tail 110 sx (152 cf – 34 bbls slurry) Type III, w/1% CACL2, .25# // **lug & displaced w/170 bbls FW. Bumped plug to 1430# 8/4/08 @ 1430 hrs. Circ 130 bbls counter to 1500#/30 mins – test good. // **/*/*/*/*/*/*/*/*/*/*/*/*/*/*/*/*/	RIH w/2 cf - 11 Sodium M 2% FL-5 Cello fla mt to sur D reached c cf - 5 bl 116 bbls bbls sug	Tagged on cmt @ 175'. 101 jts, 7", 23#, L-80 bbls slurry) Premium Lite, Metasilicate. Lead 580 sx 2, GW-3LD, 5#/sx LCM-1, lkes, .2% FL-52.Dropped face. WOC 8/5/08 @ 2300 hrs 18/8/08. Circ hole. RIH bls slurry) Premium Lite, slurry) Type III, w/.3% gar water & 117 bbls FW.
3. Describe Proposed or Completed Operations //29/08 MIRU Aztec 711. 7/30/08 PT csg to 600#/30 mins – test good. RIH w/8 ¾" bit and ED/O cmt & drill to 4360' TMD interm TD & reached 8/2/08. Circ hole. TOH & LD DD tool. T&C csg & set @ 4351'* Pre-flush w/10 bbls FW & 10 bbls mud flush. Scavenger 20 sx (6 w/8% Bentonite, 3% CACL2, .25#/sx Celllo flake, .2% FL-52, GW-3LD, 5#/sx LCM-1, .4% States of the conduction of the conducted by completion rig & record on next report. TOC will be recorded on next report. TOC will be recorded on next report.	RIH w/2 cf - 11 Sodium M 2% FL-5 Cello fla mt to sur D reached c cf - 5 bl 116 bbls bbls sug	Tagged on cmt @ 175'. 101 jts, 7", 23#, L-80 bbls slurry) Premium Lite, Metasilicate. Lead 580 sx 2, GW-3LD, 5#/sx LCM-1, ikes, .2% FL-52.Dropped face. WOC 8/5/08 @ 2300 hrs 1 8/8/08. Circ hole. RIH bls slurry) Premium Lite, slurry) Type III, w/.3% gar water & 117 bbls FW.
3. Describe Proposed or Completed Operations //29/08 MIRU Aztec 711. 7/30/08 PT csg to 600#/30 mins – test good. RIH w/8 ¾" bit and E //O cmt & drill to 4360' TMD interm TD & reached 8/2/08. Circ hole. TOH & LD DD tool. T&C csg & set @ 4351': Pre-flush w/10 bbls FW & 10 bbls mud flush. Scavenger 20 sx (6 //8% Bentonite, 3% CACL2, .25#/sx Celllo flake, .2% FL-52, GW-3LD, 5#/sx LCM-1, .4% S 1129 cf – 201 bbls slurry) Premium Lite, w/8% Bentonite, 3% CACL2, .25#/sx Celllo flake, . 4% Sodium Metasilicate. Tail 110 sx (152 cf – 34 bbls slurry) Type III, w/1% CACL2, .25# olug & displaced w/170 bbls FW. Bumped plug to 1430# 8/4/08 @ 1430 hrs. Circ 130 bbls cc of csg to 1500#/30 mins – test good. //5/08 RIH w/6 ¼" bit. Tagged on cmt @ 4360'. D/O cmt & drilled to 8563' TMD TD & TI 204 jts, 4 ½", 11.6#, L-80 LT&C csg & set @ 8562'. Pre-flush ahead of Scavenger 9 sx (28 //3% CD-32, .25#/sx Cellophane flakes, 1% FL-52, 6.25#/sx LCM-1. Tail 330 sx (653 cf – cD-32, .25#/sx Cellophane flakes, 1% FL-52, 6.25#/sx LCM-1. Dropped plug & displaced 10 ND BOP & NU WH. RD & RR 8/9/08. PT will be conducted by completion rig & record on next report. TOC will be recorded on next 4. I hereby certify that the foregoing is true and correct.	RIH w/2 cf - 11 Sodium N 2% FL-5 Cello fla mt to sur O reached c cf - 5 bi 116 bbls bbls sug	Tagged on cmt @ 175'. 101 jts, 7", 23#, L-80 bbls slurry) Premium Lite, Metasilicate. Lead 580 sx 2, GW-3LD, 5#/sx LCM-1, akes, .2% FL-52.Dropped face. WOC 8/5/08 @ 2300 hrs 1 8/8/08. Circ hole. RIH bls slurry) Premium Lite, slurry) Type III, w/.3% gar water & 117 bbls FW.
3. Describe Proposed or Completed Operations /29/08 MIRU Aztec 711. 7/30/08 PT csg to 600#/30 mins – test good. RIH w/8 %" bit and E //O cmt & drill to 4360' TMD interm TD & reached 8/2/08. Circ hole. TOH & LD DD tool. T&C csg & set @ 4351': Pre-flush w/10 bbls FW & 10 bbls mud flush. Scavenger 20 sx (6 //8% Bentonite, 3% CACL2, .25#/sx Celllo flake, .2% FL-52, GW-3LD, 5#/sx LCM-1, .4% S 1129 cf – 201 bbls slurry) Premium Lite, w/8% Bentonite, 3% CACL2, .25#/sx Celllo flake, . 4% Sodium Metasilicate. Tail 110 sx (152 cf – 34 bbls slurry) Type III, w/1% CACL2, .25# /lug & displaced w/170 bbls FW. Bumped plug to 1430# 8/4/08 @ 1430 hrs. Circ 130 bbls cc /T csg to 1500#/30 mins – test good. //5/08 RIH w/6 ¼" bit. Tagged on cmt @ 4360'. D/O cmt & drilled to 8563' TMD TD & TI 04 jts, 4 ½", 11.6#, L-80 LT&C csg & set @ 8562'. Pre-flush ahead of Scavenger 9 sx (28 //.3% CD-32, .25#/sx Cellophane flakes, 1% FL-52, 6.25#/sx LCM-1. Tail 330 sx (653 cf – //.25-32, .25#/sx Cellophane flakes, 1% FL-52, 6.25#/sx LCM-1. Dropped plug & displaced 10 ID BOP & NU WH. RD & RR 8/9/08. T will be conducted by completion rig & record on next report. TOC will be recorded on next 4. I hereby certify that the foregoing is true and correct.	RIH w/2 cf - 11 Sodium N 2% FL-5 Cello fla mt to sur O reached c cf - 5 bi 116 bbls bbls sug	Tagged on cmt @ 175'. 101 jts, 7", 23#, L-80 bbls slurry) Premium Lite, Metasilicate. Lead 580 sx 2, GW-3LD, 5#/sx LCM-1, akes, .2% FL-52.Dropped face. WOC 8/5/08 @ 2300 hrs 18/8/08. Circ hole. RIH bls slurry) Premium Lite, slurry) Type III, w/.3% gar water & 117 bbls FW.
3. Describe Proposed or Completed Operations /29/08 MIRU Aztec 711. 7/30/08 PT csg to 600#/30 mins – test good. RIH w/8 ¾" bit and E //O cmt & drill to 4360' TMD interm TD & reached 8/2/08. Circ hole. TOH & LD DD tool. T&C csg & set @ 4351': Pre-flush w/10 bbls FW & 10 bbls mud flush. Scavenger 20 sx (6 //8% Bentonite, 3% CACL2, .25#/sx Celllo flake, .2% FL-52, GW-3LD, 5#/sx LCM-1, .4% S 1129 cf – 201 bbls slurry) Premium Lite, w/8% Bentonite, 3% CACL2, .25#/sx Celllo flake, . 14% Sodium Metasilicate. Tail 110 sx (152 cf – 34 bbls slurry) Type III, w/1% CACL2, .25# lug & displaced w/170 bbls FW. Bumped plug to 1430# 8/4/08 @ 1430 hrs. Circ 130 bbls c: T csg to 1500#/30 mins – test good. 7/5/08 RIH w/6 ¼" bit. Tagged on cmt @ 4360'. D/O cmt & drilled to 8563' TMD TD & TI 04 jts, 4 ½", 11.6#, L-80 LT&C csg & set @ 8562'. Pre-flush ahead of Scavenger 9 sx (28 1/3% CD-32, .25#/sx Cellophane flakes, 1% FL-52, 6.25#/sx LCM-1. Tail 330 sx (653 cf – 1/2D-32, .25#/sx Cellophane flakes, 1% FL-52, 6.25#/sx LCM-1. Dropped plug & displaced 10 1/2D BOP & NU WH. RD & RR 8/9/08. T will be conducted by completion rig & record on next report. TOC will be recorded on next 4. I hereby certify that the foregoing is true and correct. 1 igned Rhonda Rogers Title R	RIH w/2 cf - 11 Sodium N 2% FL-5 Cello fla mt to sur O reached c cf - 5 bi 116 bbls bbls sug	Tagged on cmt @ 175'. 101 jts, 7", 23#, L-80 bbls slurry) Premium Lite, Metasilicate. Lead 580 sx 2, GW-3LD, 5#/sx LCM-1, lkes, .2% FL-52.Dropped face. WOC 8/5/08 @ 2300 hrs 18/8/08. Circ hole. RIH bls slurry) Premium Lite, slurry) Type III, w/.3% gar water & 117 bbls FW.
3. Describe Proposed or Completed Operations //29/08 MIRU Aztec 711. 7/30/08 PT csg to 600#/30 mins – test good. RIH w/8 %" bit and D/O cmt & drill to 4360' TMD interm TD & reached 8/2/08. Circ hole. TOH & LD DD tool. T&C csg & set @ 4351': Pre-flush w/10 bbls FW & 10 bbls mud flush. Scavenger 20 sx (6 v/8% Bentonite, 3% CACL2, .25#/sx Celllo flake, .2% FL-52, GW-3LD, 5#/sx LCM-1, .4% S 1129 cf – 201 bbls slurry) Premium Lite, w/8% Bentonite, 3% CACL2, .25#/sx Celllo flake, .4% Sodium Metasilicate. Tail 110 sx (152 cf – 34 bbls slurry) Type III, w/1% CACL2, .25#/sug & displaced w/170 bbls FW. Bumped plug to 1430# 8/4/08 @ 1430 hrs. Circ 130 bbls ct 27 csg to 1500#/30 mins – test good. 1/5/08 RIH w/6 ¼" bit. Tagged on cmt @ 4360'. D/O cmt & drilled to 8563' TMD TD & TI .04 jts, 4 ½", 11.6#, L-80 LT&C csg & set @ 8562'. Pre-flush ahead of Scavenger 9 sx (28 w/.3% CD-32, .25#/sx Cellophane flakes, 1% FL-52, 6.25#/sx LCM-1. Tail 330 sx (653 cf – CD-32, .25#/sx Cellophane flakes, 1% FL-52, 6.25#/sx LCM-1. Dropped plug & displaced 10 BOP & NU WH. RD & RR 8/9/08. 14. I hereby certify that the foregoing is true and correct.	RIH w/2 cf - 11 Sodium N 2% FL-5 Cello fla mt to sur O reached c cf - 5 bi 116 bbls bbls sug	Tagged on cmt @ 175'. 101 jts, 7", 23#, L-80 bbls slurry) Premium Lite, Metasilicate. Lead 580 sx 2, GW-3LD, 5#/sx LCM-1, akes, .2% FL-52.Dropped face. WOC 8/5/08 @ 2300 hrs 18/8/08. Circ hole. RIH bls slurry) Premium Lite, slurry) Type III, w/.3% gar water & 117 bbls FW.

NMOCD %