District I 1625 N French Dr , Hobbs, NM 88240

1301 W. Grand Ave., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

July 21, 2008 For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

Form C-144

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action:	X Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Modification to an existing permit
	Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the

Operator: Burlington Resources Oil & Gas Company, LP		OGRID#: 14538		
ddress: PO Box 428	9, Farmington, NM 87499			
acility or well name:	San Juan 28-6 Unit #171P			
API Number:	30-039-30549	OCD Permit Nur	nber:	
J/L or Qtr/Qtr: A(NI	ENE) Section: 24 Township:	27N Range:	6W County: Rio	Arriba
Center of Proposed Desi	gn: Latitude: 36.56675' N	Longitude:	107.41197' W	NAD: 1927 X 1983
urface Owner:	Federal State X Priv	ate Tribal Trust or Inc	lian Allotment	
Pit: Subsection F	or G of 19.15.17.11 NMAC			
Temporary: Dri	Iling Workover			
Permanent Em	ergency Cavitation P&A			
Lined Un	lined Liner type: Thickness	mil	HDPE PVC Ot	her
String-Reinforced				•
Liner Seams: W	elded Factory Other	Volume:	bbl Dimensions L	x W x D
X Closed-loop Syst Type of Operation: X Drying Pad X X Lined Unl Liner Seams: X We	P&A X Drilling a new well r Above Ground Steel Tanks Haul- ined Liner type: Thickness 2	Workover or Drilling (Applies notice of intent) off Bins Other 20 mil X LLDPE	HDPE PVD Othe	er /3 ² A 25262728
 4				OIL CONS. DIV. DIST.
	Subsection I of 19.15.17.11 NMAC			AUG 200
Volume:	bbl Type of fluid:			OIL CONS. DIV. DIST.
Tank Construction mate				/St.
=		lewalls, liner, 6-inch lift and a	automatic overflow shut-off	8910112 13 15 15 15 15 15 15 15 15 15 15 15 15 15
Visible sidewalls a	·			-011101
Liner Type: Thickr	nessmilHDPE	PVC Other		
5				
Alternative Met	hod:			
Submittal of an exception	on request is required. Exceptions must be s	ubmitted to the Santa Fe Env	ironmental Bureau office for	consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate Please specify			
Netting: Subsection E of 19 15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)			
Signs: Subsection C of 19 15.17 11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC			
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.			
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.			
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No		
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No		
(Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	NA		
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No		
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes No		
 NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site. Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Written confirmation or verification from the municipality; Written approval obtained from the municipality 	Yes No		
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes No		
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map Within a 100-year floodplain - FEMA map	Yes No		

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19 15.17 9 NMAC			
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.			
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC			
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9			
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC			
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC			
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC			
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17 9 NMAC and 19.15 17.13 NMAC			
Previously Approved Design (attach copy of design) API or Permit			
12			
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19 15 17 9 NMAC Instructions Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9			
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC			
X Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC			
X Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC			
X Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17 9			
NMAC and 19 15.17 13 NMAC			
Previously Approved Design (attach copy of design) API			
Previously Approved Operating and Maintenance Plan API			
Permanent Pits Permit Application Checklist: Subsection B of 19 15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19 15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19 15.17 11 NMAC			
Dike Protection and Structural Integrity Design based upon the appropriate requirements of 19 15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15 17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19 15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19 15.17.11 NMAC Nuisance or Hazardous Odors, including H2S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan			
Erosion Control Plan			
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC			
14 Proposed Closure: 19.15.17.13 NMAC			
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.			
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank X Closed-loop System			
Alternative Proposed Closure Method Waste Excavation and Removal			
Waste Excavation and Removal			
On-site Closure Method (only for temporary pits and closed-loop systems)			
In-place Burial On-site Trench			
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)			
Waste Excavation and Removal Closure Plan Checklist: (19.15 17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.			
Protocols and Procedures - based upon the appropriate requirements of 19.15.17 13 NMAC			
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)			
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC			
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC			
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC			

Form C-144 Oil Conservation Division Page 3 of 5

16 Weste Pemanal Classure For Classed Ioan Systems That Hilling Abous Cround Str	eel Toules on Houl off Ring Out	(10.15.17.12.D.NMAC)	,
Waste Removal Closure For Closed-loop Systems That Utilize Above Ground St Instructions: Please identify the facility or facilities for the disposal of liquids, drillin are required			icilities
Disposal Facility Name Envirotech	Disposal Facility Permit #.	NM-01-0011	
Disposal Facility Name: Basin Disposal Facility	_ Disposal Facility Permit #:	NM-01-005	
Will any of the proposed closed-loop system operations and associated activit Yes (If yes, please provide the information No	ies occur on or in areas that wi	ill not be used for future se	ervice and operations?
Required for impacted areas which will not be used for future service and operation Soil Backfill and Cover Design Specification - based upon the appropriate Re-vegetation Plan - based upon the appropriate requirements of Subs. Site Reclamation Plan - based upon the appropriate requirements of Subscriptions.	riate requirements of Subsection I of 19.15.17.13 NMAC		C .
17 Siting Criteria (Regarding on-site closure methods only: 19 15.17.10 NMA Instructions Each siting criteria requires a demonstration of compliance in the closure plan certain siting criteria may require administrative approval from the appropriate district offic for consideration of approval Justifications and/or demonstrations of equivalency are required.	Recommendations of acceptable so e or may be considered an exception	which must be submitted to the	
Ground water is less than 50 feet below the bottom of the buried waste.			Yes No
- NM Office of the State Engineer - (WATERS database search; USGS: Data ob	tained from nearby wells		□N/A
Ground water is between 50 and 100 feet below the bottom of the buried was	te		Yes No
- NM Office of the State Engineer - iWATERS database search, USGS, Data obtained to the State Engineer - iWATERS database search, USGS, Data obtained to the State Engineer - iWATERS database search, USGS, Data obtained to the State Engineer - iWATERS database search, USGS, Data obtained to the State Engineer - iWATERS database search, USGS, Data obtained to the State Engineer - iWATERS database search, USGS, Data obtained to the State Engineer - iWATERS database search, USGS, Data obtained to the State Engineer - iWATERS database search, USGS, Data obtained to the State Engineer - iWATERS database search, USGS, Data obtained to the State Engineer - iWATERS database search, USGS, Data obtained to the State Engineer - iWATERS database search, USGS, Data obtained to the State Engineer - iWATERS database search, USGS, Data obtained to the State Engineer - iWATERS database search - iWATERS data	tained from nearby wells		□N/A
Ground water is more than 100 feet below the bottom of the buried waste.			Yes No
- NM Office of the State Engineer - tWATERS database search; USGS; Data obtained the state of the State Engineer - twaters and the state of the State Engineer - twaters are the state of the State Engineer - twaters and the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are the state Engineer - twaters are the state of the State Engineer - twaters are the state of the State Engineer - twaters are	tained from nearby wells		□N/A
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significance (measured from the ordinary high-water mark).	ficant watercourse or lakebed, sin	khole, or playa lake	☐Yes ☐No
- Topographic map; Visual inspection (certification) of the proposed site			
Within 300 feet from a permanent residence, school, hospital, institution, or church in - Visual inspection (certification) of the proposed site; Aerial photo; satellite image		oplication.	∐Yes ∐No
Within 500 horizontal feet of a private, domestic fresh water well or spring that less t purposes, or within 1000 horizontal fee of any other fresh water well or spring, in exi - NM Office of the State Engineer - iWATERS database, Visual inspection (certi-	stence at the time of the initial ap	•	YesNo
Within incorporated municipal boundaries or within a defined municipal fresh water pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality, Written approval of		ipal ordinance adopted	Yes No
Within 500 feet of a wetland - US Fish and Wildlife Wetland Identification map; Topographic map, Visual in:		nosed site	Yes No
Within the area overlying a subsurface mine.	erenen (eenmenn) er ene prop	70000 5110	∏Yes ∏No
- Written confirantion or verification or map from the NM EMNRD-Mining and	Mineral Division		
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & M	Mineral Resources; USGS; NM G	eological Society;	∐Yes ∐No
Topographic map Within a 100-year floodplain FEMA map			∏Yes ∏No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each by a check mark in the box, that the documents are attached.	h of the following items must	bee attached to the closur	e plan. Please indicate,
Siting Criteria Compliance Demonstrations - based upon the appropria	ate requirements of 19.15.17.1	0 NMAC	
Proof of Surface Owner Notice - based upon the appropriate requirement	•		
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC			
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15.17 11 NMAC			
Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC			
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 10.15.17.13 NMAC.			
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC			
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC			

Form C-144

19		
Operator Application Certification: I hereby certify that the information submitted with this application is true, acc	curate and complete to the	best of my knowledge and belief.
Name (Print): Crystal Tafoya	Title:	Regulatory Technician
Signature: Constal Talogo	Date.	8/25/08
e-mail address <u>crystal tafoya@conocophillip/.com</u>	Telephone:	508-326-9837
20 OCD Approval: Permit Application (including closure plan)	Closure Plan (only)	OCD Conditions (see attachment)
OCD Representative Signature:		Approval Date: 8-26-08
Title: Enviro/spec	OCD Perm	uit Number:
21		
Closure Report (required within 60 days of closure completion): Sut Instructions: Operators are required to obtain an approved closure plan prior report is required to be submitted to the division within 60 days of the complete approved closure plan has been obtained and the closure activities have been detailed.	to implementing any closu ion of the closure activitie. completed.	re activities and submitting the closure report. The closure
22 Closure Method: Waste Excavation and Removal On-site Closure Method If different from approved plan, please explain.	Alternative Closure	Method Waste Removal (Closed-loop systems only)
23		
Closure Report Regarding Waste Removal Closure For Closed-loop System Instructions: Please identify the facility or facilities for where the liquids, dri		
were utilized. Disposal Facility Name.	Disposal Facility	Permit Number:
Disposal Facility Name:	Disposal Facility	
Were the closed-loop system operations and associated activities performed	_	be used for future service and opeartions?
Yes (If yes, please demonstrate compliane to the items below)	No	
Required for impacted areas which will not be used for future service and a Site Reclamation (Photo Documentation)	pperations:	
Soil Backfilling and Cover Installation		
Re-vegetation Application Rates and Seeding Technique		
24		
Closure Report Attachment Checklist: Instructions: Each of the fol	llowing items must be atta	ched to the closure report. Please indicate, by a check mark in
the box, that the documents are attached. Proof of Closure Notice (surface owner and division)		
Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure)		
Plot Plan (for on-site closures and temporary pits)		
Confirmation Sampling Analytical Results (if applicable)		
Waste Material Sampling Analytical Results (if applicable)		
Disposal Facility Name and Permit Number		
Soil Backfilling and Cover Installation		
Re-vegetation Application Rates and Seeding Technique		
Site Reclamation (Photo Documentation)		
On-site Closure Location: Latitude	Longitude:	NAD [] 1927 [] 1983
Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure.	-	
the closure complies with all applicable closure requirements and conditions s Name (Print):	pecified in the approved co Title:	losure plan.
Signature:	Date.	
e-mail address	Telephone	

Burlington Resources Oil & Gas Company, LP

Closed Loop Design:

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

Burlington Resources Oil & Gas Company, LP may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19.15.17.11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15.3.103.NMAC. Frac tanks will be utilized on site for fresh water storage.

Closed Loop Operations and Maintenance:

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows:

- Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005). Reuse may include the relocating of liquids to be used in other permitted drilling operations.
- 2. Drill solids will be recovered from location and hauled to a Envirotech (Permit #NM-01-0011) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burial of cuttings will occur.
- 3. In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005). The liner will be disposed of at the San Juan County Landfill located on CR 3100. The drying pad will be closed within 6 months from the date that the drilling rig is released. Berms constructed from native materials will be bladed on site to the location's contour.
- 4. Any drilling materials or trash will be stored and disposed of appropriately.
- 5. The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately.

Closed Loop Closure Plan:

- Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and Basin Disposal Facility (Permit # NM-01-005). Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit # NM-01-0011) within 6 months from the date that the drilling rig is released.
- 2. After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

- 3. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4. Notification will be sent to OCD when the reclaimed area is seeded.
- 5. BR shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality)
Purity
Source No. two (better quality)

5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS 1 lb. PLS