

UNITED STATES  
DEPARTMENT OF INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

AUG 18 2008

FORM APPROVED  
Budget Bureau No 1004-0135  
Expires March 31, 1993

SUNDRY NOTICE AND REPORTS ON WELLS

Bureau of Land Management

Lease Designation and Serial No

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir  
DRILL" for permit for such proposals

Use "APPLICATION TO ADRILL"

NMSF-078763

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE

7. If Unit or CA, Agreement Designation  
Rosa Unit

1. Type of Well  
Oil Well Gas Well ☒ Other

8. Well Name and No  
Rosa Unit #400

2. Name of Operator  
WILLIAMS PRODUCTION COMPANY

9. API Well No  
30-039-30271

3. Address and Telephone No  
PO Box 640 Aztec, NM 87410-0640

10. Field and Pool, or Exploratory Area  
BASIN FRUITLAND COAL

4. Location of Well (Footage, Sec., T, R, M, or Survey Description)  
1210' FNL & 1290' FEL SEC 9, T31N, R5W

11. County or Parish, State  
Rio Arriba, New Mexico

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

Notice of Intent

☒ Subsequent Report

Final Abandonment

Abandonment

Recompletion

Plugging Back

Casing Repair

Altering Casing

☒ Other - Surface Casing

Change of Plans

New Construction

Non-Routine Fracturing

Water Shut-Off

Conversion to Injection

Dispose Water

(Note. Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8/17/08

TD- 12 1/4 " SURFACE HOLE @ 355, 0500 HRS  
RAN 7 JTS, 9 5/8", 36#, K-55, LT&C, 8rd, CSG SET @ 345' FC @ 297'

RCVD AUG 27 '08

OIL CONS. DIV.

DIST. 3

8/18/08

CEMENT SINGLE SLURRY CEMENT JOB AS FOLLOWS : Press Test 1500#, 20 Bbl FW Spacer ahead, 150sx ( 205cuft, 37 Bbl slurry )Type 3 Cement + 2%bwoc CaCl2 + 1/4#/sk Cello-Flake + 6.84gal/sk FW.( Weight=14.5#/gal, Yield=1.41cuft / sk ) Drop Plug & Displace w/ 22.2 Bbl FW.Final Press 89#, Bump Plug to 710#, Check Float-Held. Circ 9 Bbl, 36sx Cement to Pit. ✓  
PLUG DOWN @ 11:48 AM, 8/18/2008.

INSTALL TEST PLUG & PRESS TEST BLIND RAMS,PIPE RAMS,CHOKE MANIFOLD VALVES,CHOKE LINE VALVES,& KILL LINE VALVES,LOW - 250# 5-MIN EACH,HIGH - 1500# 10-MIN EACH.TEST PLUG,TEST PUMP, & CHARTS USED,PULL TEST, PLUG & PRESS TEST 9 5/8" SURFACE CASING & BLIND RAMS 1500# 30 MIN.TEST PUMP & CHART USED.TESTS GOOD FOR RECORD

14. I hereby certify that the foregoing is true and correct

Signed

Larry Higgins

Title Drilling C.O.M.

Date 8/18/08

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any.

Title 18 U.S.C Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD