

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL AP# NO. 30-045-31611
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator ENERGEN RESOURCES CORPORATION		6. State Oil & Gas Lease No.
3. Address of Operator 2198 Bloomfield Highway, Farmington, NM 87401		7. Lease Name or Unit Agreement Name: Fifield
4. Well Location Unit Letter 0 : 790 feet from the South line and 1615 feet from the East line Section 05 Township 29N Range 11W NMPM County San Juan		8. Well No. 800S
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 5730' GL		9. Pool name or Wildcat Pictured Cliffs <del>Wash FRC</del>

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: set casing ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

07/22/03 TD:2047' PBD:2032' Ran 47 jts. 4-1/2" 10.5# J-55 ST&C casing, set @ 2047'. RU BJ Services. Cement with 125 sks Class C, 8% gel, 1/4#/sk flocele, 5#/sk gilsonite followed by 100 sks Class C, 1% CaCl2, 1/4#/sk flocele, 5#/sk gilsonite (466 cu.ft.). Plug down @ 5:15 pm on 07/22/03. Did not circulate cement. Will run temperature survey. RD BJ Services. ND BOP. Rig released 5:15 pm 07/22/03.

Temperature Survey: TOC 195'

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Vicki Donaghey TITLE Production Assistant DATE 07/25/03

Type or print name Vicki Donaghey Telephone No. 505-325-6800

(This space for State use)

APPROVED BY Chah + TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 02 DATE OCT 29 2003

Conditions of approval, if any: