

Submit 3 Copies To Appropriate District Office  
District I  
1625 N French Dr, Hobbs, NM 88240  
District II  
1301 W. Grand Ave, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
June 19, 2008

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-045-34700
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-178
7. Lease Name or Unit Agreement Name Northeast Blanco Unit
8. Well Number 354E
9. OGRID Number 6137
10. Pool name or Wildcat Basin Dakota

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator  
Devon Energy Production Company, L.P.

3. Address of Operator  
20 N. Broadway, Oklahoma City, OK 73102

4. Well Location  
Unit Letter G : 1,680 feet from the North line and 1,905 feet from the East line  
Section 32 Township 31N Range 7W NMPM San Juan County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
GR 6,388'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: Spud Notice ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

The above referenced well was spud on 8/25/08 at 10:30.

Drilled 12 1/4" hole to 308' on 8/25/08, set 15 jts of 9 5/8", H-40, ST&C, 32.3# casing at 302'. Cemented w/225 sx Type 5 cement w/2% CaCl and 1/4 ppsx Celloflake. Circulated 3 bbls of cement to surface. Tested casing to 750 psi, held ok.

RCVD SEP 8 '08  
OIL CONS. DIV.  
DIST. 3

Spud Date: 8/25/08

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Melisa Castro TITLE Senior Staff Operations Technician DATE 9-4-08

Type or print name Melisa Castro E-mail address: melisa.castro@dmn.com PHONE: 405-552-7917

For State Use Only

APPROVED BY: [Signature] TITLE Deputy Oil & Gas Inspector, District #3 DATE SEP 23 2008  
Conditions of Approval (if any):