District I

1625 N French Dr , Hobbs, NM 88240

District II

1301 W Grand Ave , Artesia, NM 88210

District III

1000 De Present Pd. Artes NM 87410

<u>District IV</u> 1220 S St Francis <u>Dr</u>, Santa Fe, NM 87505

1000 Rio Brazos Rd , Aztec, NM 87410

Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

State of New Mexico

Energy Minerals and Natural Resources

 $\label{eq:July 21, 2008} \mbox{ For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.}$

Form C-144

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office

Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action:	Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Modification to an existing permit
	X Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method

Operator: Burlington Resources Oil & Gas Company, LP	OGRID#: 14538
Address: PO Box 4289, Farmington, NM 87499	
facility or well name: Holder A 100	
API Number: 30-045-34242	OCD Permit Number:
J/L or Qtr/Qtr: F(SENW) Section: 6 Townships	: 30N Range: 12W County: San Juan
Center of Proposed Design: Latitude: 36.84516' I	N Longitude: 108.14236' W NAD: 1927 X 1983
urface Owner: X Federal State Pr	ivate Tribal Trust or Indian Allotment
Pit: Subsection F or G of 19.15.17.11 NMAC	
Temporary X Drilling Workover	
Permanent Emergency Cavitation P&A	
X Lined Unlined Liner type: Thickness	20 mil X LLDPE HDPE PVC Other
X String-Reinforced	
Liner Seams: X Welded X Factory Other	Volume: 4400 bbl Dimensions L 65' x W 45' x D 10'
	Foliance 4400 con Santonorio D 05 A 11 45 A D 20
Closed-loop System: Subsection H of 19.15.17 11 NMA Type of Operation P&A Drilling a new well Drying Pad Above Ground Steel Tanks Hau Lined Unlined Liner type Thickness Liner Seams Welded Factory Other	Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) al-off Bins Other PVD Other BECCH
Closed-loop System: Subsection H of 19.15.17 11 NMA Type of Operation P&A Drilling a new well Drying Pad Above Ground Steel Tanks Hau Lined Unlined Liner type Thickness	Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) al-off Bins Other PVD Other BECCH
Closed-loop System: Subsection H of 19.15.17 11 NMA Type of Operation P&A Drilling a new well Drying Pad Above Ground Steel Tanks Hau Lined Unlined Liner type Thickness Liner Seams Welded Factory Other	Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) al-off Bins Other PVD Other BECCH
Closed-loop System: Subsection H of 19.15.17 11 NMA Type of Operation P&A Drilling a new well Drying Pad Above Ground Steel Tanks Hau Lined Unlined Liner type Thickness Liner Seams Welded Factory Other Below-grade tank: Subsection I of 19.15.17.11 NMAC	Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) al-off Bins Other PVD Other BECCH
Closed-loop System: Subsection H of 19.15.17 11 NMA Type of Operation: P&A Drilling a new well Drying Pad Above Ground Steel Tanks Hau Lined Unlined Liner type Thickness Liner Seams Welded Factory Other Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: bbl Type of fluid. Tank Construction material.	Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) al-off Bins Other PVD Other BECCH
Closed-loop System: Subsection H of 19.15.17 11 NMA Type of Operation: P&A Drilling a new well Drying Pad Above Ground Steel Tanks Hau Lined Unlined Liner type Thickness Liner Seams Welded Factory Other Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: bbl Type of fluid. Tank Construction material.	Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) al-off Bins Other mil LLDPE HDPE PVD Other PVD OTHER OF PECETVE OCT 2008 Sidewalls, liner, 6-inch lift and automatic overflow shut-off

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate Please specify		
Netting: Subsection E of 19.15 17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)		
Signs: Subsection C of 19 15.17.11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC		
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration of approval.	eration of app	proval
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.		
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	□No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to temporary, emergency, or cavitation pits and below-grade tanks) Visual inspection (agrification) of the proposed city, Agricla photo: Satallita image.	☐ Yes ☐ NA	∏No
 Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits) Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes NA	No
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	No
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site. Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes	No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	☐Yes ☐Yes	□No □No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society; Topographic map Within a 100-year floodplain - FEMA map	Yes Yes	□No

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17 9 NMAC		
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC		
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9		
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC		
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC		
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC		
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 15.17 9 NMAC and 19.15 17.13 NMAC		
Previously Approved Design (attach copy of design) API or Permit		
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9		
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19 15.17 10 NMAC		
Design Plan - based upon the appropriate requirements of 19.15.17 11 NMAC		
Operating and Maintenance Plan - based upon the appropriate requirements of 19 15.17.12 NMAC		
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17 13 NMAC		
Previously Approved Design (attach copy of design) API		
Previously Approved Operating and Maintenance Plan API		
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC		
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.		
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC		
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC		
Climatological Factors Assessment		
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15 17.11 NMAC		
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC		
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC		
Quality Control/Quality Assurance Construction and Installation Plan		
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC		
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC		
Nuisance or Hazardous Odors, including H2S, Prevention Plan		
Emergency Response Plan		
Oil Field Waste Stream Characterization		
Monitoring and Inspection Plan		
Erosion Control Plan		
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15 17.13 NMAC		
14		
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.		
Type X Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System Alternative		
Proposed Closure Method. X Waste Excavation and Removal		
Waste Removal (Closed-loop systems only)		
On-site Closure Method (only for temporary pits and closed-loop systems)		
In-place Burial On-site Trench		
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)		
15		
Waste Excavation and Removal Closure Plan Checklist: (19.15 17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.		
Please indicate, by a check mark in the box, that the documents are attached. X Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC		
X Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15.17 13 NMAC		
[] Sometimes of the second of		
X Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)		
X Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) X Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC		

Form C-144 Oil Conservation Division Page 3 of 5

16		
Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19.15 17 13.D NMAC) Instructions Please identify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if more than two facilities for the disposal of liquids.	ıcilıtıes	
are required.		
Disposal Facility Name Disposal Facility Permit #:	<u></u>	
Disposal Facility Name Disposal Facility Permit #:		
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will not be used for future service and operations? Yes (If yes, please provide the information No		
Required for impacted areas which will not be used for future service and operations		
Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC	<u>~</u>	
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15 17.13 NMAC		
17 Siting Criteria (Regarding on-site closure methods only: 19 15.17.10 NMAC		
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below	w. Requests regarding changes to	
certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19 15 17 10 NMAC for guidance.	Santa Fe Environmental Bureau office	
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS: Data obtained from nearby wells	∐Yes ∐No	
- NW Office of the State Englises - TWATERS database scarcif, 0505. Data obtained from fically wells	∐N/A — —	
Ground water is between 50 and 100 feet below the bottom of the buried waste	Yes No	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□N/A	
Ground water is more than 100 feet below the bottom of the buried waste	Yes No	
- NM Office of the State Engineer - iWATERS database search, USGS; Data obtained from nearby wells	□ _{N/A} □	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake	☐Yes ☐No	
(measured from the ordinary high-water mark).		
- Topographic map; Visual inspection (certification) of the proposed site		
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	∐Yes ∐No	
- Visual inspection (certification) of the proposed site; Aerial photo, satellite image		
Within 500 howards foot of a project demands from howards for howards that less than five howards the control of the control o	∐Yes ∐No	
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existence at the time of the initial application		
- NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	Yes No	
- Written confirmation or verification from the municipality; Written approval obtained from the municipality		
Within 500 feet of a wetland	∏Yes ∏No	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site		
Within the area overlying a subsurface mine.	Yes No	
- Written confirantion or verification or map from the NM EMNRD-Mining and Mineral Division		
Within an unstable area.	∐Yes ∐No	
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society; Topographic map 		
Within a 100-year floodplain.	∏Yes ∏No	
- FEMA map		
18		
On-Site Closure Plan Checklist: (19 15.17.13 NMAC) Instructions: Each of the following items must bee attached to the closure	e plan. Please indicate,	
by a check mark in the box, that the documents are attached.		
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC		
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19 15.17.13 NMAC		
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15 17.11 NMAC		
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 1	9.15.17.11 NMAC	
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC		
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15 17 13 NMAC		
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17 13 NMAC		
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)		
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19 15 17.13 NMAC		
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC		

19 Operator Application Certification:	,	,
I hereby certify that the information submitted with this app	ication is true, accurate and complete to the be	est of my knowledge and belief.
Name (Print) Crystal Tafoya	Title	Regulatory Technician
Signature	Tapya Date:	9/30/08
e-mail address <u>crystal.taloya@conocop</u>	Telephone:	/ 505-326-9837
OCD Approval: Rermit Application (including	losure plan)	OCD Conditions (see attachment)
OCD Representative Signature:		
, 000	04	Approval Date:
Title: ENVOSPEC	OCD Permit	Number:
21		
Closure Report (required within 60 days of closure		
Instructions: Operators are required to obtain an approved report is required to be submitted to the division within 60	· · · · · · · · · · · · · · · · · · ·	
approved closure plan has been obtained and the closure a	· · · · · · · · · · · · · · · · · · ·	
	Closure	Completion Date:
22		
Closure Method:		
Waste Excavation and Removal On-site	Closure Method Alternative Closure M	fethod Waste Removal (Closed-loop systems only)
If different from approved plan, please explain		
23		
Closure Report Regarding Waste Removal Closure For		und Steel Tanks or Haul-off Bins Only: gs were disposed. Use attachment if more than two facilities
were utilized.	ere me aquas, arang jaws ana ara taung	s were aisposea. Ose aiacnment y more than two jacuates
Disposal Facility Name:	Disposal Facility P	ermit Number
Disposal Facility Name	Disposal Facility P	
Were the closed-loop system operations and associated Yes (If yes, please demonstrate compliane to the it	· —	be used for future service and opeartions?
Required for impacted areas which will not be used for		
Site Reclamation (Photo Documentation)	unire service una operations.	
Soil Backfilling and Cover Installation		
Re-vegetation Application Rates and Seeding Tech	ique	
24		
Closure Report Attachment Checklist: Instruction the box, that the documents are attached.	ns: Each of the following items must be attach	hed to the closure report. Please indicate, by a check mark in
Proof of Closure Notice (surface owner and div	sion)	
Proof of Deed Notice (required for on-site clos	re)	
Plot Plan (for on-site closures and temporary p	s)	
Confirmation Sampling Analytical Results (if a	oplicable)	
Waste Material Sampling Analytical Results (1	applicable)	
Disposal Facility Name and Permit Number		
Soil Backfilling and Cover Installation		
Re-vegetation Application Rates and Seeding 7 Site Reclamation (Photo Documentation)	ecunque	
On-site Closure Location: Latitude:	Longitude.	NAD 1927 1983
25		
Operator Closure Certification:		
I hereby certify that the information and attachments subm the closure complies with all applicable closure requireme		nd complete to the best of my knowledge and belief I also certify that
,		энге рин.
Name (Print):	Title.	
Signature:	Date:	
e-mail address:	Telephone	

Burlington Resources Oil & Gas Company, LP San Juan Basin Dig & Haul Closure Plan

In accordance with Rule 19.15.17.12 NMAC the following information describes the closure requirements of temporary pits on Burlington Resources Oil & Gas Company, LP (BR) locations. This is BR's standard procedure for temporary pits, which BR intends to excavate pit contents and dispose of off-site. A separate plan will be submitted for any temporary pit which does not conform to this plan.

All closure activities will include proper documentation and be available for review upon request and will be submitted to OCD within 60 days of closure of pit closure. Closure report will be filed on C-144 and incorporate the following:

- Details on Capping and Covering, where applicable.
- Plot Plan (Pit Diagram)
- Inspection Reports
- Sampling Results
- C-105
- Copy of Deed Notice will be filed with County Clerk

General Plan:

- All free standing liquids will be removed at the start of the pit closure process from the pit and disposed of in a division—approved facility or recycle, reuse or reclaim the liquids in a manner that the appropriate division district office approves. The facilities to be used will be Basin Disposal (Permit #NM-01-005) and Envirotech Land Farm (Permit #NM-01-011).
- 2. The surface owner shall be notified of BR's closing of the temporary pit prior to closure as per the approved closure plan via certified mail, return receipt requested.
- 3. Within 6 months of the Rig Off status occurring BR will ensure that temporary pits are closed, re-contoured, and reseeded.
- 4. Notice of Closure will be given prior to closure to the Aztec Division office between 72 hours and one week via email, or verbally. The notification of closure will include the following:
 - i. Operator's name
 - ii. Location by Unit Letter, Section, Township, and Range. Well name and API number.
- All contents of the temporary pit including the liner will be excavated and hauled to the Envirotech Land Farm located 16 miles south of Bloomfield on Angel Peak Road, CR 7175. Permit # NM010011
- 6. A five point composite sample will be taken from the soil under the pit using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b).

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	1000/500

- 7. Upon testing standards being passed, the pit area will be backfilled with compacted, nonwaste containing, earthen material. The cover shall include one foot of suitable material to establish vegetation at the site, or the background thickness of topsoil, whichever is greater
- 8. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Reshaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 9. Notification will be sent to OCD when the reclaimed area is seeded.

10. BR shall seed the disturbed areas the first growing season after the operator removes the pit. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality)

Purity

50 percent

Germination

40 percent

Percent PLS

20 percent

Source No. two (better quality)

Purity

80 percent

Germination

63 percent

Percent PLS

50 percent

5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS 1 lb. PLS

11. The temporary pit will be located with a steel marker, no less than four inches in diameter, cemented in a hole three feet deep in the center of the onsite burial upon the abandonment of all the wells on the pad. The marker will be flush with the ground to allow access of the active well pad and for safety concerns. The marker will include a threaded collar to be used for future abandonment. The top of the marker will contain a welded steel 12" square plate that indicates the onsite burial of the temporary pit. The plate will be easily removable and a four foot tall riser will be threaded into the top of the collar marker and welded around the base with the operator's information at the time of all wells on the pad are abandoned. The operator's information will include the following: Operator Name, Lease Name, Well Name and number, Unit Number, Section, Township, Range and an indicator that the marker is an onsite burial location.