

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

970' FNL, 1660' FEL, Sec. 26, T-27-N, R-9-W, NMMP

5. Lease Number
NMSF078356A

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name
Huerfanito Unit

8. Well Name & Number
Huerfanito Unit 94R
9. API Well No.
30-045-30845
10. Field and Pool
Blanco PC South
11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Other Csg & Cmt	

13. Describe Proposed or Completed Operations

10/10/03 MIRU. Change out both drilling lines. SDFN.
10/11/03 NU BOP. Install Manifold & choke lines. TIH & Tag Cmt @ 115'. PT BOP to 500 psi, OK. SDFN.
10/12/03 Drill Cmt & shoe. Drill 140-675'. Survey @ 637'=1 deg. SDFN.
10/14/03 TIH. Drill 675-1168'. Survey @ 1130= 0.75 deg. Drill 1168-1355'. Circ btms up. SDFN.
10/15/03 TIH, Drill 1355-1785'. Repair Swivel. SDFN.
10/16/03 Finish Repairing Swivel. TIH. Wash & Ream 60' to btm. Drill from 1784' to 2061'. Mud up @ 1968'. Circ hole clean. TOOH. Close annular Dry watch
10/17/03 TIH w/drill pipe. Drill from 2062' to 2340'. Circulate hole clean. TOOH. Close annular, open 3" manifold. Install drill pipe valve. Dry watch.
10/18/03 TIH w/drill pipe. Drill from 2340' to 2396'. Circulate hole clean. Wireline survey @ 2358'. TOOH. Close annular. Dry Watch.
10/19/03 TIH w/drill pipe. Circ & cond. L/D drill pipe. TIH w/55 Jts 4.5", STC, 10.5# csg. Tag bottom @ 2396'. Land mandrel in WH. PT cmt lines to 3500 psi, OK. Pump ahead 20 BBLs water. Pump 183 sxs Premium Lite Cmt w/3% CaCl₂, .25 PPS cello-flake, 5.PPS LCM-1, .4% FL-52, .4% Sodium metasilicate. (390 cu ft). Tail w/90 sxs Type III cmt w/1% CaCl₂, .20% FL-52, .25 PPS Cellflake. Displace w/water. Circulated 20 BBLs cmt to surface. Bottom guide shoe 2389', Top of float collar 2346', Marker joint @ 1463' to 1658'. Rig Down. Rig Released.

14. I hereby certify that the foregoing is true and correct.

Signed Frances Bond Title Regulatory Assistant **ACCEPTED FOR RECORD**

fsb

(This space for Federal or State Office use)

APPROVED BY

Title

Date

OCT 27 2003

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD