orm 3 160-5 august 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0135
Expires Jnovember 30, 2000

5. Lease Serial No.

SF-077382

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or reenter an abandoned well. Use Form 3160-3 (APD) for such proposals.

. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPL	ICATE – Other instru	ictions on revers	e side Divi	7. If Unit or CA √	Agreement, Name and/or No.
Type of Well Oil Well Sas Well	Other		27, 38, 30,	8. Well Name a	nd No.
. Name of Operator			Con Constitution of the	Kutz Govern	
Breck Operating Company				API Well No	
a. Address		3b. Phone No. finclude a	réa còde 2003	30-\045-3172	
7415 E. Main, Farmington, NM,	87402	505-327-4892	F	10. Field and Po	ol, or Exploratory Area
. Location of Well (Footage, Sec., T., R.	, M., or Survey Description)	22		Basin Fruitla	nd Coal
660' FSL and 1980' FEL, Sectio	n 3, T27N, R10W	100	Charles ""	11. County or Pa	arish, State
TYPE OF SUBMISSION	Γ	TVD	E OF ACTION	San Juan	
TIPE OF SUBMISSION		1117	E OF ACTION		
Notice of Intent Subsequent Report	Acidize Alter Casing Casing Repair	Deepen Fracture Treat New Construction	Production (S Reclamation Recomplete	tart/Resume)	Water Shut-Off Well Integrity Other
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back	Temporarily Water Dispos		
13. Describe Proposed or Completed Ope If the proposal is to deepen direction Attach the Bond under which the ware Following completion of the involve Testing has been completed. Final determined that the site is ready for fin	d operations. If the operation resu Abandonment Notices shall be fil	ilts in a multiple completion	or recompletion in a	new interval, a F	orm 3160-4 shall be filed once

9/21/03 Spud surface hole. Drilled to 139'. Ran 3 jts. (126.52') of 7", 23#, K-55, LT&C casing and set at 132' KB. Cemented with 50 sx (59 cu.ft.) of Cl "B" with 3% CaCl 2 and 1/4#/sk celloflake. Circulated 6.0 bbls of good cement to surface. Pressure test casing and BOP to 600 psi.

9/26/03 Ran 49 jts. (2127.17') of 4-1/2", 10.5#, J-55, ST&C new casing and landed at 2132' KB. Insert float ia at 2109" KB Cemented with 225 sx (470 cu.ft.) of Cl"B" 2% econolite cement with 1/4#/sk celloflake and 5#/sk gilsonite, followed by 100 sx (123 cu.ft.) of Cl"B" with 1/4#/sk celloflake and 5#/sk gilsonite. Circulated 7 bbls of cement to surface.

14. I hereby certify that the foregoing is true and correct		
Name (Printed/Typed)	Title	•
Paul Thompson		Engineer/Agent
Signature Paul C. Thomas-	Date	October 7, 20CCEPTED FOR RECORL
THIS SPACE FO	R FEDERAL OR STATE	USE
Approved by	Title	Date 00:1 2.7 2003
Conditions of approval, if any, are attached. Approval of this notice does not war certify that the applicant holds legal or equitable title to those rights in the subject which would entitle the applicant to conduct operations thereon.		RY SEE OFFICE

Title 18 U.S.C. Section 1001, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.