UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT



OCT 2 8 2008

	Sundry Notices and Reports on Wells	1111 4	יי, רפייות ואשטפטבע ובער
			ington Field Office
		5.	Lease Number SF-079266
١.	Type of Well	6.	If Indian, All. or
	GAS		Tribe Name
		7.	Unit Agreement Nam
	Name of Operator		
	BURLINGTON RESCURCES OIL & GAS COMPANY LP		
	——————————————————————————————————————	8.	Well Name & Number
	Address & Phone No. of Operator	٠,	Vaughn 8P
	PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
	Location of Well, Footage, Sec., T, R, M	•	30-039-30544
-		10.	Field and Pool
			Basin DK/Blanco MV
	Surf: Unit P (SESE), 1116' FSL & 1151' FEL, Section 26, T26N, R6W, NMPM BH: Unit J (SESE), 2175' FSL & 1875' FEL, Section 26, T26N, R6W, NMPM	11.	County and State
	DH: Unit J (SESE), 21/5 FSL & 18/5 FEL, Section 20, 120N, ROW, NIVIPNI	11.	County and State Rio Arriba, NM
	Notice of Intent Abandonment Recompletion New Construction Non-Routine Fracturing Casing Repair Water Shut off	-	Other Spud Report RCVD OCT 30 '08 OIL CONS. DIV.
			9 4 9 5
	Final Abandonment Altering Casing Conversion to Injection		DIST. 3
/el 5/ en		2bbl)	DIST. 3 2. RIH w/ 6 jnts, Type 3 cmt w/8%
/el 5/ en	Final Abandonment Altering Casing Conversion to Injection Describe Proposed or Completed Operations Il spud date; 09/30/08. 10/23/08 MIRU AWS 673. MU 12.25" bit & drilled ahead to 262'. Ci 8"csg, 32.3#, H-40, ST&C & set @ 251'. Pre-flush w/ 15bbl H2O & Pumped 180sx (236cf-4 atonite, 3% CaCl, .25pps Cello Flake. Drop & displace plug w/18 bbl H2O circ 23 bbl cmt to	2bbl)	DIST. 3 2. RIH w/ 6 jnts, Type 3 cmt w/8%
/el 5/ en sg	Final Abandonment Altering Casing Conversion to Injection Describe Proposed or Completed Operations Il spud date; 09/30/08. 10/23/08 MIRU AWS 673. MU 12.25" bit & drilled ahead to 262'. Ci 8"csg, 32.3#, H-40, ST&C & set @ 251'. Pre-flush w/ 15bbl H2O & Pumped 180sx (236cf-4 atonite, 3% CaCl, .25pps Cello Flake. Drop & displace plug w/18 bbl H2O circ 23 bbl cmt to	2bbl)	DIST. 3 2. RIH w/ 6 jnts, Type 3 cmt w/8%
/el 5/ en sg	Pinal Abandonment Altering Casing Conversion to Injection Describe Proposed or Completed Operations Il spud date; 09/30/08. 10/23/08 MIRU AWS 673. MU 12.25" bit & drilled ahead to 262'. Ci 8"csg, 32.3#, H-40, ST&C & set @ 251'. Pre-flush w/ 15bbl H2O & Pumped 180sx (236cf-4 atonite, 3% CaCl, .25pps Cello Flake. Drop & displace plug w/18 bbl H2O circ 23 bbl cmt to @ 600#/30min, OK. ✓.	2bbl)	DIST. 3 2. RIH w/ 6 jnts, Type 3 cmt w/8% 2. 10/25/08. 10/26/08 PT ACCEPTED FOR RECORD OCT 2 9 2008
/el 5/ en sg	Pinal Abandonment Altering Casing Conversion to Injection Describe Proposed or Completed Operations Il spud date; 09/30/08. 10/23/08 MIRU AWS 673. MU 12.25" bit & drilled ahead to 262'. Ci 8"csg, 32.3#, H-40, ST&C & set @ 251'. Pre-flush w/ 15bbl H2O & Pumped 180sx (236cf-4 atonite, 3% CaCl, .25pps Cello Flake. Drop & displace plug w/18 bbl H2O circ 23 bbl cmt to @ 600#/30min, OK. ✓.	2bbl)	DIST. 3 E. RIH w/ 6 jnts, Type 3 cmt w/8% E 10/25/08. 10/26/08 PT ACCEPTED FOR RECORD
Vel 5/ Sen Seg	Pinal Abandonment Altering Casing Conversion to Injection Describe Proposed or Completed Operations Il spud date; 09/30/08. 10/23/08 MIRU AWS 673. MU 12.25" bit & drilled ahead to 262'. Circ 8"csg, 32.3#, H-40, ST&C & set @ 251'. Pre-flush w/ 15bbl H2O & Pumped 180sx (236cf-4 atonite, 3% CaCl, .25pps Cello Flake. Drop & displace plug w/18 bbl H2O circ 23 bbl cmt to @ 600#/30min, OK.	2bbl)	DIST. 3 RIH w/ 6 jnts, Type 3 cmt w/8% 10/25/08. 10/26/08 PT ACCEPTED FOR RECORD OCT 2 9 2008 FARMONSTON FIELD OFFICE
/el 5/ en Sg .PI	Pinal Abandonment Altering Casing Conversion to Injection Describe Proposed or Completed Operations Il spud date; 09/30/08. 10/23/08 MIRU AWS 673. MU 12.25" bit & drilled ahead to 262'. Ci 8"csg, 32.3#, H-40, ST&C & set @ 251'. Pre-flush w/ 15bbl H2O & Pumped 180sx (236cf-4 atonite, 3% CaCl, .25pps Cello Flake. Drop & displace plug w/18 bbl H2O circ 23 bbl cmt to @ 600#/30min, OK. ✓.	2bbl) surface	DIST. 3 RIH w/ 6 jnts, Type 3 cmt w/8% 10/25/08. 10/26/08 PT ACCEPTED FOR RECORD OCT 2 9 2008 FARMS CTON FIELD OFFICE BY T. SANS
Vel 5/ Sen sg PI	Describe Proposed or Completed Operations Il spud date; 09/30/08. 10/23/08 MIRU AWS 673. MU 12.25" bit & drilled ahead to 262'. Ci (8"csg, 32.3#, H-40, ST&C & set @ 251'. Pre-flush w/ 15bbl H2O & Pumped 180sx (236cf-4 atonite, 3% CaCl, .25pps Cello Flake. Drop & displace plug w/18 bbl H2O circ 23 bbl cmt to @ 600#/30min, OK.	2bbl) surface	DIST. 3 RIH w/ 6 jnts, Type 3 cmt w/8% 10/25/08. 10/26/08 PT ACCEPTED FOR RECORD OCT 2 9 2008 FARIANCE TO FFICE BY T. SAMPES
Vel 5/Sen Sen Sen Spi 4.	Describe Proposed or Completed Operations Il spud date; 09/30/08. 10/23/08 MIRU AWS 673. MU 12.25" bit & drilled ahead to 262'. Ci 8"csg, 32.3#, H-40, ST&C & set @ 2512. Pre-flush w/ 15bbl H2O & Pumped 180sx (236cf-4 tonite, 3% CaCl, .25pps Cello Flake. Drop & displace plug w/18 bbl H2O circ 23 bbl cmt to @ 600#/30min, OK.	nician	DIST. 3 RIH w/ 6 jnts, Type 3 cmt w/8% 10/25/08. 10/26/08 PT ACCEPTED FOR RECORD OCT 2 9 2008 FARMS CTON FIELD OFFICE BY T. SANS