

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
OMB NO. 1004-0137  
Expires July 31, 2010

OCT 08 2008

SUNDRY NOTICES AND REPORTS ON WELLS

**Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.**

**SUBMIT IN TRIPLICATE - Other instructions on page 2**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Energen Resources Corporation

3a. Address

2010 Afton Place, Farmington, NM 87401

3b. Phone No. (include area code)

(505) 325-6800

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

680' ESL, 2200' FEL Section 17, T29N, R11W Unit O

5. Lease Serial No.

NM 019405

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.

Bloomfield #3

9. API Well No.

30-045-26575

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- |   |  |  |   |
|---|--|--|---|
| <input type="checkbox"/> Acidize              | <input type="checkbox"/> Deepen                      | <input type="checkbox"/> Production (Start/Resume) | <input type="checkbox"/> Water Shut-Off |
| <input type="checkbox"/> Alter Casing         | <input type="checkbox"/> Fracture Treat              | <input type="checkbox"/> Reclamation               | <input type="checkbox"/> Well Integrity |
| <input type="checkbox"/> Casing Repair        | <input type="checkbox"/> New Construction            | <input type="checkbox"/> Recomplete                | <input type="checkbox"/> Other          |
| <input type="checkbox"/> Change Plans         | <input checked="" type="checkbox"/> Plug and Abandon | <input type="checkbox"/> Temporarily Abandon       |   |
| <input type="checkbox"/> Convert to Injection | <input type="checkbox"/> Plug Back                   | <input type="checkbox"/> Water Disposal            |   |

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

RCVD OCT 30 '08  
OIL CONS. DIV.  
DIST. 3

Energen Resources plans to Plug and Abandon the Bloomfield #3 as follows:

1. MIRU. ND Wellhead. NU BOP.
2. TOH w/ 1-1/4" tbg, inspect and talley.
3. TIH w/ CIBP and set @ 1575'. Pressure test csg to 500 psi for 15 min. TOH w/ tbg. TIH w/ wire-line and run CBL. Determine TOC. TOH w/ wire-line. (Depending on the TOC, procedure may need to be altered).
4. TIH w/ tbg to 1570'. Set a cmt plug across the Fruitland Coal top f/ 1475'-1575' w/ 6 sks of neat cmt (50% excess). Pull tbg above cmt. Wait 4 hrs and tag cmt.
5. Pull tbg up to 730'. Set a balanced cmt plug across the Kirtland top f/ 630'-730' w/ 6 sks of neat cmt (50% excess). Pull tbg above cmt. Wait 4 hrs and tag cmt.
6. TIH w/ wire'line and perforate 2 squeeze holes @ 580'. TOH w/ wire-line.
7. Establish circulation out of the bradenhead w/ water. Circulate the bradenhead annulus clean. Pump 235 sks of neat cement down 2-7/8" csg to circulate good cmt out the bradenhead. This will cover the Ojo Alamo top to the surface inside and outside the csg. SI well and wait on cmt 4 hrs.
8. ND BOP and cut off csg below surface csg flange. Install P&A marker w/ cmt to comply w/ regulations. RDMO, cut off anchors and restore location.

14. I hereby certify that the foregoing is true and correct  
Name (Printed/Typed)

Kirt Snyder

Title District Engineer

Signature

Date 10/6/2008

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Original Signed: Stephen Mason

Title

Date

OCT 27 2008

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMCOO

11/6