

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

## Sundry Notices and Reports on Wells

**RECEIVED**

**OCT 28 2008**

Bureau of Land Management  
Farmington Office  
**Lease Number**  
**USA SF - 079391**

1. **Type of Well**  
GAS

6. **If Indian, All. or  
Tribe Name**

2. **Name of Operator**

**BURLINGTON**

**RESOURCES OIL & GAS COMPANY LP**

7. **Unit Agreement Name**

**San Juan 27-5 Unit**

**Well Name & Number**

3. **Address & Phone No. of Operator**

PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. **San Juan 27-5 Unit 905**

**API Well No.**

4. **Location of Well, Footage, Sec., T, R, M**

**Surf: Unit E (SWNW), 1695' FNL & 1161' FWL, Section 8, T27N, R5W, NMPM**

**BH: Unit F (SENW), 1635' FNL & 1665' FWL, Section 8, T27N, R5W, NMPM**

**30-039-30310**

10. **Field and Pool**  
**Blanco MV/Basin DK**

11. **County and State**  
**Rio Arriba Co., NM**

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

**Type of Submission**

**Type of Action**

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Other - Casing Report

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Plugging

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Final Abandonment

☐ Altering Casing

☐ Conversion to Injection

**RCVD OCT 30 '08**

**OIL CONS. DIV.**

**13. Describe Proposed or Completed Operations**

**DIST. 3**

6/15/08 MIRU AWS 184. NU BOP. PT csg to 600# 30/min - good test. RIH w/8 3/4" bit, tagged cement @ 214'. D/O cement & Ahead to 3725' (intermediate TD reached on 6/18/08). Circ hole. RIH w/87 jts 7" 23# L-80 csg set @ 3716'. RU to cement. 6/19/08 Pumped pre-flush of 10 bbls gel/2 bbls spacer. Pumped Scavenger 20 sx(60cf-32bbls) Premium Lite Cement w/8% Bentonite, 3% CaCl2, .25 #/sx Cello-Flake, .4% FL-52, 5 #/sx LCM-1, .4% Sodium Metasilicate. **Lead-** pumped 510 sx(1086cf-193bbls) Premium Lite Cement w/8% Bentonite, 3% CaCl2, .25 #/sx Cello-flakes, .4% FL-52, 5 #/sx LCM-1, & .4% Sodium Metasilicate. **Tail-** pumped 90 sx(124cf-22bbls) Type III Cement w/1% CaCl2, .25#/sx Cello-Flake, .2% FL-52. Bumped plug.

**6/20/08 Notified Wayne Townsend (BLM) no cement to surface on intermediate csg. Requested temp survey run. Temp survey showed TOC @ 400'. No remediation required.**

6/20/08 WOC. Ran temp survey. WOC. PT csg to 1500# 30/min -good test. RIH w/6 1/4" bit. D/O cement, tag @ 3665'. Drill ahead to 7911' TD. TDReached on 6/23/08. Circ hole. RIH w/185 jts 4 1/2" 11.6# L-80 LT & C casing set @ 7910'. RU to cement. 6/24/08 Pumped pre-flush of 10 bbls gel water/2 bbls FW. Pumped Scavenger 10 sx(30cf-5 bbls) Premium Lite HS FM Cement w/.3% CD-32, 1% FL-52, .25 #/sx Cello-flake, 6.25 #/sx LCM-1. **Tail-** 310 sx(614cf-109bbls) Premium Lite HS FM Cement w/.25 #/sx Cello-Flake, 6.25 #/sx LCM-1, .3% CD-32, 1% FL-52. Dropped plug & displaced w/124 bbls FW. Bumped plug to 1245#. Plug down @ 14:20. ND BOPE. RD RR @ 20:30 6/24/08.

PT will be conducted by completion rig. PT & TOC will be recorded on next report.

**14. I hereby certify that the foregoing is true and correct.**

Signed Tracey N. Monroe

Tracey N. Monroe Title Staff Regulatory Technician

Date 10/28/08

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_

Date **ACCEPTED FOR RECORD**

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

**NMOCD**

10/11/7

