

1220 S. St. Francis Dr., Santa Fe, NM 87505

AS DRILLED

Free Lease - 3 Copies


☒ AMENDED REPORT

¹ API Number 30-045-34646		² Pool Code 96175	³ Pool Name Rosa Pictured Cliffs	
⁴ Property Code 19641	⁵ Property Name Northeast Blanco Unit			⁶ Well Number 251H
⁷ OGRID No. 6137	⁸ Operator Name Devon Energy Production Company, L.P.			⁹ Elevation 6386' GL

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
O	6	31-N	6-W		235'	SOUTH	2330'	EAST	San Juan

UL or lot no. L	Section 6	Township 31-N	Range 6-W	Lot Idn	Feet from the 1998'	North/South line SOUTH	Feet from the 703'	East/West line WEST	County San Juan
--------------------	--------------	------------------	--------------	---------	------------------------	---------------------------	-----------------------	------------------------	--------------------

¹² Dedicated Acres 176.68	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No	RCVD NOV 6 08 OIL COMS DIV
---	-------------------------------	----------------------------------	------------------------	-------------------------------

				17 OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. Signature  Date 11/4/08 Mike Pippin Printed Name	
Lot 11 Lot 10 Lot 9 Lot 8 6 BOTTOM HOLE 703' 1998' 1939' 1032' 7" shoe SURFACE 2330' 5'				18 SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. 3/26/08 Date of Survey Signature and Seal of Professional Surveyor: Gary D. Vann 7016 Certificate Number	

26 11/7



Job Number:
Company: Devon Energy
Lease/Well: NEBU # 251H
Location: San Juan County
Rig Name:
RKB:
G.L. or M.S.L.:

State/Country: NM
Declination:
Grid:
File name: J:\CUST08~1\SURVEYS\DEVON\08222.SVY
Date/Time: 08-Sep-08 / 09:17
Curve Name: As Drilled

API # 30-045-34646

NEBU #251H (7")

(06) SURF: 235' FS 2330' FE
797 996
1032' FS 3326' FE
7" SHOE 2645
1939 FW 2620

Inwell, Inc

WINSERVE SURVEY CALCULATIONS
Minimum Curvature Method
Vertical Section Plane 308.31
Vertical Section Referenced to Wellhead
Rectangular Coordinates Referenced to Wellhead

NEBU #251H (BH)

(06) SURF: 235' FS 2330' FE (6)
1763 2232
(L6) 1998' FS 4562
BH -2645
-2620
703' FW (6)

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
2365.00	.00	.00	2365.00	.00	.00	.00	.00	.00	.00
2402.00	4.60	317.10	2401.96	1.09	-1.01	1.47	1.48	317.10	12.43
2433.00	6.60	314.40	2432.81	3.24	-3.13	4.47	4.51	316.03	6.51
2465.00	8.50	315.10	2464.53	6.21	-6.11	8.64	8.71	315.44	5.94
2495.00	10.40	313.80	2494.12	9.65	-9.63	13.54	13.64	315.06	6.37
2526.00	12.70	313.10	2524.49	13.92	-14.14	19.72	19.84	314.54	7.43
2558.00	14.70	312.10	2555.58	19.04	-19.72	27.28	27.42	314.00	6.29
2589.00	16.80	311.80	2585.42	24.67	-25.98	35.68	35.83	313.51	6.78
2620.00	18.90	310.80	2614.92	30.93	-33.12	45.17	45.32	313.04	6.85

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
2652.00	21.40	310.60	2644.96	38.12	-41.48	56.18	56.34	312.58	7.82
2683.00	24.10	310.20	2673.55	45.89	-50.61	68.16	68.32	312.20	8.72
2714.00	27.00	309.20	2701.51	54.42	-60.90	81.52	81.67	311.79	9.46
2746.00	29.80	307.80	2729.66	63.89	-72.81	96.74	96.87	311.26	8.99
2777.00	32.40	306.80	2756.20	73.59	-85.55	112.75	112.85	310.70	8.55
2808.00	35.20	306.40	2781.96	83.87	-99.40	129.98	130.05	310.16	9.06
2840.00	37.70	306.90	2807.70	95.22	-114.65	148.99	149.03	309.71	7.87
2871.00	40.40	307.20	2831.77	106.98	-130.23	168.51	168.54	309.40	8.73
2902.00	43.70	307.40	2854.79	119.56	-146.75	189.27	189.29	309.17	10.65
2933.00	46.70	307.80	2876.63	132.99	-164.17	211.26	211.28	309.01	9.72
2964.00	49.20	308.10	2897.39	147.14	-182.32	234.28	234.29	308.91	8.10
2993.00	51.20	308.20	2915.95	160.90	-199.84	256.56	256.57	308.84	6.90
3024.00	53.20	307.80	2934.95	175.98	-219.14	281.05	281.06	308.77	6.53
3053.00	55.40	307.40	2951.87	190.35	-237.80	304.60	304.60	308.68	7.67
3085.00	57.60	307.30	2969.53	206.54	-259.01	331.28	331.28	308.57	6.88
3116.00	59.40	307.60	2985.73	222.61	-279.99	357.70	357.70	308.49	5.86
3147.00	60.90	307.40	3001.16	238.98	-301.33	384.59	384.59	308.42	4.87
3178.00	62.50	307.20	3015.85	255.52	-323.04	411.88	411.88	308.34	5.19
3209.00	65.10	307.80	3029.54	272.45	-345.10	439.69	439.69	308.29	8.56
3241.00	68.20	308.30	3042.22	290.56	-368.23	469.06	469.06	308.28	9.79
3272.00	69.10	307.60	3053.51	308.31	-391.00	497.93	497.93	308.26	3.58
3334.00	70.40	307.90	3074.97	343.92	-436.99	556.10	556.10	308.20	2.15
3365.00	71.40	307.40	3085.11	361.82	-460.18	585.39	585.39	308.18	3.57
3456.00	70.50	307.80	3114.81	414.30	-528.33	671.40	671.40	308.10	1.07
3550.00	70.10	307.60	3146.50	468.42	-598.36	759.89	759.90	308.06	.47
3645.00	70.20	308.10	3178.76	523.24	-668.91	849.24	849.25	308.03	.51
3737.00	71.00	309.20	3209.32	577.44	-736.68	936.01	936.02	308.09	1.42
3830.00	71.80	310.60	3238.98	633.98	-804.29	1024.12	1024.12	308.25	1.67
3924.00	71.60	310.30	3268.50	691.88	-872.21	1113.30	1113.30	308.42	.37

	Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
								Distance FT	Direction Deg	
X	4017.00	69.40	309.80	3299.54	748.29	-939.31	1200.92	1200.93	308.54	2.42
	4097.00	70.40	311.60	3327.03	797.28	-996.26	1275.98	1276.00	308.67	2.45
	4119.00	70.90	312.60	3334.32	811.20	-1011.66	1296.69	1296.72	308.72	4.85
	4150.00	71.80	311.40	3344.24	830.85	-1033.49	1326.00	1326.05	308.80	4.68
	4180.00	74.30	309.90	3352.98	849.54	-1055.26	1354.67	1354.73	308.84	9.61
	4212.00	77.10	308.20	3360.89	869.07	-1079.34	1385.67	1385.73	308.84	10.15
	4243.00	79.90	307.30	3367.07	887.66	-1103.36	1416.05	1416.10	308.82	9.47
	4275.00	82.30	306.80	3372.02	906.71	-1128.59	1447.65	1447.70	308.78	7.66
	4304.00	84.80	307.60	3375.27	924.13	-1151.54	1476.46	1476.50	308.75	9.05
	4336.00	86.90	307.30	3377.59	943.54	-1176.87	1508.37	1508.41	308.72	6.63
	4367.00	88.60	307.40	3378.81	962.33	-1201.50	1539.34	1539.37	308.69	5.49
	4399.00	89.40	307.20	3379.36	981.72	-1226.95	1571.33	1571.36	308.66	2.58
	4429.00	90.10	307.60	3379.50	999.94	-1250.78	1601.33	1601.35	308.64	2.69
	4461.00	91.80	308.10	3378.97	1019.57	-1276.04	1633.32	1633.34	308.63	5.54
	4492.00	92.90	307.40	3377.69	1038.53	-1300.53	1664.29	1664.31	308.61	4.20
	4522.00	93.30	307.20	3376.07	1056.69	-1324.36	1694.24	1694.26	308.59	1.49
	4553.00	92.40	308.40	3374.53	1075.66	-1348.83	1725.20	1725.22	308.57	4.83
	4585.00	92.60	308.20	3373.13	1095.48	-1373.92	1757.17	1757.19	308.57	.88
	4616.00	92.80	307.90	3371.67	1114.56	-1398.30	1788.14	1788.15	308.56	1.16
	4646.00	92.10	308.60	3370.39	1133.12	-1421.84	1818.11	1818.12	308.55	3.30
	4677.00	91.00	308.90	3369.55	1152.51	-1446.01	1849.10	1849.11	308.56	3.68
	4706.00	91.10	309.10	3369.02	1170.76	-1468.54	1878.09	1878.11	308.56	.77
	4738.00	89.90	309.40	3368.74	1191.01	-1493.32	1910.08	1910.10	308.57	3.87
	4769.00	90.00	309.80	3368.77	1210.77	-1517.20	1941.07	1941.10	308.59	1.33
	4801.00	90.30	309.60	3368.69	1231.21	-1541.82	1973.06	1973.09	308.61	1.13
	4832.00	90.50	309.30	3368.47	1250.90	-1565.76	2004.06	2004.09	308.62	1.16
	4863.00	91.00	309.40	3368.06	1270.56	-1589.73	2035.05	2035.08	308.63	1.64
	4894.00	91.00	308.20	3367.52	1289.98	-1613.89	2066.04	2066.08	308.64	3.87
	4926.00	91.20	308.10	3366.91	1309.74	-1639.05	2098.04	2098.07	308.63	.70

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
4957.00	91.60	308.40	3366.15	1328.93	-1663.38	2129.03	2129.06	308.62	1.61
4988.00	92.10	308.60	3365.15	1348.22	-1687.63	2160.01	2160.04	308.62	1.74
5019.00	91.60	307.20	3364.15	1367.25	-1712.08	2190.99	2191.02	308.61	4.79
5051.00	92.00	306.60	3363.14	1386.45	-1737.66	2222.97	2222.99	308.59	2.25
5082.00	92.50	306.30	3361.93	1404.86	-1762.57	2253.93	2253.95	308.56	1.88
5113.00	93.00	305.80	3360.44	1423.08	-1787.61	2284.87	2284.88	308.52	2.28
5144.00	91.80	307.20	3359.14	1441.50	-1812.50	2315.82	2315.84	308.50	5.95
5175.00	90.60	308.20	3358.49	1460.45	-1837.03	2346.81	2346.83	308.49	5.04
5207.00	90.50	307.90	3358.19	1480.18	-1862.22	2378.81	2378.82	308.48	.99
5238.00	90.70	308.10	3357.86	1499.26	-1886.65	2409.81	2409.82	308.47	.91
5269.00	91.00	308.40	3357.40	1518.45	-1910.99	2440.81	2440.82	308.47	1.37
5300.00	91.20	308.10	3356.81	1537.64	-1935.33	2471.80	2471.81	308.47	1.16
5330.00	91.60	307.60	3356.07	1556.04	-1959.02	2501.79	2501.80	308.46	2.13
5362.00	92.10	307.60	3355.04	1575.55	-1984.36	2533.77	2533.78	308.45	1.56
5393.00	92.50	308.10	3353.80	1594.56	-2008.81	2564.75	2564.75	308.44	2.06
5424.00	93.10	308.10	3352.28	1613.67	-2033.18	2595.71	2595.71	308.44	1.94
5455.00	93.70	307.80	3350.44	1632.70	-2057.58	2626.65	2626.66	308.43	2.16
5486.00	93.70	307.10	3348.44	1651.51	-2082.14	2657.58	2657.59	308.42	2.25
5517.00	91.90	306.80	3346.93	1670.12	-2106.88	2688.54	2688.54	308.40	5.89
5548.00	91.80	306.40	3345.93	1688.59	-2131.76	2719.51	2719.51	308.38	1.33
5580.00	92.10	306.30	3344.84	1707.55	-2157.52	2751.47	2751.47	308.36	.99
5611.00	91.60	307.10	3343.84	1726.06	-2182.36	2782.44	2782.44	308.34	3.04
Projected to Bit									
5673.00	91.80	306.90	3342.00	1763.36	-2231.85	2844.40	2844.40	308.31	.46