

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

NOV 04 2008

## Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator  
**BURLINGTON**  
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
Unit C (NENW), 990' FNL && 1650' FWL, Sec. 19, T27N, R9W, NMPM

5. Lease Number  
NM-02861

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

8. Well Name & Number  
Lodewick #9

9. API Well No.  
30-045-06422

10. Field and Pool  
Basin Dakota

11. County and State  
San Juan Co., NM

## 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing

☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut off  
☐ Conversion to Injection

☐ Other -

RCVD NOV 6 '08  
OIL CONS. DIV.

DIST. 3

## 13. Describe Proposed or Completed Operations

10/20/08 MIRU A-Plus 10. Check psi on well, csg & BH 0#, no tbg in well. ND WH NU BOP. RU floor. Tally & PU 2.375" tbg to 2025'.  
10/21/08 PU & tally 23/8" 4.75# J-55 EUE tbg and tag CIBP @ 6770'. RU pump lines. Load hole w/17 bbls & circ well clean w/another 163 bbls. Attempt to PT csg- failed. Pump 27 bbls down BH, load hoe w/2.5 bbls. **Plug #1-** mix and pump 20 sx Type BCement from 6770' - 6593'. LD tbg to 6583'. TOH w/10 stands to 5960'. WOC.  
10/22/08 RU pump & lines. TIH & tag TOC of plug #1 @ 6649'. LD tbg to 6076'. Load hole w/9 bbls. Attempt to PT csg - failed. **Plug #2-** mix & pump 20 sx Type B Cement w/2% CaCl from 6076' to TOC @ 5889'. LD tbg to 5899'. TOH w/10 stands to 5899'. WOC. TIH & tag plug #2 TOC @ 5921'. LD tbg to 3988'. Load hole w/7 bbls. Attempt tp PT csg- failed. **Plug #3-** mix & pump 20 sx Type B Cement from 3988' to TOC @ 3811'. LD tbg to 3798'. TOH w/10 stands to 3174'.  
10/23/08 Check psi on well csg 20#, tbg 5#. BH had vacuum. TIH to 3989' w/tbg to tag plug #3- no tag, nothing there. RU pump & lines Load hle w/3 bbls water & test- no test. **Plug 3A-** spot 40 sx B Cement from 3988' to 3635' TOC. LD tbg to 3614'. POOH 10 stands to 2990'. WOC. TIH & tag TOC @ 3815' & LD tbg to 2430'. Load hole w/5 bbls water, try to test - no test. **Plug #4-** spot 70 sx B Cement from 2430' - 1812'. LD tbg to 1807'. POOH 10 stands to 1183'.  
10/24/08 Check psi on well, csg, tbg & BH slight vacuum. TIH w/tbg & tag plug #4 @ 1850'. LD tbg to 1651'. Load csg w/2 bbls water, Test csg to 750# - held for 5 minutes. **Plug #5-** spot 36 sx B Cement from 1651' to 1333'. LD all tbg.  
10/27/08 Check psi on well csg 0#, BH vacuum. No tbg in well. RU W/L. TIH & perf 3 hsc holes @ 382'. POOH & RD W/L. RD Floor & tbg equipment. **Plug #6-** mix & pump 199 sx B Cement from 382' to surface, csg full of cement, good returns out of BH. ND BOP. Cut off WH & install PA marker w/20 sx Cement. RD rig & equipment. Cut off anchors. MOL.

## 14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Staff Regulatory Technician Date 11/4/08

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

MMOCD

ACCEPTED FOR RECORD

Date NOV 05 2008

FARMINGTON FIELD OFFICE