Submit 3 Copies To Appropriate District State of New Mexico Form C-103 Office June 19, 2008 Energy, Minerals and Natural Resources District I WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 30-045-07994 District II OIL CONSERVATION DIVISION 1301 W. Grand Ave., Artesia, NM 88210 5. Indicate Type of Lease District III 1220 South St. Francis Dr. STATE | 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, INM\87505 sident 6. State Oil'& Gas Lease No. District IV 1220 S. St. Francis Dr., Santa Fe, NM SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A Valdez DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 8. Well Number 1. Type of Well: Oil Well ☐ Gas Well ☒ Other 9. OGRID Number 2. Name of Operator El PamCo, Inc. 006834 3. Address of Operator 10. Pool name or Wildcat PO Box 14738 Albuquerque, NM 87191 Aztec Fruitland Sand 4. Well Location Unit Letter : 1710 feet from the South line and 1110 feet from the East line Township 29N Range 11W **NMPM** County San Juan Section 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: ALTERING CASING [] PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK COMMENCE DRILLING OPNS.□ P AND A TEMPORARILY ABANDON CHANGE PLANS \Box \boxtimes PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE OTHER: The street OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 11/14/08 RU Bloomfield Well Service and BOP. Set CIBP @ 1500'. Pressure tested casing to 500#. Held for 15 min. Perforated casing @ 200', 4 SPF. Ran 47 JTS 1 1/4" tubing to 1496'. Shut down. 11/15/08 RU Superior. Pumped 12 SKS, 2.5 bbls Type 5 cement to set cement plug @ 1500 - 1400'. Lay down 22 JTS tubing. Pumped 46 SKS, 9.75 bbls Type 5 cement to set plug @ 765' to 350'. Lay down 25 JTS tubing, pull BOP. Pump 143 SKS, 30.8 bbls Type 5 cement. Circulate 5 bbs cement to surface. Shut Bradenhead valve. Pumped 20 bbls down back side. Shut down. RCUD MOU 25 'OB 11/17/08 Cut off wellhead, erect dry hole marker. Clean up location. OIL CONS. DIV. * . Alle. CIST. A Spud Date: Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowledge and belief. 11/19/08 SIGNATURE TITLE Vice President DATE 31,75.90. Set : 479.5 Type or print name William J. Mayhew E-mail address: Bill@McKayOilandGas.com , PHONE: 505-296-5508 For State Use Only Deputy Oil & Gas Inspector, District #3 DATE APPROVED BY: TITLE Approved for plugging of wellbore only. Conditions of Approval (if any): --Liability under bond is retained pending Receipt of C-103 (Subsequent Report of Well Plugging) which may be found @ OCD web page

under forms.

www.emnrd.state.us/ocd