In Lieu of Form 3160

## **UNITED STATES** DEPARTMENT OF INTERIOR



(June	BUREAU OF I	LAND MANAGEMENT		Expires March 31, 1993	
Do not use this form for proposals to drill or to deepen of		JAN 1220  O REPORTS ON WELLS  or reentry to a different reservoir. Use APPLICATION  in for such proposals  Farmington Field	5. gement	Lease Designation and Serial No.  Jicarilla Apache Contract #92	
	TO DRILL" for perm	nit for such proposals	6.	If Indian, Allottee or Tribe Name  Jicarilla Apache Nation	
SUBMIT IN TRIPLICATE			7	If Unit or CA, Agreement Designation	
1.	Type of Well Oil Well Gas Well X Other		8.	Well Name and No Jicarilla 92 #17A	
2.	Name of Operator WILLIAMS PRODUCTION COMPANY		9.	API Well No 30-039-29918	
3.	Address and Telephone No PO BOX 640 Aztec, NM 87410-0640		10	Field and Pool, or Exploratory Area Blanco MV	
4.	Location of Well (Footage, Sec, T, R., M, or Survey Description) 990' FNL & 920' FEL SEC 31, T27N, R3W		11	County or Parish, State Rio Arriba, NM	
	CHECK APPROPRIA	TE BOX(s) TO INDICATE NATURE OF NOTICE, REPO	ORT, OR O	THER DATA	
	TYPE OF SUBMISSION	TYPE OF SUBMISSION TYP		OF ACTION	
VF.	Notice of Intent  X Subsequent Report  Final Abandonment	Abandonment Recompletion Plugging Back Casing Repair Altering Casing X Other SURFACE CASING		Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note Report results of multiple completion on Well Completion or Recompletion Report and Log form )	
13.	Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*  RCUD JAN 29 '09				
<u>1/7/09-</u> TD- 12 1/4" SURFACE HOLE @ 350', 2230 HRS				OIL CONS. DIV. DIST. 3	
PJSM SPAC CIRC BUMF FULL VELA	ER AHEAD, 200 SX [281 cuft] TYPE III  28 BBL'S TO PIT. PLUG DN @ 5:50 A  PLUG & PRESSURE SPIKE TO 1100+ JT. CSG & SCREW BACK INTO CSG S RDE W/ JICARILLA BLM] (ALERTED (	EST LINES TO 1500 psi, PUMP SINGLE SLUICMT W/ 2% CaCl2 + 1/4# /sk cello-flake/sk ( y M 01/08/09 <b>J</b> PSI. LANDING JT. PARTED FROM CSG. 9-5 TRING & PICK UP TO SETTING DEPTH @ 3- GARY SIZEMORE TO LANDING JT FAILURE ON SETTING RAMS, MUD CROSS VALVES, CH	eild = 1.4 /8" CSG I 44'. [ CMT )	,10 bbl FRESH WATER 1 cuft/sk, WT = 14.5#/gal ) DROPPED 6'. PICK UP T JOB WITNESSED BY ROD NIFOLD VALVES, FLOOR VALVE,	
RAMS	PER KELLY VALVE @ 250# LOW-F/ 5 N 5 @ 1500# F/ 30 min. ALL TESTS GOOD FSSED TESTS ✔	nin. EACH, & 1500# HIGH- F/ 10 min. EACH. T YTEST PUMP # CHART RECORDER USED.	ROD VEI	LARDE W/ JICARILLA BLM	

14. I hereby certify that the foregoing is the and correct Title Drilling COM Date 1/12/09 Larry Higgins (This space for Federal or State office use) Approved by\_ Title Date \_\_\_\_ Conditions of approval, if any

Title 18 U.S.C Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false (fictinous of fraudulent statements or representations as to any matter within its jurisdiction.



