
In Lieu of Form 3160 (June 1990)

UNITED STATES DEPARTMENT OF INTERIOR **BUREAU OF LAND MANAGEMENT**



FORM APPROVED Budget Bureau No 1004-0135

	Links for the		Expires. March 31, 1993
Do	SUNDRY NOTICE AND REPORTS ON WELLS o not use this form for proposals to drill or to deepen or reentry to a different reservoir TO DRILL" for permit for such proposals Use "APPLICATION of Fairmington Field"	5.	Lease Designation and Serial No Jicarilla Apache Contract #92 If Indian, Allottee or Tribe Name Jicarilla Apache Nation
	SUBMIT IN TRIPLICATE	7	If Unit or CA, Agreement Designation
1.	Type of Well Oil Well Gas Well X Other	8	Well Name and No Jicarilla 92 #2B
2.	Name of Operator WILLIAMS PRODUCTION COMPANY	9.	API Well No. 30-039-29935
3	Address and Telephone No PO BOX 640 Aztec, NM 87410-0640	10.	Field and Pool, or Exploratory Area Blanco MV /Busin Dako ta
ŀ	Location of Well (Footage, Sec., T, R, M, or Survey Description) 1980' FSL & 660' FWL SEC 29, T27N, R3W	11.	County or Parish, State Rio Arriba, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION X Notice of Intent Abandonment Change of Plans Recompletion New Construction YR Subsequent Report Non-Routine Fracturing Plugging Back Casing Repair Water Shut-Off Final Abandonment Altering Casing Conversion to Injection X Other Surface Casing Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

1/16/09- TD 14 3/4" SURF HOLE @ 345', 1930 HRS RAN 8 JTS, 10.3/4", 40.50#, K-55, CSG SET @ 334', FLOAT INSERT @ 290'

1/17/09- CEMENT 10.3/4" CASING @ 334' - SHOE DEPTH / SINGLE SLURRY CEMENT JOB / 10 BBLS. FRESH WATER SPACER / 250 SXS TYPE 3 CEMENT + 2% CaCl-2 + .25#/SX CELLO FLAKE + 40.78 BBL. WATER = 112 BBL. (348 CuFt) SLURRY @ 14.5 PPG (YIELD = 1.41 / WGPS = 6.84) / DISPLACE WITH 29 BBL. WATER /500 PSI PLUG DOWN ON 1/17/2009 @ 0030 22 BBL .OF CEMENT RETURNS TO SURFACE.

INSTALL TEST PLUG & TEST BOP PIPE & BLIND RAMS, CHOKE MANIFOLD VALVES, MUD CROSS VALVES, FLOOR VALVE KELLY @ 250# 5-MIN EACH & 1500# 10-MIN EACH. TEST 10.3/4" CSG @ 1500# 30-MIN. TEST PUMP & TEST CHARTS USED ON ALL TESTS ALL TESTED GOOD.

14.	I hereby certify that the foregoing is true and correct Signed Larry Higgins	Title Drilling COM	Date <u>1/21/09</u>	
				ACCEPTED FOR RECORD
	(This space for Federal or State office use)			
	Approved by	Title		Date JAN 2 6 2009
	Conditions of approval, 1f any:			FARMINGTON/FIELD OFFICE

Title 18 U.S.C Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, ficting or fraudulent statements or representations as to any matter within its jurisdiction.

