UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

NOV 1 8 2008

FORM APPROVED OMB No 1004-0135 Expires January 31, 2004

5 Lease Serial No.

J.	Lease	OCI	ıaı	140

	IS ON WELLS		MDA 701	I - 04-00	/14		
Do not use this form for proposals to drill or to retenter an டன் மன் abandoned well. Use Form 3160-3 (APD) for such proposalsington Field Office					¹ 6. If Indian, Allottee or Tribe Name		
			Jicarilla A	pache	Nation		
SUBMIT IN TRIPLICATE - Other instruc	tions on rever	se side	7. If Unit or	CA/Ag	reement, Name and/or No		
1. Type of Well	.) ,	<u> </u>					
☐ Oil Well ☐ Gas Well ☐ Other					8. Well Name and No.		
2. Name of Operator			JAECO 28-3 No. 2				
Jicarilla Apache Energy Corp			9. API Wel				
3a Address	3b. Phone No. (incl	lo. (include area code) 30-039-30007					
P.O. Box 710 Dulce, New Mexico 87528	575-759-3224		10. Field and Pool, or Exploratory Area				
4. Location of Well (Footage, Sec., T, R., M., or Survey Description)			Blanco M				
1295' FNL & 1980' FWL, Sec 36, T28N, R3W	11. County or Parish, State						
	Rio Arriba, New Mexico						
12. CHECK APPROPRIATE BOX(ES) TO I	NDICATE NAT	URE OF NOTICE, RE	EPORT, OR	OTH	ER DATA		
TYPE OF SUBMISSION		TYPE OF ACTION					
Notice of Intent	Deepen	Production (Start/	Resume)	=	ater Shut-Off		
- Alter Casing	Fracture Treat	Reclamation		_	ell Integrity		
☑ Subsequent Report ☐ Casing Repair ☐	New Construction	= '		√ 0	ther Spud & Intermediate		
Change Plans Final Abandonment Notice Convert to Injection	Plug and Abando		ndon	_			
Final Abandonment Notice Convert to Injection	Plug Back	Water Disposal					
Cement with 200 sx Class B + 2% CaCl2 + 1/4 #/sk cellophane for Pressure test BOPE and Casing to 2000 psi for 30 minutes - ok. Drill 8 3/4" hole to 4185'. Ran 102 jts 7" 20# J-55 STC csg, 4173 Cemented as follows: Stage 1: 190 sks (392 cf) 35/65 POZ/G + 6% Gel + 5 lbs/sk Gilso (184 cf) class G + 5 lbs/sk Gilsonite + 1/8 lb/sk Pol-E-Flake+ 3% Stage 2: 272 sks (510 cf) 35/65 POZ/G + 6% Gel + 10 lbs/sk Gilsonite + 1/8 lb/sk Gilsonite + 1/	s' set at 4185', Floa onite + 1/8 lb/sk P o KCL mixed at 15	at collar at 4139' KB and I ol-E-Flake + 3% KCL mi 5.2 ppg, yield 1.269 cf/sk.	OV at 2072' I xed at 12.1 p Circ 20 bbl o	ζB. pg, yie cmt off			
sks (63 cf) class G + 5 lbs/sk Gilsonite+ 1/8 lbs/sk Pol-E-Flake + Presssure test: BOPE & casing to 2000 psi - ok.	3% KCL mixed a	Pol-E-Flake + 3% KCL n t 15.2 ppg, yield 1.269 cf	nixed at 12.5 /sk. Circ 10 b	bl cmt	of DV to Surf. Jarield 1.877 cf/sk & 50 to surf. J		
Presssure test: BOPE & casing to 2000 psi - ok.	3% KCL mixed a	Pol-E-Flake + 3% KCL n t 15.2 ppg, yield 1.269 cf	nixed at 12.5 /sk. Circ 10 b	bl cmt	of DV to Surf. J rield 1.877 cf/sk & 50 to surf. J		
Presssure test: BOPE & casing to 2000 psi - ok.	3% KCL mixed a	Pol-E-Flake + 3% KCL n t 15.2 ppg, yield 1.269 cf	nixed at 12.5 /sk. Circ 10 t	bl cmt	of DV to Surf. Jarield 1.877 cf/sk & 50 to surf. J		
Presssure test: BOPE & casing to 2000 psi - ok. 30 min - par operal	3% KCL mixed a	Pol-E-Flake + 3% KCL n t 15.2 ppg, yield 1.269 cf	nixed at 12.5 /sk. Circ 10 t	bl cmt	Tof DV to Surf. I vield 1.877 cf/sk & 50 to surf. I vield 1.877 cf/sk & 50 to surf. I vield 1.879 cf/sk & 50		
Presssure test: BOPE & casing to 2000 psi - ok. 30 min - par operal	3% KCL mixed a	Pol-E-Flake + 3% KCL n t 15.2 ppg, yield 1.269 cf	nixed at 12.5 /sk. Circ 10 t	bl cmt	of DV to Surf. I vield 1.877 cf/sk & 50 to surf. I		
Presssure test: BOPE & casing to 2000 psi - ok. 30 min - par operat 14 1 hereby certify that the foregoing is true and correct	3% KCL mixed a	Pol-E-Flake + 3% KCL nt 15.2 ppg, yield 1.269 cf	/sk. Circ 10 t	RC OI	of DV to Surf. I vield 1.877 cf/sk & 50 to surf. I vield 1.877 cf/sk & 50 to surf. I vield 1.879 cf/sk & 50		
Presssure test: BOPE & casing to 2000 psi - ok. 30 min - par operat 14 1 hereby certify that the foregoing is true and correct Name (PrintedlTyped)	3% KCL mixed a	t 15.2 ppg, yield 1.269 cf	/sk. Circ 10 t	RC OI	of DV to Surf. J rield 1.877 cf/sk & 50 to surf. J UD FEB 4'09 L CONS. DIV.		
Presssure test: BOPE & casing to 2000 psi - ok. 30 min - par operation 14 I hereby certify that the foregoing is true and correct Name (PrintedlTyped) Daneda A. Gonzales Signature Add A. Amadus	Title	t 15.2 ppg, yield 1.269 cf	ounting Tech	RC OI	of DV to Surf. J rield 1.877 cf/sk & 50 to surf. J UD FEB 4'09 L CONS. DIV.		
Presssure test: BOPE & casing to 2000 psi - ok. 30 min - par operation 14 I hereby certify that the foregoing is true and correct Name (PrintedlTyped) Daneda A. Gonzales Signature Add A. Amadus	Title	JAECO Production/Acco	ounting Tech	RC OI	of DV to Surf. J rield 1.877 cf/sk & 50 to surf. J UD FEB 4'09 L CONS. DIV.		

(Continued on next page)

NMOCD %

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FEB 0 4 2000