UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

NOV 1 8 2008

FORM APPROVED OMB No 1004-0135 Expires: January 31, 2004

SUNDRY NOTICES AND REPORTS ON WELLS	*3
Do not use this form for proposals to drill or to re-enter an	.~മി
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals:	100

	I MOLICES WAD KELOU			3011	MDA 701-04-0014				
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals!					6. If Indian, Allottee or Tribe Name				
					Jicarilla A	pache	Nation		
SUBMIT IN TR	IPLICATE - Other instruc	ctions on reve	se side	2	7. If Unit or	CA/Ag	reement, Name and/or No.		
1. Type of Well									
Oil Well Gas Well Other						8. Well Name and No.			
2. Name of Operator						Apache JVA #5A			
Jicarilla Apache Energy Corp						9. API Well No.			
			lude area co	ode)	30-039-30515 <				
P.O. Box 710 Dulce, New M	levico 87528	575-759-3224			10. Field and	0. Field and Pool, or Exploratory Area			
P.O. Box 710 Dulce, New Mexico 87528 575-759-3224 4 Location of Well (Footage, Sec., T, R., M., or Survey Description)					Blanco Mesa Verde				
660' FSL & 1052' FEL, Sec 29, T27N, R2W					11. County or Parish, State				
					Rio Arriba, New Mexico				
12. CHECK API	PROPRIATE BOX(ES) TO	INDICATE NAT	URE OF	NOTICE, REP					
TYPE OF SUBMISSION	ACTION								
	Acidize [Deepen		Production (Start/Re	esume)	□ w	ater Shut-Off		
Notice of Intent	Alter Casing	Fracture Treat		Reclamation	,	Ξw	ell Integrity		
□ 2.1	Casing Repair	New Constructio		Recomplete		_	ther Spud & Intermediate		
✓ Subsequent Report	Change Plans	Plug and Abando	=	Temporarily Aband	lon				
Final Abandonment Notice	= '	Plug Back		Water Disposal		_			
Spud 12 1/4" Hole at 9:00 am, 6 Cement with 200sx Class B + 2' Pressure test BOPE and Casing Drill 8 3/4" hole to 3990'. Ran 9 Cemented as follows: Stage 1: 155 sks (322 cf) 35/65 I (184 cf) class G + 5 lbs/sk Gilso Stage 2: 290 sks (544 cf) 35/65 F sks (63 cf) class G + 5 lbs/sk Gilso Presssure test: BOPE & casing to	% CaCl2 + 1/4 #/sk cellophane to 2000 psi for 30 minutes - ok. 9 jts 7" 20# J-55 STC csg, 3973 POZ/G + 6% Gel + 5 lbs/sk Gil nite + 1/8 lb/sk Poly-E-Flake+; POZ/G + 6% Gel + 10 lbs/sk Gil lsonite+ 1/8 lbs/sk Poly-E-Flake	flake mixed at 15.2 J 3' set at 3985' KB, F sonite + 1/8 lb/sk P 3% KCL mixed at Isonite + 1/8 lbs/sk e + 3% KCL mixed	#/gal yield loat collar oly-E-Flak 15.2 ppg, y Poly-E-Flak	1 1.18. Circulated at 3941' KB and e + 3% KCL mix ield 1.269 cf/sk. wake + 3% KCL m	DV at 2051 ed at 12.1 p Circ 5 bbl c ixed at 12.5	YKB. opg, yi mt off opgs, bbl cm	eld 2.076 cf/sk & 145 sks of DV to Surf. √ yield 1.877 cf/sk & 50		
14. 1 hereby certify that the foregoin	g is true and correct					·			
Name (PrintedlTyped)		Title							
Daneda A. Gonzales		Title	Title JAECO Production/Accounting Technician						
Signature Danida	A. Amzales	Date	Novembe	r 10, 2008					
	THIS SPACE FO	OR FEDERAL OR	STATE	OFFICE USE					
Approved by (Signature)			Name (Printed/Typed) Title						
Conditions of approval, if any, are certify that the applicant holds legs which would entitle the applicant to determine the appl	attached. Approval of this notice all or equitable title to those rights conduct operations thereon.	does not warrant or in the subject lease	Office	***************************************			Date		

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

| ACCEPTED FOR RECORD |

FEB 0 4 2009