Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

		J. C.		J 1	D. 11 11	1411 11 4	I I O DIVI				
)R	Υı	TON	ICE	ES	AND	REP	ORTS	ON	WEL	LS	

SUND Do not use this form for proposals to drill or to re-enter an FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

5. Lease Serial No. NMSF078204

_				
5.	If Indian,	Allottee or	Tribe Name	

abandoned we	6. If Indian, Allottee	6. If Indian, Allottee or Tribe Name				
SUBMIT IN TR	IPLICATE - Other instruction	ns on reverse side.	7. If Unit or CA/Agr	reement, Name and/or No.		
1. Type of Well	thor		8. Well Name and N SUNRAY D 2B	8. Well Name and No. SUNRAY D 2B		
Oil Well Gas Well O Name of Operator BURLINGTON RESOURCES	Contact: PE	GGY COLE fail: pcole@br-inc.com				
3a. Address		o. Phone No. (include area code				
3401 EAST 30TH FARMINGTON, NM 87499	P	h: 505.326.9727 x: 505.326.9781	BASIN DAKO MESAVERDE	10. Field and Pool, or Exploratory BASIN DAKOTA MESAVERDE POINT LOOKOUT		
4. Location of Well (Footage, Sec.,				11. County or Parish, and State		
Sec 21 T30N R10W NWSE	1450FSL 1850FEL		SAN JUAN CO	DUNTY, NM		
12. CHECK API	PROPRIATE BOX(ES) TO IN	NDICATE NATURE OF	NOTICE, REPORT, OR OTH	ER DATA		
TYPE OF SUBMISSION TYPE OF ACTION						
Notice of Intent	Acidize	Deepen	☐ Production (Start/Resume)	☐ Water Shut-Off		
	☐ Alter Casing	☐ Fracture Treat	☐ Reclamation	☐ Well Integrity		
Subsequent Report	☐ Casing Repair	☐ New Construction	Recomplete	Other		
☐ Final Abandonment Notice	☐ Change Plans	☐ Plug and Abandon	☐ Temporarily Abandon	Change to Original A PD		
	Convert to Injection	Plug Back	☐ Water Disposal			
testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) It is intended to alter the approved surface casing and cement program for the subject well as follows: Hole size: 12 1/4" Depth interval: 0-120' Casing size: 9 5/8" Weight: 32.3# Grade: H-40 9 5/8" surface casing - cement with 32 sacks Class A, B Portland Type I, II cement (48 cu.ft of slurry, bring cement to surface through 3/4" line) or equivalent. Wait on cement 24 hours for pre-set holes or 8 hours for conventionally set holes before pressure testing or drilling out from under surface casing.						
14. I hereby certify that the foregoing	Electronic Submission #172	256 verified by the BLM We	Il Information System			
	ommitted to AFMSS for process	sing by Adrienne Garcia on	01/07/2003 (03AXG0509SE)			
Name (Printed/Typed) PEGGY	COLE	Title REGU	LATORY ADMINISTRATOR			
Signature (Electronic	Submission)	Date 01/02/2	2003			
	THIS SPACE FOR	FEDERAL OR STATE	OFFICE USE			
Approved By /s/ Jim Lov	ato	Title Retr. A	Eng.	JAN - 8 200 Date		
Conditions of approval, if any, are attact certify that the applicant holds legal or e which would entitle the applicant to con	quitable title to those rights in the su	t warrant or bject lease Office BLA	1-500			
Title 18 U.S.C. Section 1001 and Title 4 States any false, fictitious or frauduler	3 U.S.C. Section 1212, make it a cri	me for any person knowingly ar	nd willfully to make to any department	or agency of the United		