

RECEIVED

In Lieu of
Form 3160
(June 1990)

UNITED STATES
DEPARTMENT OF INTERIOR
BUREAU OF LAND MANAGEMENT
Bureau of Land Management
Farmington Field Office

FEB 23 2009

FORM APPROVED
Budget Bureau No 1004-0135
Expires March 31, 1993

SUNDRY NOTICE AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir Use "APPLICATION TO DRILL" for permit for such proposals

SUBMIT IN TRIPLICATE		5	Lease Designation and Serial No 701-02-0014
		6.	If Indian, Allottee or Tribe Name Jicarilla Apache Nation
		7	If Unit or CA, Agreement Designation
1	Type of Well Oil Well Gas Well X Other	8.	Well Name and No JAECO 26-3 22 #2A
2	Name of Operator WILLIAMS PRODUCTION COMPANY	9	API Well No 30-039-30051
3.	Address and Telephone No PO BOX 640 Aztec, NM 87410-0640	10	Field and Pool, or Exploratory Area Blanco MV
4	Location of Well (Footage, Sec., T., R , M , or Survey Description) 790' FSL & 900' FWL, Sec. 22, T26N, R3W	11.	County or Parish, State Rio Arriba, NM


CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
Notice of Intent	Abandonment
KR x Subsequent Report	Recompletion
	Plugging Back
	Casing Repair
Final Abandonment	Altering Casing
	X Other <u>SURFACE CASING</u>
	Change of Plans
	New Construction
	Non-Routine Fracturing
	Water Shut-Off
	Conversion to Injection
	Dispose Water
	(Note. Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/20/09- TD 12/ 1/4" SURF HOLE @ 350', 1230 HRS
RAN 7 JTS, 9 5/8", 36#, K-55, LT&C, 8rd, CSG SET @ 343'
CEMENT 9 5/8" SURF, PRESS TEST 1500#, 10 Bbl FW SPACER, 230sx (49 Bbl Slurry, 276cuft) PREMIUM CLASS " G "
Cement + 2% CaCl2 + 1/4#/sk Poly-E-Flake + 5.238 wgps (Wt = 15.6ppg, Yield = 1.2cuft/sk) Drop Plug & Displace W/
23 Bbl FW, Final Press 127#, Bump Plug to 1027#, Check Float - OK. Plug Down @ 6:05pm. 2/20/2009. Full Returns Entire Job,
Circ 15 Bbl (70sx) Good Cement to Pit. RIG DN & RELEASE HOWSCO. (CMT JOB WITNESSED BY ROD VELARDE, AO&GC) ✓

2/21/09- INSTALL TEST PLUG & PRESS TEST BLIND RAMS, PIPE RAMS, CHOKE LINE VALVES, CHOKE MANIFOLD VALVES, KILL
LINE VALVES, KELLYCOCK VALVE & FLOOR VALVE 250# LOW-5 MIN EACH, 1500# HIGH-10 MIN EACH
PRESS TESTING, TEST PLUG, TEST PUMP & CHARTS USED, GOOD TESTS. PULL TEST PLUG & TEST 9.625" CASING & BLIND
RAMS @ 1500# 30 MIN, GOOD. TEST PUMP & CHART USED. ✓



14. I hereby certify that the foregoing is true and correct

Signed Larry Higgins
Larry Higgins

Title Drilling COM

Date 2/23/09

RCVD MAR 2 '09
OIL CONS. DIV.
DIST. 3

(This space for Federal or State office use)

Approved by _____

Title _____

Date _____

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCB