Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT •

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

	Expires			
_		 -		

SUNDRY NOTICES AND REPORTS ON WELLS					NMSF078543		
Do not use this form for abandoned well. Use For	6. If Indian, Allottee or Tribe Name 52						
SUBMIT IN TRIPLICATE -	Other instructions	s on reverse side	armington,	7. If Unit or CA/	Agreement, Name and/or		
1. Type of Well Oil Well X Gas Well Other				8. Well Name and	1 No.		
2. Name of Operator					61 00 7 11 11 110111		
ConocoPhillips Company					SJ 32-7 Unit #211A 9. API Well No.		
3a. Address 3b. Phone No. (inelule area code)				30-045-31802			
5525 Highway 64, NBU 3004, Farmingt 4. Location of Well (Footage, Sec., T., R., M., or Survey)		505-599-345472	9 ====	10. Field and Poo	l, or Exploratory Area		
Unit C (NENW), 785' FNL 7 1575' FWL Section 35, T32N, R7W			Basin Fruitland Coal 11. County or Parish, State				
, , , , , , , , , , , , , , , , , , ,		(E)	`	San Juan,	NM		
12. CHECK APPROPRIATE	BOX(ES) TO INI	DICATE NATURE OF N	OTIČE, REP				
TYPE OF SUBMISSION			E OF ACTION				
THE OF CODMISCION							
Notice of Intent	Acidize	Deepen	Production	ı (Start/Resume)	Water Shut-Off		
□	Alter Casing	Fracture Treat	Reclamation	on [Well Integrity		
X Subsequent Report	Casing Repair	New Construction	Recomple	te X	Other		
Final Abandonment Notice	Change Plans	Plug and Abandon	Temporari	ly Abandon 7	casing report		
T man resulted means restrict	Convert to Injecti	on Plug Back	Water Disp	posal	00011119_1 00001 0		
following completion of the involved operations. It testing has been completed. Final Abandonment I determined that the final site is ready for final inspection. 9/21/03 RIH w/8-3/4" bit & tagged hole. RIH w/7", 20#, J-55 casing bbls water w/dye in last 10 bbls. Econo-lite, 0.25#/sx Cello-flake, 50/50 POZ, 2% Bentonite, 2% CaCl2 and displaced w/130 bbls water. good cement to surface. ND BOP, casing PT on next report.	cement @ 210'. and set @ 3258 Pumped Lead - 0.2% Anti-foam , 0.25#/sx Cell Bumped plug w/1	Drilled cement and '. RU Schlumberger 424 sx (1106 cf Tail - 100 sx (1:00-flake, 5#/sx Gilson 300 psi. Plug down	d then form to cement. 196.97 bbl 27 cf - 22. onite, 0.2% @ 1741 hrs	nation to 3258 Pumped a pr slurry) Class 61 bbl slurry Antifoam. [5 9/24/03. Ci	eted, and the operator hat ceflush of 30 G, 5% Class G, cropped plug rc. 50 bbls		
				NMOCE)		
14. I hereby certify that the foregoing is true and correct Name (Printed Typed)		Title					
-(A)	Patsy Clugston		SHEAR Adm	inistrative As			
Talsy Mich		Date 10)/2/03	ACCEPTED	FOR RECORL		
THIS	SPACE FOR FED	ERAL OR STATE OFF	ICE USE		0 2000		
Approved by		Title		Date	3 2003		
Conditions of approval if any are attached Approval of	f this notice does not w	arrant or one			N FIELD OFFICE		
Conditions of approval, if any, are attached. Approval o certify that the applicant holds legal or equitable title to	those rights in the sub	arrant or Office		BA A			

which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.