#### District I

1625 N French Dr , Hobbs, NM 88240

District II

1301 W Grand Ave, Artesia, NM 88210

District III

1000 Rio Brazos Rd, Aztec, NM 87410

District IV

1220 S St Francis Dr , Santa Fe, NM 87505

## State of New Mexico **Energy Minerals and Natural Resources**

Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

July 21, 2008

Form C-144

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office

# Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action:	Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Modification to an existing permit
	Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the

perator: ConocoPhillips Company	OGRID#: 217817
ddress: PO Box 4289, Farmington, NM 87499	
cility or well name: San Juan 28-7 Unit 234P	
PI Number: 30-039-0000 30642 OCD Permit Nu	umber.
L or Qtr/Qtr: G(SW/NE) Section: 15 Township: 28N Range:	7W County: Rio Arriba
enter of Proposed Design: Latitude: 36.662766' N Longitude:	<b>107.558667' W</b> NAD: 1927 X 1983
urface Owner: Federal State X Private Tribal Trust or In	ndian Allotment
	- LILARUS
X Pit: Subsection F or G of 19 15.17.11 NMAC	\$
Temporary: X Drilling Workover	
Permanent Emergency X Cavitation P&A	
	HDPE PVC Other
X String-Reinforced	
Liner Seams X Welded X Factory Other Volume 7	7700 bbl Dimensions L 120' x W 55' x D 12'
Closed-loop System: Subsection H of 19.15.17.11 NMAC  Type of Operation: P&A Drilling a new well Workover or Drilling (Applie notice of intent)  Drying Pad Above Ground Steel Tanks Haul-off Bins Other  Lined Unlined Liner type: Thickness mil LLDPE  Liner Seams: Welded Factory Other	
X Below-grade tank: Subsection I of 19 15 17.11 NMAC	A RECENTED
Volume: 120 bbl Type of fluid: Produced Water	- CONS. DIV. DIS
Tank Construction material. Metal	automatic overflow shut-off
Secondary containment with leak detection X Visible sidewalls, liner, 6-inch lift and	automatic overflow shut-off OIL CO.
<b>=</b>	262728295
Visible sidewalls and liner Visible sidewalls only Other	LLDPE
Visible sidewalls and liner Visible sidewalls only Other  Liner Type: Thickness 45 mil HDPE PVC X Other	LLDFE

Fencing: Subsection D of 19 15.17 11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)  Four foot height, four strands of barbed wire evenly spaced between one and four feet  X Alternate. Please specify 4' hogwire fence with a single strand of barbed wire on top.			
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  X Screen Netting Other  Monthly inspections (If netting or screening is not physically feasible)			
Signs: Subsection C of 19.15 17.11 NMAC  12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  X Signed in compliance with 19.15.3.103 NMAC			
Administrative Approvals and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  X Administrative approval(s) Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration of approval.  (Fencing/BGT Liner)  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.			
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.			
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	XNo	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes	XNo	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  (Applies to temporary, emergency, or cavitation puts and below-grade tanks)	Yes NA	XNo	
<ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> <li>Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.</li> <li>(Applied to permanent pits)</li> </ul>	Yes XNA	No	
<ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> <li>Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.</li> </ul>	Yes	XNo	
<ul> <li>NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.</li> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended</li> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> </ul>	Yes	XNo	
<ul> <li>Within 500 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> <li>Within the area overlying a subsurface mine.</li> <li>Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division</li> </ul>	☐ Yes ☐ Yes	X No	
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society; Topographic map  Within a 100-year floodplain  - FEMA map	Yes Yes	X No X No	

Form C-144 Oil Conservation Division Page 2 of 5

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19 15.17 9 NMAC			
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.			
X Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15 17.9 NMAC  X Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15 17.9			
X Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC			
X Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC			
X   Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC			
X   Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of			
19.15.17.9 NMAC and 19.15.17.13 NMAC			
Previously Approved Design (attach copy of design)  API or Permit			
12 Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC			
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.			
Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19 15.17 9			
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC			
Design Plan - based upon the appropriate requirements of 19.15 17.11 NMAC			
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC			
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9  NMAC and 19.15 17.13 NMAC			
Previously Approved Design (attach copy of design)  API			
Previously Approved Operating and Maintenance Plan API			
13			
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC			
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.			
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC			
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC			
Climatological Factors Assessment  Certified Engineering Design Plans - based upon the appropriate requirements of 19 15.17.11 NMAC			
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19 15.17.11 NMAC			
Leak Detection Design - based upon the appropriate requirements of 19.15 17.11 NMAC			
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC			
Quality Control/Quality Assurance Construction and Installation Plan			
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC			
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15 17.11 NMAC  Nuisance or Hazardous Odors, including H2S, Prevention Plan			
Emergency Response Plan			
Oil Field Waste Stream Characterization			
Monitoring and Inspection Plan			
Erosion Control Plan			
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC			
14			
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.			
Type: X Drilling Workover Emergency X Cavitation P&A Permanent Pit X Below-grade Tank Closed-loop System  Alternative			
Proposed Closure Method: X Waste Excavation and Removal (Below-Grade Tank)			
Waste Removal (Closed-loop systems only)			
X On-site Closure Method (only for temporary pits and closed-loop systems)			
X In-place Burial On-site Trench			
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)			
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.			
Please indicate, by a check mark in the box, that the documents are attached.  [X] Posts and Proceedings the composition requirements of 10.15.17.13 NIMAC.			
X   Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC			
X   Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC   X   Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)			
X   Disposar Facility Name and Permit Number (for Induces, artifling Italias and drift cuttings)   X   Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC			
X  Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC			
X Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC			

Form C-144 Oil Conscivation Division Page 3 of 5

Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19.15.17 13.D NMAC) Instructions Please identify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if more than two facilities are required.  Disposal Facility Name:  Disposal Facility Permit #:  Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will not be used for future service and operations?  Yes (If yes, please provide the information No  Required for impacted areas which will not be used for future service and operations:  Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC  Instructions Each string criteria requires a demonstration of compliance in the closure plan Recommendations of acceptable source material are provided below Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office			
Disposal Facility Name:  Disposal Facility Permit #:  Disposal Facility Permit #:  Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will not be used for future service and operations?  Yes (If yes, please provide the information No  Required for impacted areas which will not be used for future service and operations:  Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC			
Disposal Facility Name:    Disposal Facility Permit #:			
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will not be used for future service and operations?    Yes (If yes, please provide the information   No   No			
Yes (If yes, please provide the information No  Required for impacted areas which will not be used for future service and operations:  Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC  17  Siting Criteria (Regarding on-site closure methods only: 19.15.17.10 NMAC  Instructions Each siting criteria requires a demonstration of compliance in the closure plan Recommendations of acceptable source material are provided below Requests regarding changes to			
Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC  17  Siting Criteria (Regarding on-site closure methods only: 19.15.17.10 NMAC  Instructions Each siting criteria requires a demonstration of compliance in the closure plan Recommendations of acceptable source material are provided below Requests regarding changes to			
Site Reclamation Plan - based upon the appropraite requirements of Subsection G of 19.15.17.13 NMAC  17  Siting Criteria (Regarding on-site closure methods only: 19.15.17.10 NMAC  Instructions Each siting criteria requires a demonstration of compliance in the closure plan Recommendations of acceptable source material are provided below Requests regarding changes to			
Siting Criteria (Regarding on-site closure methods only: 19.15.17.10 NMAC  Instructions Each siting criteria requires a demonstration of compliance in the closure plan Recommendations of acceptable source material are provided below Requests regarding changes to			
Siting Criteria (Regarding on-site closure methods only: 19.15.17.10 NMAC  Instructions Each siting criteria requires a demonstration of compliance in the closure plan Recommendations of acceptable source material are provided below Requests regarding changes to			
for consideration of approval Justifications and/or demonstrations of equivalency are required Please refer to 19 15 17 10 NMAC for guidance			
Ground water is less than 50 feet below the bottom of the buried waste			
- NM Office of the State Engineer - iWATERS database search; USGS: Data obtained from nearby wells			
Ground water is between 50 and 100 feet below the bottom of the buried waste			
- NM Office of the State Engineer - tWATERS database search; USGS; Data obtained from nearby wells			
Ground water is more than 100 feet below the bottom of the buried waste.			
- NM Office of the State Engineer - tWATERS database search; USGS; Data obtained from nearby wells			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).			
- Topographic map; Visual inspection (certification) of the proposed site			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; satellite image			
Yes X No			
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existence at the time of the initial application.  - NM Office of the State Engineer - iWATERS database, Visual inspection (certification) of the proposed site			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.			
- Written confirmation or verification from the municipality, Written approval obtained from the municipality			
Within 500 feet of a wetland  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site			
Within the area overlying a subsurface mine.			
- Written confirantion or verification or map from the NM EMNRD-Mining and Mineral Division			
Within an unstable area.			
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map			
Within a 100-year floodplain FEMA map			
18			
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.			
X Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15.17.10 NMAC			
X Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC			
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC			
X Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC			
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15.17.13 NMAC			
X Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15 17 13 NMAC			
X Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)			
V Sail Cover Design hased upon the appropriate requirements of Subsection U of 10.15.17.12 NMAC			
<ul> <li>Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC</li> <li>Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15 17 13 NMAC</li> </ul>			

Form C-144 Oil Conservation Division Page 4 of 5

19 Operator Application Certification:			
I hereby certify that the information submitted with this applic	ation is true, accurate and complete to th	e best of my knowledge and belief.	
Name (Print):	Title:	Staff Regulatory Technician	
Signature: Tampoessi	Date.	2-10-09	
e-mail address: sessitd@conocophillips.	com Telephone:	505-326-9834	
20 OCD Approval: Permit Application (including close)	sure plan) Closure Plan (only	OCD Conditions (see attachment)	
OCD Representative Signature:	1 sell	Approval Date: 4-14	-09
Title: Enviro /spec	OCD Per	mit Number:	
21			
Closure Report (required within 60 days of closure co	ompletion): Subsection K of 19 15 17 13 NMA	AC	
Instructions: Operators are required to obtain an approved cle	osure plan prior to implementing any clo	sure activities and submitting the closure report.	
report is required to be submitted to the division within 60 day approved closure plan has been obtained and the closure activ	• •	es. Please do not complete this section of the fori	n until an
-		re Completion Date:	
Amana (1990)			
22 Closure Method:			
	losure Method Alternative Closur	e Method Waste Removal (Closed-loop sys	stems only)
If different from approved plan, please explain.	_ <del></del>	<del></del>	
23	· · ·		
Closure Report Regarding Waste Removal Closure For Clo			
Instructions: Please identify the facility or facilities for when were utilized.	e the liquids, drilling fluids and drill cut	tings were disposed. Use attachment if more tha	n two facilities
Disposal Facility Name.	Disposal Facili	y Permit Number:	
Disposal Facility Name		y Permit Number:	
Were the closed-loop system operations and associated acti	vities performed on or in areas that will i	not be used for future service and opeartions?	
Yes (If yes, please demonstrate complilane to the item	s below) No		
Required for impacted areas which will not be used for futi	ire service and operations:		
Site Reclamation (Photo Documentation)  Soil Backfilling and Cover Installation			
Re-vegetation Application Rates and Seeding Techniq	ue		
24			
Closure Report Attachment Checklist: Instructions.	: Each of the following items must be at	tached to the closure report. Please indicate, by	a check mark in
the box, that the documents are attached.	,		
Proof of Closure Notice (surface owner and divisi Proof of Deed Notice (required for on-site closure			
Plot Plan (for on-site closures and temporary pits)			
Confirmation Sampling Analytical Results (if app			
Waste Material Sampling Analytical Results (if ap			
Disposal Facility Name and Permit Number	• '	•	
Soil Backfilling and Cover Installation			
Re-vegetation Application Rates and Seeding Tec	hnique		
Site Reclamation (Photo Documentation)			
On-site Closure Location: Latitude:	Longitude:	NAD 1927	1983
25 Operator Clasure Certification			
Operator Closure Certification:  I hereby certify that the information and attachments submitte	d with this closure report is ture, accura	e and complete to the best of my knowledge and b	pelief I also certify that
the closure complies with all applicable closure requirements		•	, <u>,</u> ,,
Name (Print):	Title:		
Signature:	Date:		
e-mail address:	Telephone:		

Form C-144

# ConocoPhillips Company San Juan Basin Closure Plan

In accordance with Rule 19.15.17.12 NMAC the following information describes the closure requirements of temporary pits on ConocoPhillips Company (COPC) locations. This is COPC's standard procedure for all temporary pits. A separate plan will be submitted for any temporary pit which does not conform to this plan.

All closure activities will include proper documentation and be available for review upon request and will be submitted to OCD within 60 days of closure of pit closure. Closure report will be filed on C-144 and incorporate the following:

- Details on Capping and Covering, where applicable.
- Plot Plan (Pit Diagram)
- Inspection Reports
- Sampling Results
- C-105
- · Copy of Deed Notice will be filed with County Clerk

### **General Plan:**

- All free standing liquids will be removed at the start of the pit closure process from the pit and disposed of in a division-approved facility or recycle, reuse or reclaim the liquids in a manner that the appropriate division district office approves. The facilities to be used will be Basin Disposal (Permit #NM-01-005) and Envirotech Land Farm (Permit #NM-01-011)
- 2. The preferred method of closure for all temporary pits will be on-site burial, assuming that all the criteria listed in sub-section (B) of 19.15.17.13 are met.
- 3. The surface owner shall be notified of COPC's closing of the temporary pit prior to closure as per the approved closure plan via certified mail, return receipt requested.
- 4. Within 6 months of the Rig Off status occurring COPC will ensure that temporary pits are closed, re-contoured, and reseeded.
- 5. Notice of Closure will be given prior to the Aztec Division office between 72 hours and one week via email, or verbally. The notification of closure will include the following:
  - i. Operator's name
  - ii. Location by Unit Letter, Section, Township, and Range. Well name and API number.
- 6. Liner of temporary pit shall be removed above "mud level" after stabilization. Removal of liner will consist of manually or mechanically cutting liner at mud level and removing all remaining liner. Care will be taken to remove "All" of the liner i.e., edges of liner entrenched or buried. All excessive liner will be disposed of at the San Juan County Landfill located on CR 3100.
- 7. Pit contents shall be mixed with non-waste containing, earthen material in order to achieve the solidification process. The solidification process will be accomplished using a combination of natural drying and mechanically mixing. Pit contents will be mixed with non-waste, earthen material to a consistency that is deemed a safe and stable. The mixing ratio shall not exceed 3 parts clean soil to 1 part pit contents.
- 8. A five point composite sample will be taken of the pit using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	1000/500

ŧ

9. A five point composite sample will be taken from the cavitation pit pursuant to 19.15.17.13(B)(1)(b)(i) in order to assure there has not been any type of release.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

- 10. Upon completion of solidification and testing standards being passed, the pit area will be backfilled with compacted, non-waste containing, earthen material. A minimum of four feet of cover shall be achieved and the cover shall include one foot of suitable material to establish vegetation at the site, or the background thickness of topsoil, whichever is greater. If standard testing fails COPC will dig and haul all contents pursuant to 19.15.17.13.i.a. After doing such, confirmation sampling will be conducted to ensure a release has not occurred.
- 11. During the stabilization process if the liner is ripped by equipment the Aztec OCD office will be notified within 48 hours and the liner will be repaired if possible. If the liner can not be repaired then all contents will be excavated and removed.
- 12. Dig and Haul Material will be transported to the Envirotech Land Farm located 16 miles south of Bloomfield on Angel Peak Road, CR 7175. Permit # NM010011
- 13. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 14. Notification will be sent to OCD when the reclaimed area is seeded.
- 15. COPC shall seed the disturbed areas the first growing season after the operator closes the pit. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality)

Purity

Source No. two (better quality)

5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS 1 lb. PLS

16. The temporary pit will be located with a steel marker, no less than four inches in diameter, cemented in a hole three feet deep in the center of the onsite burial upon the abandonment of all the wells on the pad. The marker will be flush with the ground to allow access of the active well pad and for safety concerns. The marker will include a threaded collar to be used for future abandonment. The top of the marker will contain a welded steel 12" square plate that indicates the onsite burial of the temporary pit. The plate will be easily removable and a four foot tall riser will be threaded into the top of the collar marker and welded around the base with the operator's information at the time of all wells on the pad are abandoned. The operator's information will include the following: Operator Name, Lease Name, Well Name and number, Unit Number, Section, Township, Range and an indicator that the marker is an onsite burial location.