## RECEIVED

submitted in lieu of Form 3160-5

Ve

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

AMENDED REPORT

APR 03 2009

Sundry Notices and Reports on Wells				Bureau of Land Management Farmington Field Office
			5.	Lease Number USA NM-013657
1. <b>Type of Well</b> GAS			6.	If Indian, All. or Tribe Name
2. Name of Operator  BURLINGTON  DECOMPOSED ON A GAS COMPANYAR			7.	Unit Agreement Name San Juan 28-6 Unit
RESCURCES OIL & GAS COMPANY LP  3. Address & Phone No. of Operator			- 8.	Well Name & Number San Juan 28-6 Unit 114N
PO Box 4289, Farmington, NM 87499 (505) 326-9700			9.	API Well No.
Unit H (SE/NE), 2085' FNL & 660' FEL, Section 25, T28N, R6W, NMPM			<del>-</del>	30-039-30539
			10.	Field and Pool Basin DK/Blanco MV
			11.	County and State Rio Arriba, NM
12. CHECK APPROPRIATE BOX		RE OF NOTICE, REPORT, O	THER	DATA
/ Type of Submission Type Notice of Intent	e of Action Abandonment	Change of Plans	x	Other – casing report
	Recompletion	New Construction		RCVD APR 15'09
Subsequent Report	Plugging .  Casing Repair	Non-Routine Fracturing Water Shut off		OIL CONS. DIV.
Final Abandonment	Altering Casing	Conversion to Injection		DIST. 3
13. Describe Proposed or Complet 3/18/08 MIRU H&P #281. NU BOP. 3/drilled ahead to 3720' reached 3/21/09. Cement. Pumped preflush of 10 bbls FW bbls) Type III w/1% CaCl2 & .25#/sx Ce#. Plug down @ 0540 hrs 3/22/09. Oper stage - Pumped preflush of 10 bbls FW & Premium Lite w/3% CaCl2, .25#/sx Cell 2525#. Plug down @ 1722 hrs, No ceme 3/24/09 to proceed). 8/24/09 D/O DV to Perforated @ 2436 to 24 37' - 4 holes. Pbbls) Class H cement. Dropped plug and Survey and find the TOC. 3/25/09 Tem TOC @ least 1325' which it was.	19/09 PT casing to 600#/30 m Circ. hole. 3/22/09 RIH w/87 ½ 10 bbls mud clean. 1st Statello-flake & 0.2% FL-52. Dromed stage tool & circ. 10 bbls & 10 bbls of gel. Pumped 19 oflake, 5#/sx LCM, .4% FL52 ent to surface. (See NOI date to land Circ. hole clean. Ranumped 18 bbls water ahead of displaced w/38 bbls FW. N	I jts 7", 20# J-55 casing and set @ 37 age - Pumped 19 sx (56 cf - 10 bbls) opped plug and displace w/40 bbls F circulated then lost circulation. Pusx (57 cf - 10 bbls) Scavanger ahead 2, 0.4% SMS. Dropped plug and disped 3/25/09 where verbal approval of CBL from 3670' - surface. TOC @ of Lead 278 sx (592 cf - 105 bbls) Claw cement to surface. Received perm	20' w/sta Scaveng W & 110 mped LC of Lead placed w was rece 2526' (n ass A cer nission fr	age tool set @ 3005'. RU to er, Tailed w/157 sx (169 cf - 30) bbls mud. Bumped plug to 1126 M to try to heal. RU to pump 2 <sup>nd</sup> - 337 sx (712 cf - 128 bbls) v/120 bbls water. Bumped plug to ived from BLM & OCD on ot at the required TOC @ 1325'). ment. Tailed w/88 sx (121 cf-22 om BLM & OCD to run Temp
3/25/09 RIH w/6-1/4" bit & tagged ceme (TD). TD reached 3/28/09. Circ. hole. Pumped 10 bbls CW, 2 bbls FW, 9 sx (2) displaced w/125.8 bbls FW. Bumped p conducted by the completion rig and rest 14. I hereby certify that the forego	RIH w/160 jts 4-1/2" 10.5 J-5 8 cf - 5 bbls) Class H cement blug w/1050# @ 1400 hrs 3/2 alts of the PT & TOC will be	55 casing and 31 jts 4-1/2" 11.6#, J-5 w/287 sx (568 cf - 102 bbls) Premiu 8/09. WOC. ND BOP, RD & relea	5 casing m Lite H	& landed @ 7915'. RU to cement. IS FM cement. Dropped plug and
Signed Falsy Clls	Patsy Cl	ugston Title Sr. Regulat	ory Spe	<u>cialist</u> Date <u>4/1/2009</u>
(This space for Federal or State Office use)  APPROVED BY				DEFEPTED FOR RECORD
CONDITION OF APPROVAL, if any:  Title 18 U.S.C Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any talse, fictitious or fraudulent statements or representations as to any matter within its jurisdiction				APR 1 3 2009
NWOCD #6				FARMINGTON FIELD OFFICE BY TL SALVERS