AMENDED CORRECT OPERATOR NAME

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	Sundry Notices and Reports on Wells		_
1.	Type of Well GAS	RECEIVE SAPR 0 8 2009	Lease Number SF-078498 If Indian, All. or Tribe Name
2.	Name of Operator	7. Bureau of Land Managem Farmington Field Office	Unit Agreement Name
	ConocoPhillips	тымуу, .	•
3.	Address & Phone No. of Operator	. 8.	Well Name & Number San Juan 28-7 Unit 230
	PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
4.	Location of Well, Footage, Sec., T, R, M Surf: Unit H (SE/NE), 2505' FNL & 1265' FEL, Section 29, T28N, R7W, NMPM		30-039-30610
~			Basin DK/Blanco MV County and State Rio Arriba, NM
12.	CHECK APPROPRIATE BOX TO INDICATE NATURE OF NO	TICE, REPORT, OTHE	R DATA
	Recompletion	Change of Plans X New Construction Non-Routine Fracturing Water Shut off Conversion to Injection	Other - Casing Report RCVD APR 15'09 OIL CONS. DIV. DIST. 3
3/19 of 7 10b 134 50:5 bbls 3/23 3/24 50:5 antii	3. Describe Proposed or Completed Operations /19/2009 NU BOP. RIH w/ 8 ¾" bit & tag cmt, D/O cmt and drilled ahead to 3092' Int TD on 3/20/2009. Circ Hole. RIH w/74 jn f 7" csg, 20#, J-55 ST&C set @ 3085' RU CMT. 3/22/2009 Preflushed w/10bbls GW & 10 bbls FW. Pumped Scavenger 15sx(50 0bbl) 75% TypeXI /25% Class G Cement, .25 lb/sx Cello Flake, 3% Sod Medasilicate, .20% Antifoam. Pumped Lead 358sx(7520 34bbl) Class G Cement, .25 lb/sx Cello Flakes, 3% Sod Medasilicate, .20% Antifoam. Pumped Tail w/ 81sx(102cf-18bbl) w/ 0:50POZ/, .25 lb/sk CellFlake, 5lb/sk Gilson, 2% Bentonite, 2%CaCL, .15% Friction Red, .1% D46. Drop plug & displace w/ 123 bls of FW. Circ 50bbls cmt to surface, bump plug @ 1745hrs on 3/22/2009. WOC. /23/2009 @ 0200 hrs PT csg 1500#/30min, ok. 3/23/2009 RIH w/ 6 ¼" bit & tag cmt, D/O cmt and drilled ahead to TD 7291' on /24/2009. Circ hole. RIH w/164 Jnts of 4 ½" csg, 10.5#, J-55 & 13 Jnts of 4 ½", 11.6#, J-55 ST& C set at 7288'. RU cement. /25/2009 Preflushed w/ 10bbls CW & 2bbls FW. Pumped Scavenger 16sx(28cf-5bbl) 50:50 POZ Cement, .25 lb/sk Cellophane Flake, 5 lb/sk Kolite, 3.5% Bentonite, .25% FL, .15% Friction Red, .15% retarder, .1% antifoam. Pumped Tail 410sx(590cf-105bb 0:50 POZ Cement, .25 lb/sk Cellophane Flake, 5 lb/sk Kolite, 3.5% Bentonite, .25% FL, .15% Friction Red, .15% retarder, .1% ntifoam. Drop plug & displace w/ 106bbls FW. Bump plug. Plug down @ 0106hrs on 3/25/2009. RD&RR on 3/26/2009 T will be conducted by completion rig; results and TOC will appear on next report.		
Sign		Fitle Staff Regulatory Tech	hnician Date <u>4/8/2009</u>
API CO:	is space for Federal or State Office use) PROVED BY	f	APR 1 3 2009