

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

AMENDED  
RECEIVED

APR 16 2009

## Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator

**ConocoPhillips**

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Surf: Unit H (SE/NE), 1380' FNL & 220' FEL, Section 23, T28N, R7W, NMPM

Bureau of Land Management  
Farmington Field Office

5. Lease Number  
SF-079290-A

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name  
San Juan 28-7 Unit

8. Well Name & Number  
158M

9. API Well No.

30-039-30238

10. Field and Pool

11. Blanco MV/Basin DK  
County and State  
Rio Arriba, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

## Type of Submission

## Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Other - ☐ Casing Report

☒ Subsequent Report

☐ Recompletion

☐ New Construction

RCVD APR 22 '09

☐ Final Abandonment

☐ Plugging

☐ Non-Routine Fracturing

OIL CONS. DIV.

☐ Casing Repair

☐ Water Shut off

DIST. 3

☐ Altering Casing

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

3/30/2009 MIRU H&P 281, NU BOP. PT csg 600#/30 min. ok. RIH w/ 8 3/4" bit & tag cmt @ 65', D/O cmt and drilled ahead to 3550' Int TD on 4/2/2009. Circ Hole. RIH w/85 jnts of 7" csg, 20#, J-55 ST&C set @ 3539' RU CMT. 4/3/2009 Preflushed w/10bbbls GW & 10 bbls FW. Pumped Scavenger w/ 15sx(56cf-10bbl) w/ 75% Type XI / 25% Class G Cement w/ .25 lb/sx Cellophane Flakes, 3% Sodium Medasilicate, 20% Antifoam. Pumped Lead w/ 525sx(1118cf-199bbl) w/ 75% Type XI / 25% Class G Cement w/ .25 lb/sx Cellophane Flakes, 2% Sodium Medasilicate, 20% Antifoam. Pumped Tail w/ 84sx(116cf-21bbl) w/ 50:50 POZ Cement w/ .25 lb/sk Cellophane Flake, 5 lb/sk Gilsonite, 2% Bent, .15% Fric Reducer, .1% Antifoam. Drop plug & displace w/ 142bbbls of FW. ~~Circ 60bbbls cmt to surface.~~ Bump plug.

4/4/2009 @ 0030hrs PT csg 1500#/30min, ok. 4/4/2009 RIH w/ 6 1/4" bit & tag cmt, D/O cmt and drilled ahead to TD 7845' on 4/5/2009. Circ hole. RIH w/172 jnts of 4 1/2" csg, 10.5#, J-55, ST&C @ 7843'. RU cement. 4/7/2009 Pumped Scavenger w/ 15sx(27cf-5bbl) w/ 50:50 POZ Cement, .25 lb/sk Cellophane Flake, 5 lb/sk Kolite, 3.5% Bentonite, .25% FL, .15% FR, .15% Retarder, .1% Antifoam. Pumped Tail w/ 305sx(604cf-107bbl) w/ 50:50 POZ Cement, .25 lb/sk Cellophane Flake, 5 lb/sk Kolite, 3.5% Bentonite, .25% FL, .15% FR, .15% Retarder, .1% Antifoam. Drop plug & displace w/ 125 bbls FW. Bump plug. Plug down @ 0720hrs on 4/7/2009. RD&RR on 4/7/2009. ~~PT~~

PT will be conducted by completion rig; results and TOC will appear on next report.

14. I hereby certify that the foregoing is true and correct.

Signed

*Ethel Tally*

Ethel Tally

Title Staff Regulatory Technician

Date 4/15/2008

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any statement or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

Date

APR 23 2009

FARMINGTON FIELD OFFICE

BY *T. Salazar*