RECEIVED

submitted in lieu of Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

APR 2 7 2009

Sureau of Land Management Farmington Field Office

Sundry Notices and Reports on Wells		·
1. Type of Well GAS	5. 6.	Lease Number SF-080675 If Indian, All. or Tribe Name
2. Name of Operator BURLINGTON	7.	Unit Agreement Name San Juan 27-4 Unit
RESCURCES OIL & GAS COMPANY LP		
3. Address & Phone No. of Operator	- 8.	Well Name & Number San Juan 27-4 Unit 57I
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
4. Location of Well, Footage, Sec., T, R, M	10.	30-039-30494 Field and Pool
Surf: Unit F (SE/NW), 1432' FNL & 1983' FWL, Section 28, T27N, R4W, NMPM	11.	Basin DK/Blanco MV County and State Rio Arriba, NM
12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, O' Type of Submission Type of Action	THER I	DATA
Notice of Intent Abandonment Change of Plans Recompletion New Construction	<u>X</u>	Other – Casing Report RCVD MAY 1'09
X Subsequent Report Plugging Non-Routine Fracturing Casing Repair Water Shut off		OIL CONS. DIV.
Final Abandonment Altering Casing Conversion to Injection		DIST. 3
13. Describe Proposed or Completed Operations 4/15/2009 NU BOP. 4/16/2009 RIH w/8 ¾" bit & tag cmt. D/O cmt and drilled ahead to TD Int 3988' on of 7" csg, 20#, J-55 ST&C set @ 3973' w/ Stage tool @ 3086'. RU CMT. 4/18/2009 1st STAGE Preflushe Pumped Scavenger 20sx(60cf-11bbl) Premium Lite Cement, Pumped Lead 45sx(96cf-17bbl) Premium Lite Cello-Flake,5 pps LCM-1, 0.4% FL-52, 8 % Bentonite and 0.4% SMS. Pumped Tail 95sx(131cf-23bbl) w. pps Cello-Flake and 0.2% FL-52. Drop plug & displace w/50bbls FW. Open Stage Tool w/ 1960# and cire WOC 4/18/2009 2nd STAGE Preflushed w/ 10 bbls FW, 10 bbls GW. Pumped Scavenger 20sx(56cf-10bbl) w/Pr w/ 400sx(852cf-151bbl) w/ Premium Lite Cement w/ 3% CaCl, 0.25 pps Cello-Flake,5 pps LCM-1, 0.4% FDrop Plug & displace w/ 125bbls FW. Circ 45bbls cmt to surface. Bump plug & Close Stage Tool. Plug 64/19/2009 PT 7" Csg @ 1500#/30Min @ 2000 hrs, QK. 4/20/2009 RIH W 6½" bit & tag cmt, D/O cmt and to final TD @ 8200 on 4/21/2009. RIH w/ 23 jnts, 4½" csg, 11.6#, J-55, LT&C, 10 jnts, 4½" csg, 10.5#, 10.5#, J-55, ST&C set @ 8196'. RU cmt. 4/22/2009 Preflushed w/ 10bbls CW & 2bbls FW. Pumped Sca Lite HS FM Cement, Pumped Tail 305sx(604cf-107bbl) w/ Premium Lite HS FM Cement w/ 0.25pps Cello 1, 1% FL-52. Drop plug & displace w/ 130 bbls FW. Bump plug. Plug down @ 1400 hrs on 4/22/2009. PT will be conducted by Completion Rig. TOC and results will appear on next report. 1 14. I hereby certify that the foregoing is true and correct.	ed w/ 10 e Cement /Type I-I c. Circ 1 remium I fL-52, 89 down @ 0 d DV To J-55, LT venger w b-Flake, 0 RD&RR	bbls H2O, 10 bbls GW, w/ 3% CaCl, 0.25 pps I Cement w/ 1% CaCl, 0.25 bbls of cmt to surface. Lite Cement, Pumped Lead Bentonite and 0.4% SMS. 0310hrs. WOC ool @ 3086'. Drilled ahead &C, & 160 jnts, 4 ½" csg, 10sx(27cf-5bbl) Premium 0.3% CD-32, 6.25pps LCM-4/23/2009.
Signed Cthul Cally Ethel Tally Title Staff Regulatory	Technic	<u>Date 4/23/2009</u>
(This space for Federal or State Office use) APPROVED BY		ACCEPTED FOR RECORD Date APR 2 8 2009 FARMINGTON FIELD OFFICE BY IL SAMES