This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator BR	***			Leas	e Name	HANC	COCK	-1	,,		Well No. 4
Location of We	ell: Unit Lette	er <u>M</u>	Sec	23	Twp _	028N	R(ge	009W	API	# 30-045-07262
	Name of Reservoir or Pool				Type of Prod			Method of Prod			Prod Medium
Upper Completion	PC			Gas			Flow			Tubing	
Lower Completion	MV			Gas	Gas			Artificial Lift			Tubing
			F	Pre-Flow S	Shut-In	Pressu	re Data	1		1-11	
Upper Completion	Hour, Date, Shut-In 4/15/2009			Length	Length of Time Shut-In 175 hours			SI Press. PSIG		158	Stabilized?(Yes or No) Yes
Lower Completion	Hour, Date, Shut-In 4/15/2008			Length	Length of Time Shut-In			SI Press. PSIG		197	Stabilized?(Yes or No) Yes
				Flo	w Test	No 1					
Commenced	at:						oducing	(Upper	or Lower	r): Lov	ver
Time Lapsed Time			PRESSURE Proc			Prod	Zone				
(date/time)		Since*	U	oper zone	Lowe	r zone	Temperature		Remarks		
4/20/2009 8:27:00 AM			158	127		52	2 Flowed Mv zone		v zone to	o 127# PC zone held 158 #	
4/21/2009 12:49:00 PM			158	1	25	76		Flowed lower zone to 125 PSI uper zone stayed at 158 PSI.			
4/22/2009 7:20:00 AM			158	158 122		48				owing 122 psi upper PC osi, Line pressure at 121 psi.	
Production rate	e during test										
Oil:BPOD Based on:Bb			bls. In	ls. InHrs			Grav.			GOR	
Gas		MCFPD; 1	Test thru (C	Orifice or M	leter) _						
				/lid-Test S	Shut-In	Pressu	re Data				
Upper Completion	Hour, Date, Shut-In				Length of Time Shut-In			SI Press. PSIG			Stabilized?(Yes or No)
Lower Completion	Hour, Date, Shut-In			Length	Length of Time Shut-In			SI Press. PSIG			Stabilized?(Yes or No)
				(Continu	ue on re	everse s	side)				RCVD MAY 1'09

OIL CONS. DIV.

)3/8 ·5⁵596 1.25 3242 by p@3401

Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

Commenced at: Zone Producing (Upper or Lower)										
Time	Lapsed Time	<u> </u>	SURE	Prod Zone		<u> </u>				
(date/time)	Since*	Upper zone	Lower zone	Temperature	·	Remarks				
			ļ							
		+								
		,								
		_								
		-								
		+	,							
Production rate during	ng test									
Oil:BPC	BPOD Based on:		Hrs.		Grav.	GOR				
Gas	asMCFPD; Test thru (Orifice or Meter)									
Damada										
Remarks:										
I hereby certify that the information herein contained is true and complete to the best of my knowledge.										
Thereby Certify that t	MAY 0 5 2009	ontained is true	and complete	to the pest of	my knowledge.					
Approved:		20	Opera	tor: BR.						
New Mexico Oil (Conservation Division		Ву:	Brent Hottell						
By:	. Kout		Title	Multi-Skilled	Operator					
Dept	ity Cii & Gas Insp	ector,			· · · · · · · · · · · · · · · · · · ·					
Title:	District #3		Date:	Date: Thursday, April 30, 2009						

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- $6 \quad \text{Flow Test No} \quad 2 \text{ shall be conducted even though no leak was indicated during Flow Test No} \quad 1 \quad \text{Procedure for Flow Test No} \quad 2 \text{ is to be the same as for Flow Test No} \quad 1 \quad \text{except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced}$
- 7 Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

5 Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above